TOUGH. SMART. TAPPAN.

All packaged systems feature Anteater® or Anteater MC® Micro-Channel evaporator coils

Product Line Comfort otal ome



All gas furnaces feature **SmartLite® Control Boards**

Ľ FG7MQ 97+ AFUE Ultra High Efficiency, Fully Modulating, Condensing, Upflow/Horizontal Gas Furnace, iSEER® technology, iQ Drive® Ready, 60,000 - 120,000 BTUH Input, Variable-Speed Blower

95.1% Gas Furnaces

Ľ

SFFF

FG7T(C, L)-VS 95.1 AFUE Extra High Efficiency, Direct Vent or Non-Direct Vent, Condensing, 2-Stage (Upflow/Horizontal, Downflow) Gas Furnace, iSEER technology, iQ Drive Ready, 60,000 -120,000 BTUH Input, Variable-Speed Blower

FG7T(C, L)-FS

95.1 AFUE Extra High Efficiency, Direct Vent or Non-Direct Vent, Condensing, 2-Stage (Upflow/Horizontal, Downflow) Gas Furnace, iSEER EMC Blower technology, 60,000 - 120,000 BTUH Input



Furnaces

95 AFUE Extra High Efficiency, Direct Vent or Non-Direct Vent, Condensing, 1-Stage, (Upflow/Horizontal, Downflow) Gas Furnace, Multi-Speed PSC Blower Motor, (38,000 -120,000, 54,000

92.1% Gas **Furnaces**

FG7S(C, L) 92.1 AFUE Extra High Efficiency, Direct Vent or Non-Direct Vent, Condensing, 1-Stage, (Upflow/Horizontal, Downflow) Gas Furnace, Multi-Speed PSC Blower Motor, (38,000 -120,000, 54,000 - 120,000) BTUH

Jrive

SFF

80% Gas **Furnaces**

FG7T(A, K)-VS 80 AFUE High Efficiency, 2-Stage (Upflow/Horizontal, Downflow) Gas Furnace, iSEER technology, iQ Drive Ready, 60,000 -140,000 BTUH Input, Variable-Speed Blower

80% Gas **Furnaces**

FG7T(A, K)-FS 80 AFUE High Efficiency, 2-Stage (Upflow/Horizontal, Downflow) Gas Furnace, iSEER EMC Blower technology, 60,000 - 140,000 BTUH Input

SFFR

and in case

FG7S(A, K) 80 AFUE High Efficiency, 1-Stage, (Upflow/Horizontal,

Downflow) Gas Furnace, Multi-Speed PSC Blower Motor, (45,000 -126,000, 54,000 - 126,000) BTUH Input

Packaged Systems

> All gas/electric and iHybrid[™] packaged systems feature **SmartLite® Control Boards**



Speed Blower, Square Duct Connections, Convertible Airflow, 15 SEER, 81% AFUE, 12 EER, 2 - 5 Ton, 80,000 - 120,000 BTUH

Input

R6GI R6GI Ultra High Efficiency, Single Packaged Gas/Electric, iQ Drive Technology, functions with 2-Stage Gas Heat/ 5-Stage Cooling output from 2-Stage thermostat, Variable-Speed ECM Blower, Square Duct Connections, Convertible Airflow, 20 SEER, 81% AFUE, Up to 13 EER, 2 - 5 Ton, 80,000 -120,000 BTUH Input

DF6SF-B

Single Packaged

iHybrid Dual Fuel,

2-Stage Gas Heat/

2-Stage Cooling,

Variable-Speed

Blower, Square

Duct Connections,

Convertible Airflow,

15 SEER, 8.0 HSPF,

81% AFUE, 12 EER,

2 - 5 Ton, 80,000 -

R8HE-A

Single Packaged

Gas/Electric, 2-Stage

Heat, Variable-Speed

ECM Blower, Square

Duct Connections,

Convertible Airflow,

14 SEER, 95% AFUE,

up to 12 EER, 2 - 5 Ton,

60,000 - 96,000

Single Packaged

Duct Connections,

Gas/Electric, Square

Convertible Airflow,

11 EER, 2 - 5 Ton,

45,000 - 120,000

BTUH Input

14 SEER, 81% AFUE,

BTUH Input

R8GE

120,000 BTUH Input

IN CLASS

Packaged Systems



Hvbrid

Packaged Systems

P5RF-A Single Packaged Air Conditioner, 2-Stage, ECM Blower, Round Duct Connections, 15 SEER, 12 EER, 2 - 5 Ton

Q5RF-A Single Packaged Heat Pump, 2-Stage, ECM Blower, Round Duct Connections, 15 SEER, 8.0 HSPF, 12 EER, 2 - 5 Ton



P8SE

Single Packaged Air Conditioner, Square Duct Connections, Convertible Airflow, 14 SEER, up to 11.5 EER, 3, 4 and 5 Ton



Single Packaged Heat Pump, Square Duct Connections, Convertible Airflow, 14 SEER, 8.0 HSPF, 11 EER, 2 - 5 Ton

P7RE

Single Packaged Air Conditioner, Round Duct Connections, 14 SEER, 11 EER, 2 - 5 Ton

> Q7RE Single Packaged Heat Pump, Round Duct Connections, 14 SEER, 8.0 HSPF, 11 EER, 2 - 5 Ton



ENERGY STAR[®] certification is awarded to products designed to reduce energy consumption and utility costs.

To qualify, gas/electric, iHybrid, air

onditioner and heat pump packaged systems must have a Seasonal Energy Efficiency Ratio (SEER) rating of 14.0 or higher and an Energy Efficiency Ratio (EER) of 11.0 or higher. Packaged heat pumps must also have a Heating Seasonal Performance Factor (HSPF) of

Split system air conditioners and heat pumps must have a 14.5 SEER rating or higher and an EER of 12.0 or higher. Split system heat pumps must also have an HSPF of 8.2 or higher.

Tappan units offer a 10 year limited warranty on all parts when registered. Plus the Tappan Tough[™] Quality Pledge on select models, which states if within the first 10 years the compressor or furnace heat exchanger fails Tappan will replace the entire unit, registration required. ES/ET models carry a 1-year Quality Pledge when registered. Air handlers and coils carry a 5-year all parts limited warranty and when installed with a matched outdoor unit, will carry the outdoor system warranty. J model air conditioners carry a 5-year all parts limited warranty and a 5-year compressor warranty. See warranty for details.





Split System **Air Conditioners**

iQ

Drive

Ľ

FS4BI

Ultra High Efficiency, Up to 25.5 SEER, Air Conditioner, iQ Drive® Technology, 2, 3 and 4 Ton Capacity

Drive FS4BG

Ultra High Efficiency, 20 SEER, Air Conditioner, iQ Drive Technology, 2, 3, 4 and 5 Ton Capacity

FS4BF

Extra High Efficiency, Up to 16 SEER, 2-Stage, Air Conditioner, 2, 3, 4 and 5 Ton Capacity, Micro-Channel

ES6BF

Extra High Efficiency, Up to 16 SEER, 1-Stage, Air Conditioner, 2, 2-1/2, 3, 3-1/2 and 4 Ton Capacity, Micro-Channel

FS4BE/ES4BE

High Efficiency, Up to 15 SEER, Air Conditioner, 1-1/2 - 5 Ton Capacity, Micro-Channel

FS4BD/ES4BD

High Efficiency, Up to 14 SEER, Air Conditioner, 1-1/2 - 5 Ton Capacity, Micro-Channel

JS6BD

High Efficiency, Up to 14 SEER, Builder's Series, Air Conditioner, 1-1/2 - 3 Ton Capacity, Micro-Channel



www.tappan.net



Ľ Heat Pump, iQ Drive

Split System

Heat Pumps

Efficiency, Up to 22

SEER, 10.0 HSPF

FT4BI

Ultra High

iQ

Drive

)rive

Ľ, * Extra High Efficiency, Up to 16 SEER, 9.0 HSPF, 2-Stage, Heat Pump, 2, 3, 4 and 5

High Efficiency, Up to 15 SEER, 8.5 HSPF, Heat Pump, 1-1/2 - 5 Ton Capacity, Micro-

* FT4BF models only are rated ecoLogic



Air Handlers

B6VMAI iQ Drive Only, Multi-Poised, Vertical/ Horizontal, Upflow/ Downflow, Variable-Speed, Air Handler, Anteater[®], Electronic TXV

B6VMAX

Multi-Poised, Vertical/ Horizontal, Variable-Speed, Air Handler, TXV, Anteater

B6BMMX Multi-Poised, Vertical/ Horizontal, Multi-Speed, Air Handler, TXV, Anteater MC[®] Micro-Channel

B6BMM0 Multi-Speed, Multi-Poised, Air Handler, Anteater MC Micro-Channel

B6EMMX ECM Fixed-Speed Motor, Multi-Poised, Air Handler, TXV, Anteater MC Micro-Channel

B6VMMX ECM Variable-Speed Motor, Multi-Poised, Air Handler, TXV, Anteater MC Micro-Channel

B6BW Vertical Wall Mount, Air Handler, Anteater MC Micro-Channel

B6EW Vertical Wall Mount, Multi-Speed, ECM Motor, Air Handler, TXV, Anteater MC Micro-Channel

MB7BM

Multi-Poised, Multi-Speed Modular Blower (matched with a cased coil easily creates a 2 piece Air Handler)

MB7EM Energy Efficient Model

MB7VM Variable-Speed Model