

Ľ

Drive

SFFF

SFFR

|C

Drive

SEER

Total Home Comfort **Product Line**

96% AFUE Gas Furnaces

All gas furnaces feature SmartLite[®] Control Boards

FG7T(E. N)-VS 96% AFUE Extra High Efficiency, Direct Vent or Non-Direct Vent, Condensing, 2-Stage (Dedicated Upflow, Downflow), iQ Drive ready, 60,000 -120.000 BTUH Input. iSEER Variable-Speed Blower technology

FG7T(E, N)-FS 96% AFUE Extra High Efficiency, Direct Vent or Non-Direct Vent. Condensing, 2-Stage (Dedicated Upflow, Downflow), iSEER ECM Blower technology, 60.000 - 120.000 **BTUH** Input

95.1% AFUE **Gas Furnaces**

FG7TC-VS Ľ 95.1% AFUE Extra High Efficiency, Direct Vent or Non-Direct Vent, Condensing, 2-Stage Upflow/Horizontal, iSEER technology, iQ Drive Ready, 60,000 - 120,000 BTUH Input, Variable-Speed Blower

FG7TC-FS

95.1% AFUE Extra High Efficiency, Direct Vent or Non-Direct Vent, Condensing, 2-Stage Upflow/Horizontal, **iSEER ECM Blower** technology, 60,000 -120,000 BTUH Input



95% AFUE Gas Furnaces FG7S(D. M) 95% AFUE Extra High Efficiency, Direct Vent or Non-Direct Vent, Condensing, 1-Stage,

(Upflow/Horizontal. Downflow), Multi-Speed PSC Blower Motor, (38,000 - 120,000, 54,000 - 118,000) BTUH Input

92.1% AFUE **Gas Furnaces**

FG7S(C, L) 92.1% AFUE Extra High Efficiency, Direct Vent or Non-Direct Vent, Condensing, 1-Stage, (Upflow/Horizontal, Downflow), Multi-Speed PSC Blower Motor, (38,000 - 120,000, 54,000 - 120,000) BTUH Input

80% AFUE **Gas Furnaces**

FG7T(A, K)-VS 80% AFUE High Efficiency, 2-Stage (Upflow/Horizontal, Downflow), iSEER technology, iQ Drive Ready, 60,000 -140,000 BTUH Input, Variable-Speed Blower

FG7T(A, K)-FS 80% AFUE High Efficiency, 2-Stage (Upflow/Horizontal, Downflow), iSEER ECM Blower technology,

60,000 - 140,000 BTUH

FG7S(A, K)

Input

80 AFUE High Efficiency, 1-Stage (Upflow/Horizontal, Downflow), Multi-Speed PSC Blower Motor, (45,000 - 126,000, 54,000 - 126,000) **BTUH** Input

96% AFUE Gas Furnaces

KG7T(E, N)-FS

96% AFUE Extra High Efficiency, Direct Vent or Non-Direct Vent. Condensing. 2-Stage (Upflow/Horizontal, Downflow), iSEER ECM Blower technology, 60,000 - 120,000 BTUH Input SEEF

ISEER



KG7TC-FS 95.1% AFUE Extra High Efficiency, Direct Vent or Non-Direct Vent, Condensing, 2-Stage Upflow/Horizontal, iSEER ECM Blower technology, 60,000 - 120,000 BTUH Input

Up to 95.1% AFUE Gas Furnaces

KG7SD-E

Up to 95% AFUE Extra High Efficiency, Direct Vent or Non-Direct Vent. Condensing, 1-Stage Upflow/Horizontal, iSEER ECM Blower technology, 38,000 - 120,000 BTUH Input

95%/92.1% AFUE Gas Furnaces

KG7S(D,M)/KG7S(C, L) 95% AFUE/92.1% AFUE Extra High Efficiency, Direct Vent or Non-Direct Vent, Condensing, 1-Stage (Upflow/Horizontal. Downflow), Multi-Speed PSC Blower Motor, (38,000 - 120,000, 54,000 - 118,000)/ (38,000 - 120,000, 54,000 -

80% AFUE High Efficiency, 2-Stage (Upflow/Horizontal, Input

80% AFUE High Efficiency, 1-Stage (Upflow/Horizontal, Downflow), Multi-Speed PSC Blower Motor, (45,000 -126,000, 54,000 - 126,000) **BTUH** Input

Large Packaged Systems

All gas/electric and iHybrid[®] packaged systems feature SmartLite Control **Boards**

R6GI

Ultra High Efficiency, Gas/Electric, iQ Drive Technology, functions with 2-Stage Gas Heat/ 5-Stage Cooling output from 2-Stage thermostat. Variable-Speed ECM Blower, Square Duct Connections, Convertible Airflow, 20 SEER, 81% AFUE, Up to 13 EER, 2 - 5 Ton, 80,000 - 120,000 **BTUH** Input

R6GF-B

Gas/Electric, 2-Stage Heat & Cool, Variable-Speed Blower, Square Duct Connections, Convertible Airflow, 15 SEER, 81% AFUE, 12 EER, 2 - 5 Ton, 80,000 - 120.000 BTUH Input

-1st

DF6SF-B iHybrid Dual Fuel,

2-Stage Gas Heat/ 2-Stage Cooling, Variable-Speed Blower, Square Duct Connections, Convertible Airflow, 15 SEER. 8.0 HSPF. 81% AFUE, 12 EER, 2 - 5 Ton, 80,000 -120,000 BTUH Input

R8HE-A IN CLASS Gas/Electric, 2-Stage Heat, Square Duct Connections. Convertible Airflow, 14 SEER, 95% AFUE, up to 12 EER, 2 - 5 Ton. 60.000 -

96,000 BTUH Input

R8GE

Gas/Electric, Square Duct Connections, Convertible Airflow, 14 SEER, 81% AFUE, 11 EER, 2 - 5 Ton, 45.000 - 120.000 BTUH Input

All packaged Large Packaged systems

Systems continued feature enhanced P8SE all-aluminum Micro-Channel evaporator and condenser coils



-lvbrid

IN CLASS

Air Conditioner, Square Duct Connections. Convertible Airflow, 14 SEER, up to 11.5 EER, 3, 4 and 5 Ton





Small Packaged Systems

P7RF Air Conditioner, Micro-Channel coil technology inside and out, 2-Stage cooling, 5 speed ECM Blower, Round Duct Connections, 16 SEER, 12 EER, 2 - 5 Ton



Q7RF

Heat Pump, Micro-Channel coil technology inside and out, patented hot gas bypass defrost technology, 2-Stage heating and cooling, 5 speed ECM Blower, Round Duct Connections, 16 SEER, 8.2 HSPF, 12 EER, 2 - 5 Ton



P7RE Air Conditioner, Round Duct Connections, 14 SEER, 11 EER, 2 - 5 Ton

Q7RE Heat Pump, Round Duct Connections, 14 SEER, 8.0 HSPF, 11 EER. 2 - 5 Ton





ENERGY STAR® certification is awarded to products designed to reduce energy consumption and utility costs.

To qualify, packaged systems must have a Seasonal Energy Efficiency Ratio (SEER) rating of 15.0 or higher and an Energy Efficiency Ratio (EER) of 12.0 or higher. Packaged heat pumps must also have a Heating Seasonal Performance Factor (HSPF) of 8.2 or higher

Gas furnaces must have an AFUE of 95% or higher for northern states, at least 90% AFUE for southern states, have an approved energy efficient blower motor and cabinet air leakage of less than or equal to 2%

Split system air conditioners and heat pumps must have a 15.0 SEER rating or higher and an EER of 12.5 or higher. Split system heat pumps must also have an HSPF of 8.5 or higher



SFFF

120,000) BTUH Input 80% AFUE Gas

KG7T(A, K)-FS Downflow), iSEER ECM Blower technology,

KG7S(A, K)

i Drive

SEEF

ISEEF

Furnaces

60,000 - 140,000 BTUH



WESTINGHOUSE and INNOVATION YOU CAN BE SURE OF are trademarks of Westinghouse Electric Corporation. Used under license All Rights Reserved. © Nortek Global HVAC, LLC 2017.

124C-0717

www.westinghousehvac.com

iHybrid®, iSEER®, iQ Drive®, ecoLogic® and SmartLite® are registered trademarks of Nortek Global HVAC, LLC Specifications and illustrations subject to change ithout notice and without incurring obligation

Modular Energy Efficient Model MB7VM Modular Variable-Speed

Model

MB7EM

to maintain, 24V,

1" Electronic, Easy 95% efficient down to .01 microns

HEPA, High efficiency air filtration, captures 99.97% of harmful airborne pollutants Thermostats Universal, Programmable 7-day, 24V, digital, up to 3 heat/2 cool, backlit display + keypad, auto or manual changeover



O-YEAF

QUALIT

PLEDGE

ANDROW

WARRANTY

UV Air Treatment Systems UV object purifiers and Photo Catalytic Oxidation (PCO) units remove mold, bacteria, and viruses that are found in the air stream and also remove odors from the home.

parched, dry air which can cause throat, itchy & dry

.. Total comfort for creating custom comfort zones