BR Product Line **HEATING AND COOLING SYSTEMS**

97+% GAS **FURNACES**

All gas furnaces feature SmartLite® **Control Boards**

ISEER

Drive

Barris and

SEER

Drive

Statistics.

ISEER

Contra of

Section 2

San (194

FG7MQ 97+ AFUE Ultra High Efficiency, Fully Modulating, Condensing, Upflow/Horizontal Gas Furnace, iSEER[®] technology, iQ Drive[®] Ready, 60.000 - 120.000 BTUH Input, Variable-Speed Blower

95.1% GAS **FURNACES**

FG7T(C, L)-VS 95.1 AFUE Extra High Efficiency, Direct Vent or Non-Direct Vent, Condensing, 2-Stage (Upflow/Horizontal, Downflow) Gas Furnace, iSEER technology, iQ Drive Ready, 60,000 - 120,000 BTUH Input, Variable-Speed Blower

FG7T(C, L)-FS

95.1 AFUE Extra High Efficiency, Direct Vent or Non-Direct Vent, Condensing, 2-Stage (Upflow/Horizontal, Downflow) Gas Furnace, **iSEER ECM** Blower technology, 60,000 - 120,000 **BTUH** Input

95% GAS FURNACES FG7S(D, M)

95 AFUE Extra High Efficiency, Direct Vent or Non-Direct Vent, Condensing, 1-Stage (Upflow/Horizontal, Downflow) Gas Furnace, Multi-Speed PSC Blower Motor, (38,000 - 120,000, 54,000 -118,000) BTUH Input

Contra to

ISEER

i R Drive

Const.

(States of the second s

92.1% GAS FURNACES

FG7S(C, L) 92.1 AFUE Extra High Efficiency, Direct Vent or Non-Direct Vent, Condensing, 1-Stage (Upflow/Horizontal, Downflow) Gas Furnace, Multi-Speed PSC Blower Motor, (38,000 - 120,000, 54,000 -120,000) BTUH Input

80% GAS FURNACES

FG7T(A, K)-VS 80 AFUE High Efficiency, 2-Stage (Upflow/Horizontal, Downflow) Gas Furnace, iSEER technology, iQ Drive Ready, 60,000 - 140,000 BTUH Input, Variable-Speed Blower

FG7T(A, K)-FS 80 AFUE High

Efficiency, 2-Stage (Upflow/Horizontal, Downflow) Gas Furnace, **iSEER ECM Blower** technology, 60,000 -140,000 BTUH Input

FG7S(A, K)

80 AFUE High Efficiency, 1-Stage (Upflow/ Horizontal, Downflow) Gas Furnace, Multi-Speed PSC Blower Motor, (45,000 - 126,000, 54,000 - 126,000) **BTUH** Input

95.1% GAS FURNACES

ÍSEER

ÍSEER

KG7T(C, L)-FS 95.1 AFUE Extra High Efficiency. Direct Vent or Non-Direct Vent. Condensing, 2-Stage (Upflow/Horizontal, Downflow) Gas Furnace, iSEER ECM Blower technology, 60,000 - 120,000 **BTUH** Input

95%/92.1% GAS **FURNACES**

KG7S(D,M)/KG7S(C, L) 95 AFUE/92.1 AFUE Extra High Efficiency. Direct Vent or Non-Direct Vent, Condensing, 1-Stage (Upflow/Horizontal, Downflow) Gas Furnace, Multi-Speed PSC Blower Motor, (38.000 - 120.000. 54.000 - 118.000)/ (38,000 - 120,000,54,000 - 120,000) **BTUH Input**

80% GAS FURNACES

KG7T(A. K)-FS

80 AFUE High Efficiency, 2-Stage (Upflow/Horizontal. Downflow) Gas Furnace, iSEER ECM Blower technology. 60,000 - 140,000 **BTUH** Input

KG7S(A, K)

80 AFUE High Efficiency, 1-Stage (Upflow/Horizontal, Downflow) Gas Furnace, Multi-Speed PSC Blower Motor, (45,000 - 126,000 54.000 - 126.000) **BTUH** Input

All packaged systems feature Anteater® or Anteater MC® Micro-Channel evaporator coils

PACKAGED SYSTEMS

All gas/electric and iHybrid[™] packaged systems feature SmartLite Control Boards

R6GI

Ultra High Efficiency. Single Packaged Gas/Electric, iQ Drive® Technology, functions with 2-Stage Gas Heat/5-Stage Cooling output from 2-Stage thermostat, Variable-Speed ECM Blower, Square Duct Connections, Convertible Airflow, 20 SEER, 81% AFUE, Up to 13 EER, 2 - 5 Ton, 80,000 - 120,000 **BTUH** Input

Ľ

Ľ

Drive

R6GF-B

Single Packaged Gas/ Electric, 2-Stage Heat & Cool, Variable-Speed Blower. Square Duct Connections, Convertible Airflow, 15 SEER, 81% AFUE, 12 EER, 2 - 5 Ton, 80,000 - 120,000 **BTUH** Input

DF6SF-B

Single Packaged iHybrid Dual Fuel, 2-Stage Gas Heat/2-Stage Cooling, Variable-Speed Blower, Square Duct Connections, Convertible Airflow, 15 SEER, 81% AFUE, 8.0 HSPF, 12 EER, 2 - 5 Ton, 80,000 - 120,000 BTUH Input



Electric, 2-Stage Heat, Square Duct Connections, 95% AFUE, up to 12 EER. 2 - 5 Ton, 60,000 -96,000 BTUH Input

PACKAGED SYSTEMS



Single Packaged Gas/Electric, Square Duct Connections, Convertible Airflow, 14 SEER,81% AFUE, 11 EER, 2 - 5 Ton, 45,000 - 120,000 **BTUH Input**



P5RF-A/Q5RF-A

Single Packaged Air Conditioner/Heat Pump, 2-Stage, ECM Blower, Round Duct Connections, 15 SEER/8.0 HSPF, 12 EER, 2 - 5 Ton



P8SE/Q6SE

Single Packaged Air Conditioner/Heat Pump, Square Duct Connections, Convertible Airflow, 14 SEER/8.0 HSPF, up to 11.5 EER/11 EER, 3, 4 and 5 Ton



P7RE/Q7RE

Single Packaged Air Conditioner\Heat Pump, Round Duct Connections, 14 SEER/8.0 HSPF, 11 EER, 2 - 5 Ton



ENERGY STAR[®] certification is awarded to products designed to reduce energy consumption and utility costs.

ENERGY STAR PARTNER To qualify, gas/electric, iHybrid, air conditioner and heat pump packaged systems must have a Seasonal Energy Efficiency Ratio (SEER) rating of 14.0 or higher and an Energy Efficiency Ratio (EER) of 11.0 or higher. Packaged heat pumps must also have a Heating Seasonal Performance Factor (HSPF) of 8.0 or higher.

Split system air conditioners and heat pumps must have a 14.5 SEER rating or higher and an EER of 12.0 or higher. Split system heat pumps must also have an HSPF of 8.2 or higher.



Hybrid





Variable-Speed ECM Blower, Convertible Airflow, 14 SEER,

BROAN UNITS OFFER A 10-YEAR LIMITED WARRANTY ON ALL PARTS WHEN REGISTERED. PLUS THE BROAN QUALITY PLEDGE ON SELECT MODELS, WHICH STATES IF WITHIN THE FIRST 10 YEARS THE COMPRESSOR OR FURNACE HEAT EXCHANGER FAILS BROAN WILL REPLACE THE ENTIRE UNIT, REGISTRATION REQUIRED. AIR HANDLERS AND COILS CARRY A 5-YEAR ALL PARTS LIMITED WARRANTY AND WHEN INSTALLED WITH A MATCHED OUTDOOR UNIT. WILL CARRY THE OUTDOOR SYSTEM WARRANTY. SEE WARRANTY FOR DETAILS.

i Drive

٠





HEATING AND COOLING SYSTEMS

SPLIT SYSTEM **AIR CONDITIONERS**

Extra High Efficiency, Up to 15 SEER, Air Conditioner, 1-1/2 - 5 Ton Capacity, Micro-Channel

High Efficiency, Up to 14 SEER, Air Conditioner, 1-1/2 - 5 Ton Capacity, Micro-Channel

SPLIT SYSTEM HEAT PUMPS

FT4BI Ultra High Efficiency, Up to 22 SEER, 10.0 HSPF, Heat Pump, iQ Drive® Technology, 2, 3 and 4 Ton Capacity



i Drive

Broan® trademark used under license. iSEER®, iQ Drive®, ecoLogic®, SmartLite®, Anteater® and Anteater MC[®] are registered trademarks of Nortek Global HVAC LLC. iHybrid™ is a trademark of Nortek Global HVAC LLC. © Nortek Global HVAC LLC 2015. All Rights Reserved. 164D-0315



FT4BE High Efficiency, Up to 15 SEER. 8.5 HSPF, Heat Pump, 1-1/2 - 5 Ton Capacity, Micro-Channel

AIR HANDLERS

B6VMAI iQ Drive Only, Multi-Poised, Vertical/Horizontal, Upflow/Downflow, Variable-Speed, Air Handler, Anteater®, Electronic TXV

B6VMAX

Multi-Poised. Vertical/Horizontal, Variable-Speed, Air Handler, TXV, Anteater

Multi-Poised, Vertical/Horizontal, Multi-Speed, Air Handler, TXV, Anteater MC® Micro-Channel

B6BMMO Multi-Poised, Multi-Speed, Air Handler, Anteater MC Micro-Channel

B6EMMX ECM Fixed-Speed Motor, Multi-Poised, Air Handler, TXV, Anteater MC Micro-Channel

B6VMMX

ECM Variable-Speed Motor, Multi-Poised, Air Handler, TXV, Anteater MC Micro-Channel

B6BW

Vertical Wall Mount, Air Handler, Anteater MC Micro-Channel

B6EW

Vertical Wall Mount, Multi-Speed, ECM Motor, Air Handler, TXV, Anteater MC Micro-Channel

AIR HANDLERS

MB7BM Multi-Poised, Multi-Speed Modular Blower (matched with a cased coil easily creates a 2 piece Air Handler)

MB7EM **Energy Efficient** Model



INDOOR COILS

C7B(A.H)MOAnteater MC Micro-Channel

A, B, C and D sizes available in various capacities

Cased & Vertical/ Horizontal, Multi-poised versions available

C7BHMX

TXV, Anteater MC Micro-Channel A. B. C and D sizes available in various capacities Cased Horizontal





Cased Horizontal

Factory-installed

B6BMMX