

TECHNICAL SPECIFICATIONS

FT4BE Series

R-410A High Efficiency Heat Pump

14 SEER Residential System 1 1/2 – 5 Ton Capacity

FT4BE Series now offers the choice of a heat pump that uses a more efficient and environmentally friendly refrigerant designated R-410A. The FT4BE Series of heat pumps offers exceptional performance. The unit, when combined with our engineered coils or air handlers, offers a full line of quality, split system cooling equipment.




WARRANTY

- This product offers a 10-year all-parts warranty.
- This product offers a 10 year Quality Pledge to replace the entire unit, if the unit's major component (heat exchanger or compressor) fails within the first 10 years of operation, to the original owner. All split system products must be installed with a matched indoor air handler or indoor coil to qualify.
- Consumer product registration required for both 10 year All Parts Warranty and Quality Pledge within a limited period of time after the installation. See current warranty document or visit our consumer web site listed on the back of this document for warranty details.

FEATURES and BENEFITS

- **R-410A Refrigerant** – Earth friendly non-ozone depleting refrigerant.
- **Designed using galvanized steel** – with a polyester urethane coat finish. The 950 hour salt spray finish resists corrosion 50% better than comparable units.
- **Copper Tube / Aluminum Fin Coils** – Both indoor and outdoor coils are designed to optimize heat transfer, minimize size and cost, and increase durability and reliability.
- **Permanently Lubricated Motor** – A heavy duty PSC motor for long lasting reliability and quiet operation. Requires no maintenance and is completely protected from rain and snow.
- **Composite Base Pan** – Absorbs sound and is corrosion resistant. Composite is also stronger and lighter than steel.
- **Louvered Condenser Guard** – Durable metal guard protects the coil from yard hazards and extreme weather.
- **Removable Top Grille Assembly** – Allows ease of service from the top without disconnecting fan motor leads.
- **Swept-Wing Fan Blade** – Designed to significantly reduce unwanted noise.
- **High Pressure Switch** – Protects against abnormally high system pressures. Auto-reset feature prevents nuisance service visits.
- **Low Pressure Switch** – Loss charge protection ensures long compressor life. Auto-reset feature prevents nuisance service trips.
- **Liquid Line Filter Drier** – Included with unit, field installed.
- **One Piece Top/Orifice** – Designed for maximum airflow and quiet operation.
- **Five Minute Restart Time Delay** – When the unit shuts down, a five minute delay keeps the unit from restarting, eliminating the highest cause for compressor failure.
- **Easy Compressor and Control Access** – Designed to make servicing easier for the contractor, access panels are provided to all controls and the compressor from the side of the unit.
- **Fixed Orifice** – Integrated in liquid line service valve for easy change-out.


MODEL IDENTIFICATION CODES



DIMENSIONS

AIR CONDITIONER OUTDOOR SECTION

FT4BE	018K	024K	030K	036K	042K	048K	060K
H	45	45	45	45	45	45	45
W	31 1/4	31 1/4	31 1/4	31 1/4	31 1/4	31 1/4	31 1/4
D	31 1/4	31 1/4	31 1/4	31 1/4	31 1/4	31 1/4	31 1/4



PHYSICAL AND ELECTRICAL SPECIFICATIONS / OUTDOOR UNITS

14 SEER — High Efficiency — Single Phase

Model Number FT4BE		018K	024K	030K	036K	042K	048K	060K	
Electrical Data	Volts-Cycles-Phase (1)	208/230-60-1	208/230-60-1	208/230-60-1	208/230-60-1	208/230-60-1	208/230-60-1	208/230-60-1	
	Total Amps	11.86	16.34	15.7	16.98	20.82	21.24	27.64	
	Delay Fuse Max. (2)	20	30	30	30	40	45	60	
	Min. Circuit Ampacity	14.1	19.7	18.9	20.5	25.3	26.2	34.2	
Condenser Data	Coil	Area ft ²	25.4	25.4	25.4	25.4	25.4	25.4	25.4
		Rows-FPI	1-20	1-20	1-20	1-20	2-16	2-16	2-16
		Tube Dia	3/8" O.D.	3/8" O.D.	3/8" O.D.	3/8" O.D.	3/8" O.D.	3/8" O.D.	3/8" O.D.
	Fan Motor	Type	BLDC	BLDC	BLDC	BLDC	BLDC	PSC	PSC
		Amps	2.9	2.9	2.9	2.9	2.9	1.4	1.4
		Watts-HP	1/3	1/3	1/3	1/3	1/3	1/4	1/4
	Fan Blade	Dia-# Blades	24"-2	24"-2	24"-2	24"-2	24"-2	24"-2	24"-2
		SCFM	2800	2800	2800	3400	4000	4000	4000
	Compressor Data	RLA	8.96	13.44	12.8	14.08	17.92	19.84	26.24
		LRA	48	58.3	64	77	112	109	134
Refrigerant suction line O.D.(all length of liquid line are 3/8" O.D.)	0-24 ft.	3/4"	3/4"	3/4"	7/8"	7/8"	7/8"	7/8"	
	25-39 ft.	3/4"	3/4"	3/4"	7/8"	7/8"	1 1/8" (3)	1 1/8" (3)	
	40-75 ft.	3/4"	3/4"	3/4"	7/8"	7/8"	1 1/8" (3)	1 1/8" (3)	
Weight Approximate (lbs.)	Net	179	180	180	182	279	280	290	
	Ship	188	189	189	191	294	295	305	
Sound Ratings db		68	68	68	70	70	72	72	

(1) Operating Voltage Range: 187V min.- 253V max.

(2) HACR Type Circuit Breaker may be used.

(3) Requires 7/8" to 1-1/8" reducer from line to unit.

ACCESSORIES - Condensing Unit

Start Assist Kit - 912933

Provides additional starting torque for the compressor motor when operating with low line voltage or high operating temperatures.

SYSTEM HEATING AND COOLING CAPACITIES

14+ SEER — High Efficiency — Single Phase

Outdoor Unit	Indoor Unit	BTUH	SEER	EER	Heating Capacity BTUH @ 47 F	HSPF	CFM
FT4BE-018K	C7B(A,H)M01824(C,U)-A + TXV	18,000	14.00	12.20	19,000	8.2	665
FT4BE-018K	C7B(A,H)M01824(C,U)-B + TXV	18,000	14.00	12.20	19,000	8.2	655
FT4BE-024K	C7B(A,H)M01824(C,U)-A + TXV	22,800	14.00	12.20	25,000	8.2	755
FT4BE-024K	C7B(A,H)M01824(C,U)-B + TXV	22,800	14.00	12.20	25,000	8.2	830
FT4BE-030K	C7B(A,H)M03036(C,U)-A + TXV	28,200	14.00	12.20	29,200	8.2	990
FT4BE-030K	C7B(A,H)M03036(C,U)-B+TXV	28,200	14.00	12.20	29,200	8.2	990
FT4BE-030K	C7B(A,H)M030(C,U)-C + TXV	28,200	14.00	12.20	29,200	8.2	990
FT4BE-036K	C7B(A,H)M03642(C,U)-B + TXV	34,400	14.00	12.20	35,800	8.2	1215
FT4BE-036K	C7B(A,H)M03648(C,U)-C + TXV	34,400	14.00	12.20	35,800	8.2	1215
FT4BE-042K	C7B(A,H)M03642(C,U)-B + TXV	40,000	14.00	12.00	41,500	8.2	1360
FT4BE-042K	C7B(A,H)M03648(C,U)-C + TXV	40,000	14.00	12.00	41,500	8.2	1360
FT4BE-042K	C7B(A,H)M042(C,U)-D + TXV	40,000	14.00	12.00	41,500	8.2	1360

Outdoor Unit	Indoor Unit	BTUH	SEER	EER	Heating Capacity BTUH @ 47 F	HSPF	SCFM
FT4BE-018K	B6BM-X24K-A	18,000	14.0	12.2	19,000	8.2	675
FT4BE-018K	B6BM-X24K-B	18,000	14.0	12.2	19,000	8.2	675
FT4BE-024K	B6BM-X24K-A	23,200	14.0	12.2	25,000	8.2	700
FT4BE-024K	B6BM-X24K-B	23,200	14.0	12.2	25,000	8.2	700
FT4BE-030K	B6BM-X30K-A	27,600	14.0	12.2	28,200	8.2	905
FT4BE-030K	B6BM-X30K-B	27,600	14.0	12.2	28,200	8.2	905
FT4BE-036K	B6EMMX36K-B	34,200	15.0	12.5	34,200	8.5	1270
FT4BE-042K	B6BM-X42K-B	39,000	14.0	11.0	39,000	8.2	1340
FT4BE-048K	B6BM-X60K-C	45,500	14.0	12.2	44,000	8.2	1575
FT4BE-060K	B6EMMX60K-C	58,000	14.1	11.5	60,000	8.5	1710

Outdoor Unit	Indoor Unit	BTUH	SEER	EER	Heating Capacity BTUH @ 47° F	HSPF	SCFM
FT4BE-018K	B6EMMX24K-A	17400	15.00	12.50	18900	8.50	560
FT4BE-018K	B6EMMX24K-B	18900	15.00	12.50	19900	8.50	670
FT4BE-024K	B6EMMX24K-A	22800	15.00	12.50	25400	8.50	740
FT4BE-024K	B6EMMX24K-B	23000	15.00	12.50	24800	8.50	690
FT4BE-030K	B6EMMX30K-A	28600	15.00	12.50	29400	8.50	1070
FT4BE-030K	B6EMMX30K-B	28000	15.00	12.50	28400	8.50	1030
FT4BE-036K	B6EMMX36K-B	34200	15.00	12.50	34200	8.50	1270
FT4BE-042K	B6EMMX42K-B	40000	15.00	12.50	42000	8.50	1500
FT4BE-042K	B6EMMX48K-C	40000	15.00	12.50	41000	8.50	1405
FT4BE-048K	B6EMMX48K-C	45500	15.00	12.50	46500	8.50	1660
FT4BE-060K	B6EMMX60K-C	58000	14.10	11.50	60000	8.50	1710

Outdoor Unit	Indoor Unit	BTUH	SEER	EER	Heating Capacity BTUH @ 47°F	HSPF	SCFM
FT4BE-018K	B6VMAX24K-(A,B)	19000	15.0	13.5	18800	8.5	675
FT4BE-024K	B6VMAX24K-(A,B)	23400	15.0	13.5	24600	8.6	675
FT4BE-030K	B6VMAX30K-B	28400	15.0	13.5	29400	8.7	960
FT4BE-036K	B6VMAX36K-B	34800	15.0	13.5	33600	8.8	1125
FT4BE-042K	B6VMAX48K-C	40000	15.5	14.0	38000	9.0	1300
FT4BE-048K	B6VMAX48K-C	45500	14.0	12.6	44000	8.5	1660
FT4BE-060K	B6VMAX60K-C	59000	14.0	12.5	52500	8.5	1660

All ratings are with time delay relay.

See current AHRI Directory for certified combinations and ratings.

www.ahridirectory.org

14 SEER COOLING EXPANDED RATINGS - LOOSE COIL

FT4BE-018K C7B(A,H)M01824(C,U)-A + TXV Kit

CFM	O.D.T		65°F			75°F			85°F			95°F			105°F			115°F		
	E.D.B.	E.W.B.	T.C.	S.C.	K.W.	T.C.	S.C.	K.W.	T.C.	S.C.	K.W.	T.C.	S.C.	K.W.	T.C.	S.C.	K.W.	T.C.	S.C.	K.W.
525	80	62	18.7	14.8	0.99	18.0	14.6	1.13	17.2	14.7	1.26	16.4	14.4	1.41	15.52	15.18	1.56	14.58	14.26	1.74
	80	67	20.5	12.0	0.98	19.6	11.9	1.12	18.8	12.0	1.26	17.9	11.7	1.41	16.87	11.53	1.57	15.81	10.73	1.75
	80	72	22.8	9.3	0.97	21.9	9.3	1.11	20.9	9.5	1.26	19.8	9.3	1.41	18.69	9.11	1.57	17.44	9.32	1.75
	75	63	18.9	11.6	0.99	18.1	11.5	1.12	17.3	11.6	1.26	16.5	11.3	1.41	15.58	10.35	1.56	14.57	11.12	1.74
600	80	62	19.3	15.9	1.02	18.5	16.2	1.15	17.7	15.8	1.29	16.8	15.7	1.43	16.05	15.50	1.59	15.18	15.05	1.77
	80	67	21.0	12.8	1.01	20.1	13.1	1.15	19.2	12.7	1.29	18.2	12.6	1.43	17.17	12.54	1.60	16.08	12.49	1.77
	80	72	23.3	9.9	1.00	22.3	10.3	1.14	21.2	10.0	1.29	20.1	9.9	1.44	18.66	9.91	1.60	17.44	9.88	1.78
	75	63	19.4	12.3	1.02	18.6	12.6	1.15	17.7	12.2	1.29	16.8	12.1	1.43	15.86	12.00	1.59	14.83	11.91	1.77
675	80	62	19.7	17.2	1.04	18.9	17.3	1.17	18.2	16.9	1.31	17.4	16.5	1.46	16.56	16.00	1.62	15.64	15.57	1.80
	80	67	21.4	13.7	1.03	20.5	13.8	1.17	19.5	13.5	1.31	18.5	13.4	1.46	17.44	13.24	1.62	16.29	13.24	1.80
	80	72	23.7	10.6	1.02	22.6	10.8	1.17	21.2	10.5	1.31	20.1	10.4	1.47	18.90	10.29	1.63	17.65	10.33	1.81
	75	63	19.8	13.2	1.04	18.9	13.3	1.17	18.0	12.9	1.31	17.1	12.8	1.46	16.10	12.65	1.62	15.02	12.61	1.80

FT4BE-024K C7B(A,H)M01824(C,U)-B + TXV Kit

CFM	O.D.T		65°F			75°F			85°F			95°F			105°F			115°F		
	E.D.B.	E.W.B.	T.C.	S.C.	K.W.	T.C.	S.C.	K.W.	T.C.	S.C.	K.W.	T.C.	S.C.	K.W.	T.C.	S.C.	K.W.	T.C.	S.C.	K.W.
700	80	62	23.7	19.0	1.31	22.8	18.8	1.47	21.8	18.9	1.63	20.7	18.6	1.81	19.63	19.27	2.01	18.58	18.24	2.23
	80	67	25.7	15.3	1.31	24.7	15.1	1.47	23.6	15.3	1.64	22.4	15.0	1.82	21.19	14.69	2.02	19.87	13.86	2.24
	80	72	28.6	11.9	1.30	27.3	11.8	1.47	26.1	12.0	1.64	24.7	11.8	1.83	23.25	11.58	2.03	21.50	11.81	2.25
	75	63	23.8	14.8	1.31	22.9	14.6	1.47	21.9	14.7	1.63	20.8	14.4	1.81	19.62	13.22	2.01	18.38	14.19	2.23
800	80	62	24.3	20.4	1.35	23.3	20.8	1.50	22.3	20.4	1.67	21.3	20.0	1.85	20.34	19.66	2.05	19.24	19.07	2.27
	80	67	26.3	16.2	1.34	25.2	16.7	1.50	24.1	16.2	1.67	22.8	16.0	1.86	21.54	15.97	2.05	20.17	15.90	2.28
	80	72	29.1	12.5	1.34	27.8	13.1	1.51	26.3	12.7	1.69	24.7	12.5	1.87	23.33	12.52	2.07	21.82	12.50	2.29
	75	63	24.3	15.7	1.35	23.3	16.0	1.50	22.3	15.6	1.67	21.1	15.4	1.85	19.93	15.29	2.05	18.65	15.18	2.27
900	80	62	24.8	22.1	1.38	23.9	22.2	1.54	23.0	21.5	1.71	22.0	20.9	1.89	20.93	20.23	2.09	19.76	19.68	2.31
	80	67	26.8	17.4	1.38	25.6	17.6	1.54	24.4	17.1	1.71	23.2	17.0	1.89	21.81	16.85	2.09	20.44	16.87	2.31
	80	72	29.1	13.4	1.38	27.8	13.6	1.55	26.5	13.2	1.72	25.1	13.1	1.90	23.61	13.00	2.10	22.05	13.06	2.33
	75	63	24.8	16.8	1.38	23.7	16.9	1.54	22.6	16.4	1.71	21.4	16.3	1.89	20.22	16.12	2.08	18.92	16.44	2.31

FT4BE-030K C7B(A,H)M03036(C,U)-A + TXV Kit

CFM	O.D.T		65°F			75°F			85°F			95°F			105°F			115°F		
	E.D.B.	E.W.B.	T.C.	S.C.	K.W.	T.C.	S.C.	K.W.	T.C.	S.C.	K.W.	T.C.	S.C.	K.W.	T.C.	S.C.	K.W.	T.C.	S.C.	K.W.
875	80	62	28.9	22.2	1.71	27.9	22.8	1.87	26.7	22.9	2.06	25.5	22.6	2.27	24.20	23.69	2.51	22.90	22.42	2.78
	80	67	31.7	18.4	1.72	30.4	18.2	1.88	29.1	18.4	2.07	27.8	18.1	2.27	26.33	17.83	2.51	24.77	16.71	2.79
	80	72	34.9	14.2	1.72	33.5	14.2	1.89	32.1	14.5	2.07	30.6	14.2	2.28	29.01	14.00	2.52	27.29	14.38	2.80
	75	63	29.3	17.8	1.71	28.2	17.7	1.88	27.0	17.8	2.06	25.7	17.5	2.27	24.37	16.08	2.51	22.84	17.29	2.78
1000	80	62	29.7	24.7	1.76	28.6	25.2	1.92	27.4	24.7	2.11	26.1	24.5	2.32	25.15	24.30	2.56	23.86	23.66	2.83
	80	67	32.4	19.5	1.76	31.0	20.1	1.93	29.7	19.6	2.12	28.3	19.4	2.32	26.79	19.40	2.56	25.15	19.39	2.84
	80	72	35.6	15.0	1.77	34.2	15.7	1.93	32.7	15.2	2.12	31.1	15.1	2.33	29.45	15.24	2.57	27.65	15.37	2.84
	75	63	30.0	18.9	1.76	28.8	19.4	1.92	27.5	18.9	2.11	26.2	18.6	2.32	24.78	18.59	2.56	23.23	18.52	2.83
1125	80	62	30.4	26.8	1.81	29.2	27.0	1.97	28.3	26.3	2.16	27.2	25.8	2.37	25.92	25.04	2.61	24.55	24.45	2.88
	80	67	32.9	20.9	1.81	31.6	21.2	1.98	30.2	20.7	2.16	28.7	20.6	2.37	27.15	20.47	2.61	25.47	20.57	2.89
	80	72	36.2	16.0	1.82	34.7	16.4	1.98	33.1	15.9	2.16	31.5	16.0	2.37	29.71	15.97	2.61	27.82	16.17	2.89
	75	63	30.5	20.2	1.81	29.3	20.4	1.97	28.0	19.9	2.15	26.6	19.8	2.36	25.12	19.59	2.61	23.53	19.60	2.88

FT4BE-036K C7B(A,H)M03648(C,U)-C + TXV Kit

CFM	O.D.T		65°F			75°F			85°F			95°F			105°F			115°F		
	E.D.B.	E.W.B.	T.C.	S.C.	K.W.	T.C.	S.C.	K.W.	T.C.	S.C.	K.W.	T.C.	S.C.	K.W.	T.C.	S.C.	K.W.	T.C.	S.C.	K.W.
1050	80	62	35.6	28.2	2.02	34.2	28.0	2.24	32.8	28.1	2.47	31.2	27.5	2.73	29.55	28.69	3.03	27.86	27.05	3.36
	80	67	38.7	23.2	2.03	37.2	23.1	2.25	35.6	23.3	2.49	33.9	22.8	2.75	32.05	22.43	3.04	30.12	20.95	3.38
	80	72	42.6	18.0	2.05	40.8	17.9	2.27	38.9	18.3	2.51	36.8	17.9	2.77	34.58	17.59	3.06	32.51	17.93	3.39
	75	63	36.0	22.5	2.02	34.5	22.3	2.24	33.0	22.4	2.48	31.5	22.0	2.73	29.77	20.24	3.03	27.95	21.70	3.36
1200	80	62	36.4	30.2	2.08	35.0	30.7	2.30	33.4	29.9	2.53	31.8	29.5	2.79	30.22	29.06	3.09	28.60	28.36	3.42
	80	67	39.5	24.7	2.09	37.9	25.4	2.31	36.2	24.7	2.55	34.4	24.4	2.81	32.55	24.37	3.10	30.58	24.29	3.44
	80	72	42.8	19.0	2.11	40.9	19.8	2.33	39.1	19.2	2.57	37.2	18.9	2.83	35.14	18.97	3.12	32.97	18.99	3.45
	75	63	36.7	23.9	2.08	35.2	24.4	2.30	33.6	23.8	2.54	32.0	23.5	2.79	30.20	23.35	3.09	28.36	23.21	3.42
1350	80	62	37.0	32.3	2.14	35.6	32.4	2.36	34.0	31.5	2.59	32.5	30.9	2.85	30.98	29.93	3.15	29.33	29.20	3.49
	80	67	40.1	26.5	2.15	38.5	26.7	2.37	36.7	26.1	2.61	34.9	25.9	2.87	32.91	25.71	3.16	30.89	25.64	3.50
	80	72	43.3	20.2	2.17	41.5	20.6	2.39	39.6	19.9	2.64	37.6	19.9	2.89	35.52	19.72	3.18	33.28	19.86	3.51
	75	63	37.3	25.5	2.14	35.7	25.7	2.36	34.1	25.0	2.59	32.4	24.9	2.85	30.54	24.57	3.14	28.61	24.43	3.48

14 SEER COOLING EXPANDED RATINGS - LOOSE COIL (CONTINUED)

FT4BE-042K C7B(A,H)M03642(C,U)-B + TXV Kit

O.D.T			65°F			75°F			85°F			95°F			105°F			115°F		
CFM	E.D.B.	E.W.B.	T.C.	S.C.	K.W.	T.C.	S.C.	K.W.	T.C.	S.C.	K.W.	T.C.	S.C.	K.W.	T.C.	S.C.	K.W.	T.C.	S.C.	K.W.
1225	80	62	41.6	32.4	2.40	40.1	32.1	2.63	38.4	32.3	2.90	36.6	31.6	3.21	34.66	33.05	3.55	32.68	31.16	3.94
	80	67	45.1	26.7	2.41	43.4	26.5	2.65	41.5	26.8	2.92	39.6	26.2	3.23	37.49	25.78	3.58	35.31	24.12	3.97
	80	72	49.6	20.9	2.44	47.5	20.8	2.68	45.2	21.2	2.95	42.6	20.7	3.26	40.36	20.33	3.61	37.98	20.73	4.01
	75	63	42.0	26.0	2.40	40.4	25.7	2.63	38.7	25.9	2.90	36.8	25.3	3.21	34.84	23.36	3.56	32.80	25.01	3.94
1400	80	62	42.5	34.6	2.47	40.8	35.2	2.70	39.2	34.4	2.97	37.3	33.8	3.28	35.34	33.55	3.63	33.33	33.05	4.01
	80	67	46.0	28.3	2.48	44.2	29.1	2.72	42.3	28.3	2.99	40.3	28.0	3.30	38.11	27.94	3.65	35.84	27.87	4.04
	80	72	49.6	21.9	2.50	47.6	22.8	2.75	45.5	22.1	3.02	43.3	21.8	3.33	40.95	21.86	3.69	38.48	21.88	4.08
	75	63	42.8	27.4	2.47	41.2	28.1	2.70	39.4	27.3	2.97	37.5	26.9	3.28	35.45	26.81	3.63	33.31	26.66	4.01
1575	80	62	43.2	37.0	2.53	41.5	37.1	2.77	39.8	36.2	3.04	37.9	35.7	3.35	36.03	34.81	3.70	34.17	34.02	4.09
	80	67	46.8	30.3	2.55	44.9	30.6	2.79	42.9	29.8	3.06	40.7	29.7	3.38	38.57	29.39	3.72	36.25	29.42	4.11
	80	72	50.3	23.3	2.57	48.3	23.7	2.82	46.1	22.9	3.09	43.8	22.8	3.41	41.38	22.64	3.76	38.83	22.78	4.14
	75	63	43.5	29.2	2.54	41.8	29.5	2.77	39.9	28.7	3.04	37.9	28.5	3.35	35.85	28.12	3.70	33.63	28.10	4.08

FT4BE-048K C7B(A,H)M048(C,U)-C + TXV Kit + VSB

O.D.T			65°F			75°F			85°F			95°F			105°F			115°F		
CFM	E.D.B.	E.W.B.	T.C.	S.C.	K.W.	T.C.	S.C.	K.W.	T.C.	S.C.	K.W.	T.C.	S.C.	K.W.	T.C.	S.C.	K.W.	T.C.	S.C.	K.W.
1400	80	62	47.2	37.4	2.59	45.4	37.1	2.84	43.5	37.3	3.14	41.4	36.6	3.48	39.16	38.15	3.87	36.92	35.97	4.29
	80	67	51.6	30.8	2.61	49.5	30.6	2.88	47.4	30.9	3.17	45.1	30.3	3.51	42.62	29.89	3.89	40.07	27.91	4.32
	80	72	56.5	23.6	2.65	54.2	23.5	2.90	51.8	24.0	3.20	49.3	23.5	3.54	46.61	23.22	3.92	43.79	23.82	4.35
	75	63	47.9	29.9	2.59	46.1	29.6	2.85	44.0	29.9	3.15	41.9	29.3	3.49	39.65	27.05	3.87	37.25	29.08	4.29
1600	80	62	48.3	40.0	2.64	46.4	40.8	2.90	44.4	39.8	3.20	42.3	39.2	3.54	40.08	38.72	3.92	38.05	37.73	4.35
	80	67	52.6	32.8	2.67	50.5	33.7	2.93	48.2	32.9	3.22	45.9	32.6	3.56	43.32	32.62	3.94	40.68	32.63	4.37
	80	72	57.6	24.9	2.70	55.2	26.1	2.95	52.7	25.3	3.25	50.0	25.1	3.59	47.18	25.30	3.97	44.32	25.46	4.40
	75	63	48.9	31.7	2.64	47.0	32.5	2.90	44.9	31.7	3.20	42.6	31.4	3.54	40.27	31.30	3.92	37.79	31.23	4.34
1800	80	62	49.2	42.9	2.69	47.3	43.1	2.95	45.3	41.8	3.25	43.2	41.1	3.59	41.23	39.84	3.97	39.10	38.93	4.41
	80	67	53.5	35.2	2.72	51.3	35.7	2.98	48.9	34.8	3.27	46.5	34.7	3.61	43.87	34.53	3.99	41.15	34.53	4.42
	80	72	58.4	26.7	2.75	55.9	27.3	3.00	53.3	26.5	3.30	50.6	26.6	3.64	47.77	26.48	4.02	44.82	26.82	4.45
	75	63	49.7	34.0	2.69	47.7	34.4	2.95	45.5	33.5	3.25	43.2	33.4	3.59	40.79	33.07	3.97	38.23	32.96	4.39

FT4BE-060K with C6BH-X60C-C + VSB

ODT			75°F			85°F			95°F			105°F			115°F		
CFM	E.D.B.	E.W.B.	T.C.	S.C.	K.W.	T.C.	S.C.	K.W.	T.C.	S.C.	K.W.	T.C.	S.C.	K.W.	T.C.	S.C.	K.W.
1460	80	62	58.4	46.7	3.93	55.8	45.8	4.35	53.2	45.0	4.82	50.3	44.4	5.36	47.0	42.7	5.97
	80	67	63.4	40.5	3.98	60.6	39.4	4.41	57.8	38.2	4.89	54.6	36.8	5.42	51.0	35.4	6.03
	80	72	69.5	33.1	4.06	66.4	32.0	4.50	63.1	30.8	4.97	59.6	29.6	5.50	55.5	28.2	6.11
	75	63	58.1	40.5	3.94	55.6	39.3	4.36	53.0	38.1	4.82	50.1	36.5	5.36	46.8	35.0	5.96
1660	80	62	60.1	50.0	3.96	57.4	49.0	4.37	54.7	48.2	4.84	51.7	48.2	5.38	48.3	46.4	5.99
	80	67	65.2	43.1	4.02	62.2	41.9	4.43	59.0	40.7	4.91	55.9	39.0	5.44	52.2	37.5	6.05
	80	72	71.0	34.8	4.10	67.7	33.6	4.52	64.3	32.5	4.98	60.4	31.2	5.52	56.3	29.7	6.12
	75	63	59.8	42.7	3.96	57.1	41.5	4.37	54.4	40.3	4.84	51.3	38.9	5.38	47.9	37.4	5.98
1860	80	62	61.4	53.9	4.01	58.8	52.6	4.39	56.0	52.0	4.86	52.9	51.0	5.40	49.5	48.7	6.00
	80	67	66.7	45.1	4.05	63.6	43.9	4.45	60.5	42.7	4.93	57.0	41.2	5.46	53.1	39.7	6.06
	80	72	72.0	36.4	4.13	68.6	35.2	4.54	65.2	34.0	5.01	61.4	32.6	5.54	57.2	31.1	6.14
	75	63	61.3	45.1	3.99	58.5	43.9	4.39	55.5	42.6	4.86	52.3	41.2	5.40	48.8	39.6	6.00

14 SEER HEATING EXPANDED RATINGS - LOOSE COIL

FT4BE-018K / C7B(A,H)M01824(C,U)-A + TXV Kit

		OUTDOOR TEMPERATURE (Deg. F)																							
CFM	Indoor T. Deg.F	10			17			20			30			40			47			50			60		
		MBH	COP	kW	MBH	COP	kW	MBH	COP	kW	MBH	COP	kW	MBH	COP	kW	MBH	COP	kW	MBH	COP	kW	MBH	COP	kW
565	60	10.6	2.35	1.32	12.6	2.69	1.38	13.5	2.83	1.40	16.4	3.27	1.47	19.3	3.66	1.55	21.4	3.91	1.60	22.3	4.01	1.63	25.2	4.34	1.70
	70	10.0	2.37	1.24	11.9	2.66	1.32	12.7	2.77	1.35	15.4	3.11	1.45	18.1	3.40	1.56	19.9	3.58	1.63	20.7	3.65	1.67	23.4	3.88	1.77
	80	9.5	2.35	1.18	11.2	2.58	1.27	11.9	2.68	1.30	14.3	2.95	1.42	16.7	3.17	1.55	18.4	3.31	1.63	19.2	3.37	1.67	21.6	3.54	1.79
665	60	10.6	2.28	1.37	12.7	2.63	1.42	13.6	2.77	1.44	16.6	3.22	1.51	19.6	3.62	1.59	21.7	3.88	1.64	22.6	3.98	1.66	25.5	4.32	1.74
	70	10.2	2.30	1.29	12.1	2.59	1.37	12.9	2.71	1.40	15.6	3.05	1.50	18.3	3.36	1.60	20.2	3.55	1.67	21.1	3.62	1.70	23.8	3.86	1.81
	80	9.6	2.30	1.22	11.3	2.54	1.31	12.1	2.63	1.35	14.6	2.90	1.47	17.1	3.13	1.60	18.8	3.28	1.68	19.6	3.33	1.72	22.0	3.50	1.85
765	60	10.8	2.24	1.41	12.9	2.59	1.46	13.8	2.73	1.48	16.8	3.18	1.55	19.8	3.59	1.62	21.9	3.85	1.67	22.8	3.96	1.69	25.8	4.31	1.76
	70	10.3	2.26	1.33	12.2	2.55	1.40	13.0	2.67	1.43	15.8	3.02	1.53	18.6	3.33	1.64	20.5	3.53	1.71	21.4	3.61	1.74	24.1	3.85	1.84
	80	9.7	2.25	1.26	11.5	2.49	1.35	12.2	2.58	1.39	14.7	2.85	1.51	17.2	3.08	1.64	19.0	3.22	1.73	19.7	3.28	1.77	22.3	3.45	1.89

FT4BE-024K / C7B(A,H)M01824(C,U)-B + TXV Kit

		OUTDOOR TEMPERATURE (Deg. F)																							
CFM	Indoor T. Deg.F	10			17			20			30			40			47			50			60		
		MBH	COP	kW	MBH	COP	kW	MBH	COP	kW	MBH	COP	kW	MBH	COP	kW	MBH	COP	kW	MBH	COP	kW	MBH	COP	kW
730	60	13.0	2.43	1.58	15.7	2.79	1.65	16.9	2.94	1.69	20.7	3.38	1.80	24.6	3.78	1.91	27.3	4.03	1.99	28.4	4.13	2.02	32.3	4.45	2.13
	70	12.5	2.38	1.53	15.0	2.69	1.63	16.1	2.82	1.67	19.7	3.18	1.81	23.3	3.50	1.95	25.8	3.69	2.05	26.9	3.77	2.09	30.5	4.01	2.23
	80	11.9	2.30	1.51	14.2	2.57	1.62	15.2	2.68	1.67	18.6	2.99	1.83	22.0	3.25	1.99	24.4	3.41	2.10	25.4	3.48	2.14	28.8	3.67	2.30
830	60	13.1	2.38	1.62	15.8	2.74	1.69	17.0	2.89	1.72	20.9	3.35	1.83	24.8	3.75	1.94	27.6	4.01	2.02	28.8	4.12	2.05	32.7	4.44	2.16
	70	12.6	2.33	1.58	15.1	2.65	1.68	16.2	2.77	1.72	19.9	3.15	1.85	23.6	3.48	1.99	26.1	3.68	2.08	27.2	3.76	2.12	30.9	4.01	2.26
	80	12.0	2.26	1.55	14.4	2.54	1.66	15.4	2.65	1.71	18.9	2.96	1.87	22.3	3.23	2.03	24.7	3.40	2.14	25.8	3.46	2.18	29.2	3.66	2.34
930	60	13.2	2.33	1.66	16.0	2.70	1.73	17.2	2.85	1.76	21.1	3.32	1.87	25.1	3.73	1.97	27.8	4.00	2.04	29.0	4.10	2.07	33.0	4.44	2.18
	70	12.7	2.30	1.62	15.3	2.62	1.71	16.4	2.74	1.75	20.1	3.13	1.89	23.8	3.46	2.02	26.4	3.67	2.11	27.6	3.75	2.15	31.3	4.01	2.29
	80	12.1	2.23	1.59	14.5	2.50	1.70	15.6	2.61	1.75	19.0	2.93	1.91	22.5	3.20	2.06	24.9	3.37	2.17	26.0	3.43	2.22	29.4	3.63	2.37

FT4BE-030K / C7B(A,H)M03036(C,U)-A + TXV Kit

		OUTDOOR TEMPERATURE (Deg. F)																							
CFM	Indoor T. Deg.F	10			17			20			30			40			47			50			60		
		MBH	COP	kW	MBH	COP	kW	MBH	COP	kW	MBH	COP	kW	MBH	COP	kW	MBH	COP	kW	MBH	COP	kW	MBH	COP	kW
890	60	16.1	2.59	1.82	18.9	2.90	1.91	20.0	3.02	1.95	24.0	3.40	2.07	27.9	3.73	2.20	30.7	3.94	2.28	31.9	4.03	2.32	35.8	4.30	2.44
	70	15.5	2.49	1.82	18.1	2.75	1.93	19.2	2.85	1.97	22.9	3.17	2.12	26.6	3.44	2.27	29.2	3.61	2.38	30.4	3.68	2.42	34.1	3.89	2.57
	80	14.9	2.38	1.84	17.3	2.60	1.96	18.4	2.69	2.01	21.9	2.95	2.17	25.4	3.18	2.34	27.8	3.32	2.46	28.8	3.38	2.51	32.3	3.55	2.67
990	60	16.2	2.54	1.86	19.0	2.86	1.95	20.2	2.98	1.98	24.2	3.37	2.10	28.2	3.72	2.22	31.0	3.94	2.31	32.2	4.03	2.34	36.2	4.31	2.47
	70	15.6	2.45	1.87	18.2	2.72	1.97	19.4	2.82	2.01	23.1	3.15	2.16	26.9	3.43	2.30	29.5	3.61	2.40	30.7	3.68	2.45	34.5	3.90	2.59
	80	15.0	2.34	1.88	17.5	2.57	1.99	18.5	2.66	2.04	22.1	2.94	2.21	25.7	3.17	2.37	28.2	3.32	2.49	29.2	3.38	2.54	32.8	3.56	2.70
1090	60	16.2	2.50	1.90	19.1	2.82	1.99	20.3	2.95	2.02	24.4	3.34	2.14	28.4	3.70	2.25	31.3	3.93	2.33	32.5	4.02	2.37	36.5	4.31	2.48
	70	15.7	2.42	1.90	18.4	2.70	2.00	19.5	2.80	2.04	23.4	3.13	2.19	27.2	3.42	2.33	29.8	3.61	2.43	31.0	3.68	2.47	34.8	3.91	2.61
	80	15.1	2.32	1.91	17.6	2.55	2.03	18.7	2.64	2.08	22.3	2.92	2.24	25.9	3.16	2.40	28.4	3.30	2.52	29.4	3.36	2.57	33.0	3.55	2.73

FT4BE-036K / C7B(A,H)M03648(C,U)-C + TXV Kit

		OUTDOOR TEMPERATURE (Deg. F)																							
CFM	Indoor T. Deg.F	10			17			20			30			40			47			50			60		
		MBH	COP	kW	MBH	COP	kW	MBH	COP	kW	MBH	COP	kW	MBH	COP	kW	MBH	COP	kW	MBH	COP	kW	MBH	COP	kW
1065	60	19.6	2.62	2.19	22.9	2.95	2.28	24.3	3.08	2.31	29.1	3.50	2.44	33.8	3.87	2.56	37.1	4.12	2.64	38.5	4.21	2.68	43.2	4.53	2.80
	70	18.9	2.47	2.25	22.1	2.76	2.35	23.4	2.88	2.39	28.0	3.24	2.53	32.5	3.57	2.67	35.6	3.78	2.77	37.0	3.86	2.81	41.5	4.13	2.95
	80	18.3	2.32	2.32	21.4	2.58	2.43	22.6	2.68	2.47	26.9	3.00	2.63	31.2	3.29	2.78	34.2	3.47	2.89	35.5	3.55	2.94	39.8	3.78	3.09
1215	60	19.8	2.58	2.24	23.1	2.92	2.33	24.6	3.05	2.36	29.4	3.48	2.48	34.2	3.87	2.59	37.6	4.12	2.67	39.0	4.23	2.71	43.8	4.55	2.82
	70	19.1	2.43	2.30	22.3	2.73	2.40	23.7	2.85	2.44	28.3	3.23	2.57	32.9	3.57	2.70	36.1	3.78	2.80	37.5	3.87	2.84	42.1	4.15	2.97
	80	18.5	2.29	2.37	21.6	2.55	2.48	22.9	2.66	2.52	27.3	2.99	2.67	31.7	3.29	2.82	34.7	3.48	2.93	36.1	3.56	2.97	40.4	3.80	3.12
1365	60	19.8	2.54	2.29	23.3	2.88	2.37	24.7	3.02	2.40	29.7	3.46	2.52	34.6	3.86	2.63	38.0	4.12	2.71	39.5	4.22	2.74	44.4	4.56	2.85
	70	19.3	2.41	2.35	22.6	2.71	2.44	24.0	2.84	2.48	28.6	3.22	2.61	33.3	3.56	2.74	36.6	3.79	2.83	38.0	3.88	2.87	42.6	4.17	3.00
	80	18.7	2.26	2.42	21.8	2.53	2.53	23.1	2.64	2.57	27.6	2.98	2.71	32.0	3.28	2.86	35.1	3.48	2.96	36.4	3.56	3.00	40.9	3.81	3.15

14 SEER HEATING EXPANDED RATINGS - LOOSE COIL (CONTINUED)

FT4BE-042K / C7B(A,H)M03642(C,U)-B + TXV Kit

		OUTDOOR TEMPERATURE (Deg. F)																							
CFM	Indoor T. Deg.F	10			17			20			30			40			47			50			60		
		MBH	COP	kW	MBH	COP	kW	MBH	COP	kW	MBH	COP	kW	MBH	COP	kW	MBH	COP	kW	MBH	COP	kW	MBH	COP	kW
1215	60	23.3	2.83	2.42	27.0	3.05	2.60	28.6	3.14	2.67	33.9	3.38	2.93	39.1	3.59	3.19	42.8	3.72	3.37	44.4	3.77	3.45	49.6	3.92	3.71
	70	22.6	2.64	2.51	26.1	2.83	2.71	27.6	2.90	2.80	32.7	3.11	3.08	37.8	3.29	3.37	41.4	3.40	3.57	42.9	3.44	3.65	48.0	3.57	3.94
	80	22.0	2.47	2.62	25.4	2.63	2.84	26.9	2.69	2.93	31.7	2.87	3.25	36.6	3.01	3.56	40.0	3.10	3.78	41.4	3.14	3.87	46.3	3.24	4.18
1365	60	23.5	2.80	2.46	27.3	3.03	2.64	28.9	3.12	2.71	34.2	3.38	2.96	39.6	3.61	3.21	43.3	3.75	3.39	44.9	3.80	3.46	50.2	3.97	3.71
	70	22.8	2.61	2.56	26.4	2.81	2.75	27.9	2.89	2.83	33.1	3.12	3.11	38.2	3.31	3.38	41.8	3.43	3.58	43.4	3.47	3.66	48.5	3.62	3.93
	80	22.2	2.43	2.67	25.6	2.61	2.88	27.1	2.68	2.97	32.1	2.87	3.27	37.0	3.04	3.57	40.5	3.14	3.78	41.9	3.18	3.87	46.9	3.29	4.17
1515	60	23.5	2.75	2.51	27.4	2.99	2.68	29.0	3.09	2.75	34.5	3.37	3.00	39.9	3.61	3.24	43.7	3.76	3.41	45.4	3.81	3.49	50.8	3.99	3.73
	70	23.0	2.59	2.61	26.7	2.80	2.79	28.2	2.88	2.87	33.4	3.12	3.14	38.6	3.32	3.41	42.3	3.45	3.59	43.8	3.50	3.68	49.0	3.65	3.94
	80	22.4	2.41	2.72	25.9	2.60	2.92	27.4	2.67	3.01	32.4	2.87	3.30	37.3	3.05	3.59	40.8	3.16	3.80	42.3	3.20	3.88	47.3	3.32	4.17

FT4BE-048K / C7B(A,H)M048(C,U)-C + TXV Kit + VSB

		OUTDOOR TEMPERATURE (Deg. F)																							
CFM	Indoor T. Deg.F	10			17			20			30			40			47			50			60		
		MBH	COP	kW	MBH	COP	kW	MBH	COP	kW	MBH	COP	kW	MBH	COP	kW	MBH	COP	kW	MBH	COP	kW	MBH	COP	kW
1430	60	24.5	2.75	2.62	28.8	3.06	2.76	30.6	3.19	2.82	36.7	3.57	3.02	42.8	3.90	3.22	47.1	4.11	3.36	48.9	4.20	3.42	55.1	4.46	3.62
	70	23.7	2.54	2.74	27.9	2.82	2.89	29.6	2.94	2.96	35.6	3.28	3.18	41.5	3.58	3.40	45.7	3.77	3.55	47.4	3.85	3.62	53.4	4.08	3.84
	80	23.2	2.36	2.88	27.2	2.62	3.05	28.9	2.72	3.12	34.6	3.02	3.36	40.3	3.29	3.59	44.3	3.46	3.76	46.0	3.52	3.83	51.7	3.73	4.07
1630	60	24.8	2.72	2.67	29.1	3.04	2.81	31.0	3.17	2.86	37.2	3.57	3.05	43.4	3.93	3.24	47.8	4.15	3.38	49.6	4.24	3.43	55.9	4.52	3.62
	70	24.0	2.52	2.80	28.2	2.81	2.94	30.0	2.93	3.01	36.1	3.29	3.21	42.1	3.61	3.42	46.3	3.81	3.57	48.1	3.89	3.63	54.1	4.14	3.84
	80	23.4	2.33	2.94	27.5	2.60	3.10	29.2	2.71	3.17	35.1	3.03	3.39	40.9	3.32	3.61	45.0	3.50	3.77	46.7	3.57	3.84	52.5	3.79	4.06
1830	60	24.9	2.67	2.73	29.3	3.01	2.86	31.2	3.14	2.91	37.6	3.56	3.10	43.9	3.93	3.28	48.4	4.16	3.41	50.3	4.26	3.46	56.6	4.55	3.65
	70	24.3	2.50	2.86	28.6	2.80	2.99	30.4	2.92	3.05	36.5	3.29	3.25	42.6	3.62	3.45	46.9	3.83	3.59	48.7	3.92	3.65	54.8	4.18	3.85
	80	23.7	2.31	3.00	27.8	2.59	3.15	29.6	2.70	3.21	35.5	3.03	3.43	41.4	3.33	3.64	45.5	3.52	3.79	47.3	3.60	3.85	53.2	3.83	4.07

FT4BE-060K with C6BH-X60C-C + VSB

		OUTDOOR TEMPERATURE (Deg. F)																							
CFM	Indoor T. Deg.F	10			17			20			30			40			47			50			60		
		MBH	COP	kW	MBH	COP	kW	MBH	COP	kW	MBH	COP	kW	MBH	COP	kW	MBH	COP	kW	MBH	COP	kW	MBH	COP	kW
1450	60	32.8	2.65	3.62	36.8	2.87	3.76	38.6	2.96	3.82	44.4	3.24	4.02	50.2	3.49	4.21	54.3	3.66	4.35	56.1	3.73	4.41	61.9	3.94	4.61
	70	31.8	2.39	3.89	35.8	2.60	4.04	37.5	2.68	4.10	43.2	2.95	4.30	48.9	3.19	4.50	52.9	3.34	4.64	54.6	3.41	4.70	60.3	3.61	4.90
	80	31.3	2.19	4.19	35.2	2.38	4.34	36.8	2.45	4.40	42.3	2.69	4.61	47.7	2.90	4.82	51.5	3.05	4.96	53.2	3.10	5.03	58.6	3.29	5.23
1650	60	33.1	2.65	3.65	37.2	2.88	3.78	39.0	2.98	3.84	44.9	3.27	4.02	50.8	3.54	4.21	55.0	3.72	4.34	56.8	3.79	4.40	62.7	4.01	4.58
	70	32.2	2.41	3.92	36.2	2.62	4.05	37.9	2.71	4.11	43.7	2.98	4.30	49.5	3.24	4.48	53.5	3.40	4.61	55.2	3.47	4.67	61.0	3.68	4.86
	80	31.5	2.19	4.22	35.5	2.39	4.36	37.1	2.47	4.41	42.7	2.72	4.61	48.3	2.95	4.80	52.2	3.11	4.93	53.9	3.17	4.99	59.4	3.37	5.18
1850	60	33.1	2.63	3.69	37.3	2.87	3.81	39.1	2.97	3.87	45.2	3.28	4.05	51.3	3.56	4.23	55.6	3.74	4.36	57.4	3.82	4.41	63.5	4.06	4.59
	70	32.5	2.41	3.96	36.6	2.63	4.09	38.4	2.72	4.14	44.2	3.00	4.32	50.0	3.27	4.49	54.1	3.44	4.61	55.8	3.51	4.67	61.7	3.73	4.84
	80	31.9	2.19	4.26	35.8	2.40	4.38	37.5	2.48	4.44	43.1	2.74	4.61	48.8	2.99	4.79	52.7	3.15	4.91	54.4	3.21	4.97	60.1	3.43	5.14

14 SEER COOLING EXPANDED RATINGS

FT4BE-018K with B6BM-X24K-(A,B)

O.D.T			75°F			85°F			95°F			105°F			115°F		
CFM	E.D.B.	E.W.B.	T.C.	S.C.	K.W.	T.C.	S.C.	K.W.	T.C.	S.C.	K.W.	T.C.	S.C.	K.W.	T.C.	S.C.	K.W.
600	80	62	19.3	17.3	1.24	18.4	16.9	1.37	17.5	16.6	1.53	16.6	16.3	1.71	15.6	15.4	1.91
	80	67	20.9	14.4	1.24	20.0	14.0	1.37	19.0	13.6	1.53	17.8	13.2	1.71	16.6	12.7	1.91
	80	72	22.7	11.4	1.24	21.7	11.1	1.37	20.6	10.7	1.53	19.3	10.2	1.71	18.1	9.8	1.91
	75	63	19.0	14.6	1.24	18.2	14.1	1.37	17.3	13.7	1.53	16.3	13.3	1.71	15.2	12.8	1.91
700	80	62	20.0	18.7	1.24	19.1	18.4	1.37	18.1	17.7	1.53	17.3	17.3	1.71	16.3	16.3	1.91
	80	67	21.5	15.6	1.24	20.5	15.2	1.37	18.7	14.8	1.53	18.3	14.3	1.71	17.0	13.8	1.91
	80	72	23.3	12.2	1.24	22.2	11.8	1.37	21.0	11.4	1.53	19.8	11.0	1.72	18.4	10.5	1.92
	75	63	19.6	15.8	1.25	18.8	15.4	1.37	17.8	14.9	1.53	16.7	14.4	1.71	15.5	13.9	1.91
800	80	62	20.7	19.7	1.25	19.9	19.3	1.37	19.0	18.7	1.53	18.0	18.0	1.71	16.9	16.9	1.91
	80	67	21.9	16.8	1.25	20.9	16.4	1.37	19.8	15.9	1.53	18.6	15.5	1.71	17.3	14.9	1.91
	80	72	23.7	13.0	1.24	22.6	12.5	1.37	21.4	12.1	1.54	20.1	11.7	1.72	18.7	11.2	1.92
	75	63	20.1	17.0	1.25	19.2	16.5	1.37	18.2	16.1	1.53	17.1	15.5	1.71	15.9	14.9	1.91

FT4BE-024K with B6BM-X24K-(A,B)

O.D.T			75°F			85°F			95°F			105°F			115°F		
CFM	E.D.B.	E.W.B.	T.C.	S.C.	K.W.	T.C.	S.C.	K.W.	T.C.	S.C.	K.W.	T.C.	S.C.	K.W.	T.C.	S.C.	K.W.
600	80	62	22.9	18.8	1.48	21.9	18.4	1.63	20.9	18.1	1.83	19.7	17.9	2.04	18.5	17.2	2.29
	80	67	24.9	15.7	1.48	23.7	15.3	1.63	22.6	14.8	1.83	21.4	14.3	2.05	20.0	13.8	2.29
	80	72	27.3	12.7	1.48	26.1	12.2	1.64	24.8	11.8	1.84	23.3	11.3	2.06	21.7	10.8	2.30
	75	63	22.8	16.1	1.48	21.8	15.7	1.64	20.7	15.1	1.83	19.6	14.6	2.04	18.3	14.0	2.29
700	80	62	23.7	20.5	1.48	22.6	20.0	1.63	21.6	19.7	1.83	20.4	19.7	2.04	19.1	18.9	2.29
	80	67	25.7	16.9	1.48	24.5	16.5	1.63	23.2	16.0	1.83	22.0	15.4	2.05	20.6	14.9	2.29
	80	72	27.8	13.5	1.48	26.5	13.0	1.64	25.2	12.6	1.83	23.8	12.1	2.06	22.2	11.5	2.30
	75	63	23.5	17.3	1.48	22.4	16.8	1.64	21.4	16.3	1.83	20.2	15.8	2.04	18.8	15.2	2.29
800	80	62	24.3	22.3	1.49	23.3	21.8	1.63	22.2	21.5	1.83	21.0	21.0	2.05	19.8	19.8	2.29
	80	67	26.3	18.1	1.49	25.1	17.6	1.64	23.8	17.1	1.83	22.5	16.6	2.05	21.0	16.0	2.29
	80	72	28.4	14.2	1.49	27.0	13.7	1.64	25.7	13.3	1.84	24.3	12.8	2.06	22.6	12.2	2.31
	75	63	24.1	18.5	1.49	23.0	18.0	1.64	21.9	17.5	1.83	20.6	16.9	2.05	19.3	16.3	2.29

FT4BE-030K with B6BM-X30K-(A,B)

O.D.T			75°F			85°F			95°F			105°F			115°F		
CFM	E.D.B.	E.W.B.	T.C.	S.C.	K.W.	T.C.	S.C.	K.W.	T.C.	S.C.	K.W.	T.C.	S.C.	K.W.	T.C.	S.C.	K.W.
830	80	62	27.8	24.3	1.81	26.6	23.9	2.00	25.4	23.5	2.22	24.0	23.2	2.47	22.5	22.2	2.76
	80	67	30.1	20.7	1.80	28.8	20.1	2.00	27.5	19.6	2.22	26.0	19.0	2.47	24.3	18.3	2.75
	80	72	30.1	20.8	1.80	28.8	20.1	2.00	27.5	19.6	2.22	26.0	19.0	2.47	24.3	18.3	2.75
	75	63	27.6	20.7	1.81	26.4	20.1	2.01	25.1	19.5	2.23	23.7	18.9	2.47	22.1	18.2	2.76
930	80	62	28.6	25.9	1.81	27.3	25.4	2.00	26.1	24.9	2.22	24.7	24.7	2.47	23.3	23.3	2.76
	80	67	30.8	22.0	1.81	29.4	21.4	2.00	28.0	20.8	2.22	26.4	20.2	2.47	24.7	19.5	2.75
	80	72	30.8	22.1	1.81	29.4	21.4	2.00	28.0	20.8	2.22	26.4	20.2	2.47	24.7	19.5	2.75
	75	63	28.2	21.9	1.82	27.0	21.3	2.00	25.7	20.7	2.22	24.2	20.1	2.47	22.6	19.4	2.76
1030	80	62	29.1	27.7	1.83	27.9	27.0	2.00	26.7	26.3	2.22	25.4	25.4	2.47	24.0	24.0	2.75
	80	67	31.3	23.2	1.82	29.9	22.6	2.00	28.4	22.0	2.22	26.9	21.4	2.47	25.1	20.7	2.75
	80	72	31.4	23.3	1.82	29.9	22.6	2.00	28.4	22.0	2.22	26.9	21.4	2.47	25.1	20.7	2.75
	75	63	28.8	23.1	1.82	27.4	22.5	2.00	26.1	21.9	2.22	24.6	21.3	2.47	22.9	20.5	2.76

FT4BE-036K B6EMMX36K-C

O.D.T			65°F			75°F			85°F			95°F			105°F			115°F		
CFM	E.D.B.	E.W.B.	T.C.	S.C.	K.W.	T.C.	S.C.	K.W.	T.C.	S.C.	K.W.	T.C.	S.C.	K.W.	T.C.	S.C.	K.W.	T.C.	S.C.	K.W.
1050	80	62	35.2	28.5	1.89	33.9	28.3	2.12	32.5	28.4	2.37	31.0	27.9	2.65	29.42	28.89	2.97	27.79	27.29	3.33
	80	67	38.3	23.4	1.90	36.7	23.3	2.15	35.1	23.5	2.39	33.5	23.1	2.67	31.74	22.71	2.99	29.87	21.38	3.35
	80	72	42.0	18.0	1.93	40.2	18.0	2.17	38.3	18.3	2.42	36.2	18.0	2.70	34.29	17.65	3.01	32.24	18.02	3.37
	75	63	35.5	22.7	1.89	34.1	22.5	2.12	32.7	22.7	2.37	31.1	22.2	2.65	29.52	20.52	2.97	27.73	22.04	3.33
1200	80	62	36.1	30.6	1.91	34.7	31.1	2.15	33.3	30.3	2.40	31.8	29.8	2.68	30.29	29.26	3.00	28.75	28.50	3.36
	80	67	39.0	25.0	1.92	37.5	25.7	2.17	35.8	25.0	2.42	34.1	24.8	2.70	32.30	24.72	3.01	30.36	24.69	3.38
	80	72	42.3	19.1	1.95	40.6	19.9	2.19	38.8	19.3	2.44	36.9	19.1	2.72	34.88	19.13	3.04	32.77	19.18	3.40
	75	63	36.3	24.2	1.91	34.8	24.7	2.15	33.3	24.1	2.40	31.7	23.8	2.68	30.02	23.70	3.00	28.23	23.60	3.35
1350	80	62	36.9	32.8	1.94	35.5	32.8	2.17	34.1	31.8	2.43	32.7	31.0	2.71	31.17	30.11	3.03	29.55	29.42	3.38
	80	67	39.7	26.9	1.95	38.1	27.2	2.19	36.4	26.6	2.44	34.6	26.4	2.72	32.76	26.18	3.04	30.76	26.25	3.40
	80	72	43.0	20.4	1.98	41.2	20.7	2.22	39.3	20.1	2.47	37.4	20.1	2.75	35.32	19.97	3.06	33.14	20.15	3.42
	75	63	36.9	25.9	1.94	35.4	26.2	2.17	33.9	25.4	2.42	32.2	25.3	2.70	30.47	25.04	3.02	28.58	25.03	3.38

14 SEER COOLING EXPANDED RATINGS (CONTINUED)

FT4BE-042K with B6BM-X42K-B

CFM	O.D.T		75°F			85°F			95°F			105°F			115°F		
	E.D.B.	E.W.B.	T.C.	S.C.	K.W.	T.C.	S.C.	K.W.	T.C.	S.C.	K.W.	T.C.	S.C.	K.W.	T.C.	S.C.	K.W.
1140	80	62	38.7	33.0	2.57	37.0	32.3	2.85	35.3	31.8	3.15	33.4	31.4	3.49	31.4	30.2	3.88
	80	67	42.0	28.7	2.59	40.1	27.9	2.86	38.3	27.0	3.17	36.2	26.1	3.51	33.9	25.1	3.90
	80	72	45.8	23.2	2.60	43.7	22.4	2.88	41.6	21.7	3.19	39.2	20.8	3.54	36.7	19.9	3.93
	75	63	38.4	28.1	2.58	36.8	27.3	2.85	35.1	26.5	3.15	33.1	25.6	3.50	31.0	24.7	3.88
1340	80	62	40.1	35.9	2.59	38.3	35.2	2.85	36.5	34.5	3.16	34.7	34.3	3.50	32.6	32.6	3.89
	80	67	43.3	30.9	2.60	41.3	30.1	2.87	39.0	29.3	3.18	37.1	28.3	3.52	34.7	27.3	3.91
	80	72	46.8	24.7	2.62	44.7	23.9	2.89	42.5	23.1	3.20	40.2	22.3	3.55	37.5	21.3	3.94
	75	63	39.7	30.4	2.59	37.9	29.6	2.86	36.1	28.8	3.16	34.0	27.9	3.50	31.8	26.9	3.89
1540	80	62	41.4	38.7	2.61	39.6	37.7	2.86	37.7	37.1	3.16	35.9	35.8	3.51	33.8	33.8	3.90
	80	67	44.3	33.2	2.62	42.3	32.3	2.87	40.2	31.4	3.18	37.9	30.5	3.53	35.4	29.4	3.91
	80	72	47.8	26.2	2.63	45.5	25.4	2.89	43.3	24.6	3.21	40.8	23.7	3.55	38.1	22.7	3.94
	75	63	40.7	32.7	2.60	38.8	31.8	2.86	36.9	30.9	3.16	34.8	29.9	3.51	32.5	28.9	3.90

FT4BE-048K B6BM-X60K-C

CFM	O.D.T		65°F			75°F			85°F			95°F			105°F			115°F		
	E.D.B.	E.W.B.	T.C.	S.C.	K.W.	T.C.	S.C.	K.W.	T.C.	S.C.	K.W.	T.C.	S.C.	K.W.	T.C.	S.C.	K.W.	T.C.	S.C.	K.W.
1400	80	62	49.2	40.7	2.65	47.3	40.4	2.91	45.2	40.6	3.22	43.0	39.9	3.57	40.98	40.29	3.97	38.91	38.25	4.42
	80	67	53.5	33.1	2.66	51.2	32.9	2.93	48.9	33.2	3.24	46.4	32.6	3.59	43.87	32.17	3.99	41.24	30.74	4.43
	80	72	58.4	25.0	2.69	55.9	24.9	2.96	53.3	25.4	3.26	50.7	24.9	3.61	47.84	24.53	4.01	44.96	25.15	4.45
	75	63	49.8	32.1	2.65	47.7	31.8	2.91	45.5	32.1	3.22	43.2	31.4	3.57	40.86	29.05	3.97	38.38	31.22	4.42
1600	80	62	50.5	44.1	2.70	48.5	44.8	2.97	46.6	43.5	3.28	44.6	42.1	3.63	42.51	41.08	4.03	40.32	39.98	4.48
	80	67	54.5	35.6	2.72	52.2	36.6	2.99	49.8	35.7	3.29	47.3	35.4	3.65	44.64	35.40	4.04	41.92	35.41	4.49
	80	72	59.5	26.6	2.75	56.9	27.8	3.00	54.3	27.0	3.32	51.5	26.7	3.68	48.59	26.93	4.06	45.60	27.14	4.50
	75	63	50.8	34.4	2.70	48.7	35.3	2.97	46.4	34.4	3.28	44.0	34.0	3.63	41.57	33.92	4.03	39.02	33.84	4.47
1800	80	62	51.9	47.3	2.76	50.1	46.7	3.03	48.1	44.8	3.33	46.0	43.7	3.69	43.78	42.30	4.08	41.46	41.28	4.53
	80	67	55.4	38.6	2.77	53.0	39.0	3.04	50.5	38.2	3.35	47.9	38.0	3.70	45.22	37.81	4.09	42.44	37.99	4.54
	80	72	60.3	28.7	2.80	57.6	29.3	3.06	54.9	28.5	3.37	52.0	28.6	3.72	49.05	28.50	4.11	45.95	28.88	4.55
	75	63	51.6	37.2	2.75	49.4	37.5	3.02	47.1	36.6	3.34	44.7	36.4	3.68	42.14	36.14	4.08	39.51	36.20	4.52

FT4BE-060K B6EMMX60K-C

CFM	O.D.T		65°F			75°F			85°F			95°F			105°F			115°F		
	E.D.B.	E.W.B.	T.C.	S.C.	K.W.	T.C.	S.C.	K.W.	T.C.	S.C.	K.W.	T.C.	S.C.	K.W.	T.C.	S.C.	K.W.	T.C.	S.C.	K.W.
1550	80	62	60.8	43.5	3.60	58.6	43.2	3.96	56.2	43.4	4.38	53.7	42.7	4.84	51.06	44.88	5.38	48.18	42.35	5.99
	80	67	66.2	36.4	3.67	63.7	36.1	4.04	61.2	36.6	4.46	58.5	35.8	4.93	55.55	35.27	5.46	52.48	32.86	6.08
	80	72	72.8	28.8	3.76	70.1	28.7	4.14	67.2	29.3	4.56	64.2	28.7	5.03	60.89	28.25	5.58	57.39	29.04	6.18
	75	63	61.6	35.6	3.61	59.4	35.2	3.97	57.0	35.5	4.39	54.4	34.8	4.86	51.68	32.26	5.39	48.80	34.55	6.00
1700	80	62	61.9	45.4	3.65	59.6	46.4	4.02	57.2	45.4	4.43	54.7	44.9	4.90	51.93	44.82	5.43	48.95	44.37	6.05
	80	67	67.4	37.8	3.72	64.9	39.0	4.10	62.2	37.9	4.51	59.4	37.5	4.98	56.39	37.58	5.52	53.18	37.60	6.13
	80	72	74.0	29.7	3.82	71.1	31.2	4.20	68.2	30.2	4.62	65.0	29.9	5.09	61.59	30.20	5.63	57.93	30.46	6.23
	75	63	62.8	36.9	3.66	60.4	37.9	4.03	58.0	36.8	4.44	55.3	36.4	4.91	52.53	36.34	5.45	49.51	36.24	6.06
1850	80	62	62.9	47.9	3.70	60.6	48.3	4.07	58.1	47.3	4.48	55.5	46.7	4.96	52.61	46.29	5.49	49.56	46.27	6.10
	80	67	68.4	39.8	3.78	65.9	40.3	4.15	63.2	39.3	4.57	60.3	39.2	5.04	57.09	38.89	5.57	53.87	39.16	6.18
	80	72	75.0	31.3	3.88	72.0	32.1	4.25	68.8	31.1	4.67	65.5	31.2	5.14	62.07	31.10	5.68	58.24	31.58	6.28
	75	63	63.8	38.8	3.71	61.4	39.2	4.08	58.8	38.1	4.49	56.1	37.9	4.97	53.21	37.57	5.50	50.11	37.68	6.11

14 SEER HEATING EXPANDED RATINGS

FT4BE-018K with B6BM-X24K-(A,B)

		OUTDOOR TEMPERATURE (Deg. F)																							
CFM	Indoor T. Deg.F	10			17			20			30			40			47			50			60		
		MBH	COP	kW	MBH	COP	kW	MBH	COP	kW	MBH	COP	kW	MBH	COP	kW	MBH	COP	kW	MBH	COP	kW	MBH	COP	kW
510	60	10.0	2.13	1.38	12.0	2.50	1.40	12.8	2.66	1.41	15.5	3.17	1.43	18.2	3.66	1.46	20.2	4.00	1.48	21.0	4.14	1.49	23.7	4.59	1.51
	70	9.5	2.14	1.31	11.3	2.46	1.34	12.0	2.59	1.36	14.5	3.01	1.41	17.0	3.40	1.46	18.7	3.66	1.50	19.5	3.77	1.51	21.9	4.11	1.56
	80	8.9	2.09	1.25	10.5	2.37	1.30	11.2	2.49	1.32	13.4	2.85	1.38	15.6	3.19	1.44	17.2	3.40	1.48	17.9	3.49	1.50	20.1	3.78	1.56
610	60	10.1	2.08	1.42	12.0	2.45	1.44	12.9	2.61	1.45	15.7	3.12	1.47	18.5	3.61	1.50	20.4	3.95	1.52	21.3	4.09	1.52	24.1	4.56	1.55
	70	9.6	2.08	1.36	11.4	2.40	1.39	12.2	2.53	1.41	14.7	2.96	1.46	17.2	3.36	1.51	19.0	3.62	1.54	19.8	3.73	1.55	22.3	4.08	1.60
	80	9.0	2.05	1.29	10.7	2.33	1.34	11.3	2.45	1.36	13.6	2.81	1.42	16.0	3.14	1.49	17.6	3.35	1.54	18.3	3.44	1.56	20.6	3.72	1.62
710	60	10.3	2.05	1.47	12.2	2.42	1.49	13.1	2.57	1.49	15.9	3.08	1.51	18.7	3.58	1.53	20.7	3.92	1.55	21.5	4.07	1.55	24.3	4.54	1.57
	70	9.7	2.04	1.40	11.5	2.37	1.43	12.3	2.50	1.44	14.9	2.93	1.49	17.5	3.33	1.54	19.3	3.59	1.57	20.1	3.70	1.59	22.7	4.06	1.64
	80	9.2	2.01	1.34	10.8	2.29	1.38	11.5	2.40	1.40	13.8	2.76	1.47	16.1	3.08	1.54	17.7	3.29	1.58	18.4	3.38	1.60	20.8	3.65	1.67

FT4BE-024K with B6BM-X24K-(A,B)

		OUTDOOR TEMPERATURE (Deg. F)																							
CFM	Indoor T. Deg.F	10			17			20			30			40			47			50			60		
		MBH	COP	kW	MBH	COP	kW	MBH	COP	kW	MBH	COP	kW	MBH	COP	kW	MBH	COP	kW	MBH	COP	kW	MBH	COP	kW
600	60	13.1	2.42	1.59	15.4	2.74	1.65	16.4	2.87	1.67	19.6	3.28	1.75	22.9	3.65	1.84	25.2	3.89	1.90	26.1	3.99	1.92	29.4	4.29	2.01
	70	12.5	2.38	1.55	14.7	2.65	1.62	15.6	2.75	1.66	18.6	3.08	1.77	21.6	3.37	1.88	23.7	3.56	1.95	24.6	3.63	1.99	27.6	3.86	2.10
	80	12.0	2.30	1.53	13.9	2.53	1.61	14.7	2.62	1.65	17.5	2.89	1.78	20.3	3.13	1.90	22.2	3.28	1.99	23.1	3.34	2.03	25.8	3.52	2.15
700	60	13.2	2.37	1.63	15.5	2.70	1.69	16.5	2.83	1.71	19.8	3.24	1.79	23.1	3.62	1.87	25.4	3.87	1.93	26.4	3.97	1.95	29.8	4.29	2.03
	70	12.7	2.33	1.59	14.8	2.60	1.67	15.7	2.71	1.70	18.8	3.05	1.81	21.9	3.35	1.91	24.0	3.54	1.99	24.9	3.62	2.02	28.0	3.86	2.13
	80	12.1	2.26	1.57	14.1	2.49	1.65	14.9	2.58	1.69	17.7	2.86	1.82	20.6	3.11	1.94	22.6	3.26	2.03	23.4	3.32	2.07	26.3	3.51	2.19
800	60	13.3	2.33	1.67	15.6	2.66	1.73	16.7	2.79	1.75	20.0	3.21	1.83	23.3	3.60	1.90	25.7	3.85	1.96	26.7	3.96	1.98	30.0	4.29	2.05
	70	12.8	2.29	1.63	14.9	2.57	1.70	15.9	2.68	1.74	19.0	3.03	1.84	22.1	3.33	1.95	24.3	3.53	2.02	25.2	3.61	2.05	28.4	3.86	2.15
	80	12.2	2.23	1.61	14.2	2.46	1.69	15.1	2.55	1.73	17.9	2.83	1.86	20.8	3.07	1.98	22.8	3.23	2.07	23.6	3.29	2.11	26.5	3.48	2.23

FT4BE-030K with B6BM-X30K-(A,B)

		OUTDOOR TEMPERATURE (Deg. F)																							
CFM	Indoor T. Deg.F	10			17			20			30			40			47			50			60		
		MBH	COP	kW	MBH	COP	kW	MBH	COP	kW	MBH	COP	kW	MBH	COP	kW	MBH	COP	kW	MBH	COP	kW	MBH	COP	kW
785	60	15.8	2.62	1.76	18.5	2.91	1.87	19.7	3.03	1.91	23.7	3.38	2.05	27.6	3.68	2.20	30.3	3.87	2.30	31.5	3.95	2.34	35.5	4.18	2.49
	70	15.1	2.53	1.75	17.7	2.78	1.87	18.9	2.87	1.93	22.6	3.15	2.10	26.3	3.39	2.27	28.9	3.54	2.39	30.0	3.60	2.44	33.7	3.78	2.62
	80	14.6	2.43	1.76	17.0	2.63	1.90	18.1	2.71	1.95	21.5	2.94	2.15	25.0	3.14	2.34	27.5	3.25	2.47	28.5	3.30	2.53	32.0	3.44	2.72
885	60	15.8	2.57	1.80	18.6	2.87	1.90	19.8	2.99	1.94	23.8	3.35	2.09	27.8	3.67	2.23	30.7	3.87	2.32	31.9	3.95	2.37	35.9	4.19	2.51
	70	15.3	2.49	1.80	17.9	2.74	1.92	19.0	2.84	1.97	22.8	3.13	2.13	26.6	3.38	2.30	29.2	3.54	2.42	30.3	3.60	2.47	34.1	3.79	2.64
	80	14.7	2.39	1.80	17.2	2.60	1.93	18.2	2.68	1.99	21.8	2.93	2.18	25.3	3.13	2.37	27.8	3.25	2.51	28.9	3.30	2.56	32.4	3.45	2.75
985	60	15.9	2.53	1.85	18.8	2.83	1.94	20.0	2.96	1.98	24.0	3.33	2.12	28.1	3.65	2.25	30.9	3.86	2.35	32.1	3.94	2.39	36.2	4.20	2.53
	70	15.4	2.46	1.83	18.1	2.72	1.95	19.2	2.82	2.00	23.0	3.12	2.16	26.8	3.38	2.33	29.5	3.54	2.44	30.6	3.60	2.49	34.5	3.80	2.66
	80	14.8	2.36	1.84	17.3	2.58	1.97	18.4	2.66	2.03	21.9	2.90	2.21	25.5	3.11	2.40	28.0	3.24	2.54	29.1	3.29	2.59	32.6	3.44	2.78

FT4BE-036K with B6EMMX36K-C

		OUTDOOR TEMPERATURE (Deg. F)																							
CFM	Indoor T. Deg.F	10			17			20			30			40			47			50			60		
		MBH	COP	kW	MBH	COP	kW	MBH	COP	kW	MBH	COP	kW	MBH	COP	kW	MBH	COP	kW	MBH	COP	kW	MBH	COP	kW
1120	60	17.9	2.64	1.99	21.2	2.96	2.10	22.6	3.09	2.15	27.3	3.49	2.30	32.0	3.83	2.45	35.3	4.05	2.56	36.7	4.14	2.60	41.4	4.41	2.76
	70	17.3	2.51	2.02	20.4	2.79	2.14	21.7	2.90	2.20	26.2	3.24	2.37	30.7	3.53	2.55	33.9	3.71	2.67	35.2	3.79	2.73	39.7	4.01	2.91
	80	16.7	2.37	2.06	19.7	2.62	2.20	21.0	2.72	2.26	25.2	3.01	2.45	29.5	3.26	2.65	32.5	3.41	2.79	33.7	3.48	2.85	38.0	3.66	3.04
1270	60	18.1	2.59	2.05	21.4	2.92	2.15	22.9	3.05	2.19	27.7	3.46	2.34	32.4	3.83	2.49	35.8	4.05	2.59	37.2	4.15	2.63	42.0	4.44	2.78
	70	17.5	2.46	2.08	20.6	2.75	2.20	22.0	2.87	2.25	26.6	3.22	2.42	31.1	3.53	2.59	34.3	3.72	2.71	35.7	3.80	2.76	40.3	4.03	2.93
	80	16.8	2.33	2.12	19.9	2.59	2.25	21.2	2.69	2.31	25.6	3.00	2.50	29.9	3.26	2.69	33.0	3.42	2.82	34.3	3.49	2.88	38.6	3.69	3.07
1420	60	18.2	2.54	2.10	21.6	2.88	2.20	23.1	3.02	2.24	27.9	3.44	2.38	32.8	3.81	2.52	36.2	4.05	2.62	37.7	4.15	2.66	42.5	4.45	2.81
	70	17.7	2.43	2.13	20.9	2.73	2.25	22.3	2.85	2.29	26.9	3.21	2.46	31.5	3.52	2.62	34.8	3.72	2.74	36.2	3.80	2.79	40.8	4.05	2.95
	80	17.1	2.30	2.17	20.1	2.56	2.30	21.4	2.67	2.36	25.8	2.98	2.54	30.2	3.25	2.73	33.3	3.42	2.86	34.6	3.48	2.91	39.0	3.69	3.10

14 SEER HEATING EXPANDED RATINGS (CONTINUED)

FT4BE-042K with B6BM-X42K-B

		OUTDOOR TEMPERATURE (Deg. F)																							
CFM	Indoor T. Deg.F	10			17			20			30			40			47			50			60		
		MBH	COP	kW	MBH	COP	kW	MBH	COP	kW	MBH	COP	kW	MBH	COP	kW	MBH	COP	kW	MBH	COP	kW	MBH	COP	kW
1175	60	22.9	2.72	2.47	26.4	3.04	2.55	27.9	3.17	2.59	33.0	3.58	2.70	38.0	3.96	2.81	41.5	4.21	2.89	43.0	4.31	2.92	48.0	4.64	3.04
	70	22.1	2.53	2.57	25.5	2.82	2.66	27.0	2.93	2.70	31.8	3.31	2.82	36.6	3.64	2.95	40.0	3.86	3.04	41.5	3.96	3.08	46.3	4.24	3.20
	80	21.6	2.36	2.69	24.8	2.62	2.78	26.2	2.72	2.82	30.8	3.06	2.96	35.4	3.36	3.09	38.6	3.55	3.19	40.0	3.63	3.23	44.6	3.89	3.37
1325	60	23.1	2.69	2.52	26.7	3.01	2.59	28.2	3.15	2.63	33.3	3.57	2.73	38.4	3.97	2.84	42.0	4.22	2.91	43.5	4.33	2.95	48.6	4.67	3.05
	70	22.4	2.51	2.62	25.8	2.80	2.70	27.3	2.92	2.74	32.2	3.30	2.86	37.1	3.65	2.98	40.5	3.88	3.06	42.0	3.97	3.10	46.9	4.27	3.22
	80	21.8	2.33	2.73	25.1	2.60	2.83	26.5	2.71	2.86	31.2	3.05	2.99	35.9	3.37	3.12	39.1	3.57	3.21	40.6	3.66	3.25	45.2	3.92	3.38
1475	60	23.1	2.64	2.56	26.8	2.98	2.64	28.3	3.12	2.67	33.5	3.55	2.77	38.7	3.96	2.87	42.4	4.22	2.94	44.0	4.33	2.98	49.2	4.68	3.08
	70	22.6	2.49	2.66	26.1	2.79	2.74	27.6	2.91	2.78	32.5	3.30	2.89	37.5	3.65	3.01	41.0	3.89	3.09	42.4	3.99	3.12	47.4	4.29	3.24
	80	22.0	2.32	2.78	25.3	2.59	2.87	26.7	2.70	2.90	31.5	3.05	3.03	36.2	3.37	3.15	39.5	3.58	3.24	40.9	3.66	3.28	45.7	3.94	3.40

FT4BE-048K with B6BM-X60K-C

		OUTDOOR TEMPERATURE (Deg. F)																							
CFM	Indoor T. Deg.F	10			17			20			30			40			47			50			60		
		MBH	COP	kW	MBH	COP	kW	MBH	COP	kW	MBH	COP	kW	MBH	COP	kW	MBH	COP	kW	MBH	COP	kW	MBH	COP	kW
1375	60	23.5	2.54	2.71	28.0	2.91	2.82	30.0	3.06	2.87	36.5	3.53	3.03	43.0	3.95	3.19	47.5	4.22	3.30	49.5	4.33	3.35	56.0	4.68	3.51
	70	22.7	2.33	2.85	27.1	2.68	2.97	29.0	2.81	3.02	35.3	3.24	3.19	41.7	3.63	3.37	46.1	3.87	3.49	48.0	3.97	3.54	54.3	4.29	3.72
	80	22.1	2.16	3.00	26.4	2.47	3.13	28.2	2.60	3.19	34.4	2.99	3.37	40.5	3.33	3.56	44.7	3.55	3.69	46.6	3.64	3.75	52.7	3.93	3.93
1575	60	23.7	2.51	2.77	28.3	2.89	2.87	30.3	3.05	2.92	37.0	3.53	3.07	43.6	3.97	3.22	48.2	4.26	3.32	50.2	4.37	3.37	56.8	4.74	3.52
	70	23.0	2.32	2.90	27.5	2.67	3.02	29.4	2.81	3.07	35.8	3.25	3.23	42.2	3.65	3.39	46.7	3.91	3.51	48.7	4.01	3.55	55.1	4.34	3.72
	80	22.4	2.14	3.06	26.7	2.46	3.18	28.6	2.59	3.24	34.8	2.99	3.41	41.0	3.36	3.58	45.4	3.59	3.71	47.3	3.69	3.76	53.5	3.99	3.93
1775	60	23.8	2.48	2.82	28.5	2.87	2.92	30.6	3.02	2.96	37.3	3.52	3.11	44.1	3.97	3.25	48.8	4.27	3.35	50.8	4.39	3.40	57.6	4.77	3.54
	70	23.3	2.31	2.96	27.8	2.66	3.07	29.8	2.80	3.11	36.3	3.26	3.27	42.8	3.66	3.42	47.3	3.93	3.53	49.3	4.04	3.58	55.8	4.38	3.73
	80	22.6	2.13	3.12	27.0	2.45	3.23	28.9	2.58	3.28	35.2	3.00	3.45	41.5	3.37	3.61	45.9	3.61	3.73	47.8	3.71	3.78	54.1	4.03	3.94

FT4BE-060K with B6EMMX60K-C

		OUTDOOR TEMPERATURE (Deg. F)																							
CFM	Indoor T. Deg.F	10			17			20			30			40			47			50			60		
		MBH	COP	kW	MBH	COP	kW	MBH	COP	kW	MBH	COP	kW	MBH	COP	kW	MBH	COP	kW	MBH	COP	kW	MBH	COP	kW
1510	60	31.5	2.66	3.48	37.4	2.99	3.68	40.0	3.12	3.76	48.4	3.51	4.04	56.8	3.86	4.32	62.7	4.07	4.52	65.3	4.16	4.60	73.7	4.43	4.88
	70	30.6	2.40	3.74	36.4	2.71	3.94	38.9	2.83	4.03	47.2	3.20	4.32	55.5	3.53	4.61	61.3	3.73	4.82	63.8	3.81	4.90	72.1	4.07	5.20
	80	30.1	2.20	4.01	35.7	2.48	4.23	38.2	2.59	4.32	46.3	2.93	4.63	54.3	3.22	4.95	60.0	3.41	5.16	62.4	3.48	5.26	70.5	3.71	5.57
1710	60	31.8	2.65	3.52	37.8	2.99	3.70	40.4	3.13	3.78	48.9	3.54	4.05	57.5	3.91	4.31	63.4	4.13	4.50	66.0	4.23	4.58	74.6	4.51	4.85
	70	30.9	2.41	3.77	36.8	2.72	3.96	39.3	2.85	4.04	47.7	3.24	4.32	56.1	3.58	4.60	61.9	3.79	4.79	64.5	3.88	4.87	72.8	4.15	5.15
	80	30.3	2.19	4.05	36.0	2.48	4.25	38.5	2.60	4.34	46.7	2.96	4.63	54.9	3.27	4.92	60.7	3.47	5.12	63.1	3.55	5.21	71.3	3.80	5.50
1910	60	31.8	2.63	3.55	37.9	2.98	3.73	40.5	3.12	3.81	49.2	3.55	4.07	58.0	3.92	4.33	64.1	4.16	4.51	66.7	4.26	4.59	75.4	4.56	4.85
	70	31.3	2.41	3.81	37.2	2.73	4.00	39.7	2.86	4.08	48.2	3.26	4.34	56.6	3.61	4.60	62.5	3.83	4.78	65.1	3.92	4.86	73.5	4.20	5.13
	80	30.6	2.19	4.09	36.4	2.49	4.28	38.9	2.61	4.36	47.2	2.98	4.64	55.4	3.31	4.91	61.2	3.52	5.10	63.7	3.60	5.18	72.0	3.87	5.45

HEAT PUMP EXPANDED RATINGS + VSB

FT4BE-018K with B6VMAX24K-(A,B)

ODT			75°F			85°F			95°F			105°F			115°F		
CFM	E.D.B.	E.W.B.	T.C.	S.C.	K.W.	T.C.	S.C.	K.W.	T.C.	S.C.	K.W.	T.C.	S.C.	K.W.	T.C.	S.C.	K.W.
575	80	62	19.6	17.5	1.14	18.7	17.2	1.26	17.8	16.9	1.41	16.8	16.5	1.57	15.8	15.6	1.75
	80	67	21.2	14.6	1.14	20.3	14.2	1.26	19.3	13.8	1.41	18.1	13.4	1.57	16.9	12.9	1.75
	80	72	23.1	11.6	1.14	22.1	11.2	1.26	20.9	10.8	1.41	19.7	10.4	1.57	18.3	9.9	1.76
	75	63	19.3	14.8	1.14	18.5	14.4	1.26	17.6	13.9	1.41	16.5	13.5	1.57	15.4	13.0	1.75
675	80	62	20.3	19.0	1.14	19.4	18.6	1.26	18.4	18.0	1.41	17.6	17.6	1.57	16.6	16.6	1.75
	80	67	21.8	15.9	1.14	20.8	15.5	1.26	19.0	15.0	1.41	18.6	14.6	1.57	17.3	14.0	1.76
	80	72	23.6	12.4	1.14	22.5	12.0	1.26	21.4	11.6	1.41	20.1	11.1	1.58	18.7	10.7	1.76
	75	63	20.0	16.1	1.14	19.1	15.6	1.26	18.1	15.2	1.41	17.0	14.7	1.57	15.8	14.1	1.75
775	80	62	21.1	20.0	1.15	20.2	19.6	1.26	19.3	19.0	1.41	18.3	18.2	1.57	17.2	17.1	1.75
	80	67	22.3	17.1	1.15	21.3	16.6	1.26	20.1	16.2	1.41	18.9	15.7	1.57	17.6	15.2	1.76
	80	72	24.1	13.2	1.14	22.9	12.7	1.26	21.7	12.3	1.41	20.4	11.9	1.58	19.0	11.4	1.76
	75	63	20.4	17.3	1.15	19.5	16.8	1.26	18.4	16.3	1.41	17.3	15.8	1.57	16.2	15.2	1.75

FT4BE-024K with B6VMAX24K-(A,B)

O.D.T			75°F			85°F			95°F			105°F			115°F		
CFM	E.D.B.	E.W.B.	T.C.	S.C.	K.W.	T.C.	S.C.	K.W.	T.C.	S.C.	K.W.	T.C.	S.C.	K.W.	T.C.	S.C.	K.W.
575	80	62	23.1	18.9	1.40	22.1	18.6	1.55	21.0	18.3	1.73	19.9	18.0	1.93	18.7	17.4	2.16
	80	67	25.1	15.9	1.40	24.0	15.4	1.55	22.8	15.0	1.73	21.6	14.4	1.94	20.2	13.9	2.17
	80	72	27.6	12.8	1.40	26.3	12.4	1.55	25.0	11.9	1.74	23.5	11.4	1.95	21.9	10.9	2.18
	75	63	22.9	16.3	1.40	21.9	15.8	1.55	20.9	15.3	1.73	19.8	14.7	1.93	18.5	14.2	2.17
675	80	62	23.9	20.6	1.40	22.8	20.2	1.55	21.8	19.9	1.73	20.6	19.9	1.94	19.3	19.1	2.17
	80	67	25.9	17.1	1.40	24.7	16.6	1.55	23.4	16.1	1.73	22.2	15.6	1.94	20.8	15.0	2.17
	80	72	28.0	13.6	1.41	26.7	13.1	1.55	25.4	12.7	1.73	24.0	12.2	1.95	22.4	11.6	2.18
	75	63	23.7	17.5	1.40	22.6	17.0	1.55	21.6	16.5	1.73	20.3	15.9	1.93	19.0	15.3	2.17
775	80	62	24.5	22.5	1.41	23.5	21.9	1.55	22.4	21.6	1.73	21.2	21.2	1.94	20.0	20.0	2.17
	80	67	26.5	18.2	1.41	25.3	17.7	1.55	24.0	17.2	1.73	22.7	16.7	1.94	21.2	16.1	2.17
	80	72	28.6	14.3	1.41	27.3	13.9	1.55	25.9	13.4	1.74	24.5	12.9	1.95	22.8	12.3	2.18
	75	63	24.3	18.7	1.41	23.2	18.2	1.55	22.1	17.6	1.73	20.8	17.1	1.94	19.4	16.4	2.17

FT4BE-030K with B6VMAX30K-(A,B)

O.D.T			75°F			85°F			95°F			105°F			115°F		
CFM	E.D.B.	E.W.B.	T.C.	S.C.	K.W.	T.C.	S.C.	K.W.	T.C.	S.C.	K.W.	T.C.	S.C.	K.W.	T.C.	S.C.	K.W.
860	80	62	28.2	24.7	1.72	27.0	24.2	1.90	25.8	23.9	2.11	24.4	23.5	2.35	22.8	22.5	2.62
	80	67	30.5	21.0	1.71	29.2	20.4	1.90	27.9	19.9	2.10	26.3	19.3	2.34	24.6	18.6	2.61
	80	72	30.6	21.1	1.71	29.2	20.4	1.90	27.9	19.9	2.10	26.3	19.3	2.34	24.6	18.6	2.61
	75	63	28.0	20.9	1.72	26.8	20.3	1.90	25.5	19.8	2.11	24.1	19.2	2.35	22.4	18.5	2.62
960	80	62	29.0	26.3	1.72	27.7	25.8	1.90	26.4	25.3	2.11	25.1	25.0	2.35	23.6	23.6	2.62
	80	67	31.2	22.3	1.72	29.8	21.7	1.89	28.4	21.1	2.10	26.8	20.5	2.34	25.0	19.8	2.61
	80	72	31.3	22.4	1.72	29.8	21.7	1.89	28.4	21.1	2.10	26.8	20.5	2.34	25.0	19.8	2.61
	75	63	28.6	22.2	1.72	27.3	21.6	1.90	26.0	21.0	2.11	24.5	20.4	2.35	22.9	19.7	2.62
1060	80	62	29.5	28.0	1.73	28.3	27.4	1.90	27.1	26.7	2.11	25.8	25.8	2.34	24.3	24.3	2.61
	80	67	31.8	23.6	1.73	30.3	22.9	1.90	28.8	22.4	2.10	27.2	21.7	2.34	25.4	21.0	2.61
	80	72	31.8	23.7	1.73	30.3	22.9	1.90	28.8	22.4	2.10	27.2	21.7	2.34	25.4	21.0	2.61
	75	63	29.2	23.5	1.73	27.8	22.8	1.90	26.5	22.2	2.11	25.0	21.6	2.35	23.3	20.8	2.62

FT4BE-036K with B6VMAX36K-B

O.D.T			75°F			85°F			95°F			105°F			115°F		
CFM	E.D.B.	E.W.B.	T.C.	S.C.	K.W.	T.C.	S.C.	K.W.	T.C.	S.C.	K.W.	T.C.	S.C.	K.W.	T.C.	S.C.	K.W.
1025	80	62	34.9	31.2	2.09	33.4	30.6	2.31	31.8	30.1	2.57	30.1	29.4	2.85	28.3	27.9	3.19
	80	67	37.8	26.9	2.10	36.1	26.1	2.32	34.4	25.4	2.58	32.4	24.6	2.86	30.2	23.7	3.19
	80	72	41.2	21.4	2.11	39.4	20.7	2.34	37.4	20.0	2.59	35.2	19.3	2.88	32.9	18.4	3.21
	75	63	34.6	26.4	2.09	33.1	25.6	2.32	31.5	24.9	2.57	29.6	24.1	2.85	27.7	23.3	3.19
1125	80	62	35.7	32.7	2.10	34.1	32.0	2.32	32.4	31.4	2.57	30.8	30.8	2.86	29.1	29.0	3.19
	80	67	38.4	28.1	2.11	36.7	27.4	2.33	34.8	26.6	2.58	32.8	25.8	2.86	30.6	24.9	3.19
	80	72	41.8	22.2	2.12	39.8	21.5	2.34	37.8	20.8	2.59	35.7	20.0	2.88	33.2	19.2	3.21
	75	63	35.2	27.7	2.10	33.6	26.9	2.32	31.9	26.1	2.57	30.1	25.3	2.86	28.0	24.4	3.19
1225	80	62	36.2	34.4	2.12	34.7	33.6	2.32	33.2	32.7	2.57	31.6	31.5	2.86	29.7	29.7	3.19
	80	67	39.0	29.3	2.12	37.1	28.6	2.33	35.3	27.8	2.58	33.2	27.0	2.87	31.0	26.1	3.19
	80	72	42.2	23.0	2.13	40.2	22.3	2.34	38.3	21.6	2.60	36.0	20.8	2.88	33.6	20.0	3.21
	75	63	35.7	28.9	2.11	34.1	28.1	2.32	32.4	27.3	2.57	30.5	26.5	2.86	28.4	25.5	3.19

HEAT PUMP EXPANDED RATINGS + VSB (CONTINUED)

FT4BE-042K with B6VMAX48K-(B,C)

O.D.T			75°F			85°F			95°F			105°F			115°F		
CFM	E.D.B.	E.W.B.	T.C.	S.C.	K.W.	T.C.	S.C.	K.W.	T.C.	S.C.	K.W.	T.C.	S.C.	K.W.	T.C.	S.C.	K.W.
1115	80	62	39.2	33.4	2.46	37.5	32.7	2.73	35.8	32.2	3.01	33.8	31.8	3.34	31.8	30.6	3.71
	80	67	42.5	29.1	2.47	40.6	28.3	2.74	38.8	27.3	3.03	36.7	26.4	3.36	34.3	25.4	3.74
	80	72	46.4	23.5	2.49	44.3	22.7	2.76	42.1	22.0	3.05	39.7	21.1	3.39	37.2	20.2	3.76
	75	63	38.9	28.4	2.46	37.2	27.6	2.73	35.5	26.8	3.02	33.5	26.0	3.34	31.4	25.0	3.71
1315	80	62	40.6	36.4	2.48	38.8	35.6	2.73	37.0	35.0	3.02	35.2	34.7	3.35	33.0	33.0	3.73
	80	67	43.9	31.3	2.49	41.9	30.5	2.75	39.5	29.6	3.04	37.6	28.7	3.37	35.2	27.7	3.74
	80	72	47.4	25.1	2.51	45.2	24.2	2.76	43.0	23.4	3.06	40.7	22.6	3.39	38.0	21.6	3.77
	75	63	40.2	30.8	2.48	38.3	30.0	2.73	36.5	29.1	3.03	34.5	28.2	3.35	32.2	27.2	3.72
1515	80	62	41.9	39.1	2.50	40.1	38.2	2.74	38.2	37.6	3.03	36.3	36.3	3.36	34.3	34.2	3.74
	80	67	44.9	33.6	2.50	42.8	32.7	2.75	40.7	31.8	3.04	38.4	30.9	3.38	35.8	29.8	3.74
	80	72	48.4	26.6	2.52	46.1	25.7	2.77	43.8	24.9	3.07	41.4	24.0	3.40	38.6	23.0	3.77
	75	63	41.2	33.1	2.49	39.3	32.2	2.74	37.4	31.3	3.03	35.2	30.3	3.36	32.9	29.2	3.73

FT4BE-048K with B6VMAX48K-C

ODT			75°F			85°F			95°F			105°F			115°F		
CFM	E.D.B.	E.W.B.	T.C.	S.C.	K.W.	T.C.	S.C.	K.W.	T.C.	S.C.	K.W.	T.C.	S.C.	K.W.	T.C.	S.C.	K.W.
1460	80	62	45.7	40.5	2.95	43.8	39.8	3.27	41.7	39.1	3.61	39.5	38.3	4.00	37.2	36.6	4.44
	80	67	49.3	34.9	2.97	47.1	33.9	3.29	44.9	32.9	3.63	42.5	31.9	4.02	39.7	30.8	4.45
	80	72	53.4	28.0	2.98	51.0	27.1	3.31	48.5	26.2	3.65	45.9	25.2	4.04	43.0	24.1	4.47
	75	63	45.2	34.4	2.95	43.2	33.4	3.27	41.2	32.5	3.62	38.9	31.4	4.00	36.4	30.3	4.44
1660	80	62	47.1	43.2	2.97	45.0	42.3	3.28	42.8	41.5	3.62	40.7	40.7	4.01	38.5	38.5	4.45
	80	67	50.5	37.2	2.98	48.2	36.1	3.29	45.5	35.2	3.63	43.3	34.1	4.02	40.5	32.9	4.46
	80	72	54.4	29.5	3.00	51.9	28.6	3.31	49.4	27.6	3.65	46.6	26.6	4.04	43.6	25.5	4.48
	75	63	46.3	36.7	2.97	44.2	35.6	3.28	42.1	34.7	3.62	39.7	33.6	4.01	37.1	32.4	4.44
1860	80	62	48.1	45.7	2.99	46.0	44.6	3.28	44.1	43.5	3.63	42.0	41.9	4.02	39.6	39.6	4.45
	80	67	51.4	39.4	3.00	49.0	38.3	3.30	46.6	37.3	3.64	44.0	36.2	4.03	41.1	35.0	4.46
	80	72	55.3	31.0	3.02	52.6	30.0	3.32	50.1	29.0	3.66	47.3	28.0	4.04	44.2	26.9	4.48
	75	63	47.2	38.9	2.99	45.0	37.8	3.28	42.8	36.7	3.62	40.4	35.6	4.01	37.8	34.3	4.45

FT4BE-060K with B6VMAX60K-C

ODT			75°F			85°F			95°F			105°F			115°F		
CFM	E.D.B.	E.W.B.	T.C.	S.C.	K.W.	T.C.	S.C.	K.W.	T.C.	S.C.	K.W.	T.C.	S.C.	K.W.	T.C.	S.C.	K.W.
1460	80	62	58.4	46.7	3.93	55.8	45.8	4.35	53.2	45.0	4.82	50.3	44.4	5.36	47.0	42.7	5.97
	80	67	63.4	40.5	3.98	60.6	39.4	4.41	57.8	38.2	4.89	54.6	36.8	5.42	51.0	35.4	6.03
	80	72	69.5	33.1	4.06	66.4	32.0	4.50	63.1	30.8	4.97	59.6	29.6	5.50	55.5	28.2	6.11
	75	63	58.1	40.5	3.94	55.6	39.3	4.36	53.0	38.1	4.82	50.1	36.5	5.36	46.8	35.0	5.96
1660	80	62	60.1	50.0	3.96	57.4	49.0	4.37	54.7	48.2	4.84	51.7	48.2	5.38	48.3	46.4	5.99
	80	67	65.2	43.1	4.02	62.2	41.9	4.43	59.0	40.7	4.91	55.9	39.0	5.44	52.2	37.5	6.05
	80	72	71.0	34.8	4.10	67.7	33.6	4.52	64.3	32.5	4.98	60.4	31.2	5.52	56.3	29.7	6.12
	75	63	59.8	42.7	3.96	57.1	41.5	4.37	54.4	40.3	4.84	51.3	38.9	5.38	47.9	37.4	5.98
1860	80	62	61.4	53.9	4.01	58.8	52.6	4.39	56.0	52.0	4.86	52.9	51.0	5.40	49.5	48.7	6.00
	80	67	66.7	45.1	4.05	63.6	43.9	4.45	60.5	42.7	4.93	57.0	41.2	5.46	53.1	39.7	6.06
	80	72	72.0	36.4	4.13	68.6	35.2	4.54	65.2	34.0	5.01	61.4	32.6	5.54	57.2	31.1	6.14
	75	63	61.3	45.1	3.99	58.5	43.9	4.39	55.5	42.6	4.86	52.3	41.2	5.40	48.8	39.6	6.00

HEAT PUMP EXPANDED RATINGS + VSB HEATING

FT4BE-018K with B6VMAX24K-(A,B)

		OUTDOOR TEMPERATURE (Deg. F)																							
CFM	Indoor T. Deg.F	10			17			20			30			40			47			50			60		
		MBH	COP	kW	MBH	COP	kW	MBH	COP	kW	MBH	COP	kW	MBH	COP	kW	MBH	COP	kW	MBH	COP	kW	MBH	COP	kW
510	60	10.0	2.13	1.38	12.0	2.50	1.40	12.8	2.66	1.41	15.5	3.17	1.43	18.2	3.66	1.46	20.2	4.00	1.48	21.0	4.14	1.49	23.7	4.59	1.51
	70	9.5	2.14	1.31	11.3	2.46	1.34	12.0	2.59	1.36	14.5	3.01	1.41	17.0	3.40	1.46	18.7	3.66	1.50	19.5	3.77	1.51	21.9	4.11	1.56
	80	8.9	2.09	1.25	10.5	2.37	1.30	11.2	2.49	1.32	13.4	2.85	1.38	15.6	3.19	1.44	17.2	3.40	1.48	17.9	3.49	1.50	20.1	3.78	1.56
610	60	10.1	2.08	1.42	12.0	2.45	1.44	12.9	2.61	1.45	15.7	3.12	1.47	18.5	3.61	1.50	20.4	3.95	1.52	21.3	4.09	1.52	24.1	4.56	1.55
	70	9.6	2.08	1.36	11.4	2.40	1.39	12.2	2.53	1.41	14.7	2.96	1.46	17.2	3.36	1.51	19.0	3.62	1.54	19.8	3.73	1.55	22.3	4.08	1.60
	80	9.0	2.05	1.29	10.7	2.33	1.34	11.3	2.45	1.36	13.6	2.81	1.42	16.0	3.14	1.49	17.6	3.35	1.54	18.3	3.44	1.56	20.6	3.72	1.62
710	60	10.3	2.05	1.47	12.2	2.42	1.49	13.1	2.57	1.49	15.9	3.08	1.51	18.7	3.58	1.53	20.7	3.92	1.55	21.5	4.07	1.55	24.3	4.54	1.57
	70	9.7	2.04	1.40	11.5	2.37	1.43	12.3	2.50	1.44	14.9	2.93	1.49	17.5	3.33	1.54	19.3	3.59	1.57	20.1	3.70	1.59	22.7	4.06	1.64
	80	9.2	2.01	1.34	10.8	2.29	1.38	11.5	2.40	1.40	13.8	2.76	1.47	16.1	3.08	1.54	17.7	3.29	1.58	18.4	3.38	1.60	20.8	3.65	1.67

FT4BE-024K with B6VMAX24K-(A,B)

		OUTDOOR TEMPERATURE (Deg. F)																							
CFM	Indoor T. Deg.F	10			17			20			30			40			47			50			60		
		MBH	COP	kW	MBH	COP	kW	MBH	COP	kW	MBH	COP	kW	MBH	COP	kW	MBH	COP	kW	MBH	COP	kW	MBH	COP	kW
600	60	12.7	2.40	1.55	15.0	2.74	1.61	16.0	2.88	1.63	19.2	3.31	1.70	22.5	3.71	1.77	24.8	3.97	1.83	25.7	4.08	1.85	29.0	4.42	1.92
	70	12.1	2.36	1.51	14.3	2.65	1.58	15.2	2.76	1.61	18.2	3.12	1.71	21.2	3.44	1.81	23.3	3.64	1.88	24.2	3.72	1.91	27.2	3.98	2.01
	80	11.6	2.28	1.48	13.5	2.53	1.56	14.3	2.63	1.60	17.1	2.93	1.71	19.9	3.20	1.82	21.8	3.36	1.90	22.7	3.43	1.94	25.4	3.64	2.05
700	60	12.8	2.35	1.60	15.1	2.69	1.65	16.1	2.83	1.67	19.4	3.27	1.74	22.7	3.68	1.81	25.0	3.95	1.86	26.0	4.06	1.88	29.4	4.41	1.95
	70	12.3	2.31	1.56	14.4	2.60	1.62	15.3	2.72	1.65	18.4	3.08	1.75	21.5	3.41	1.84	23.6	3.62	1.91	24.5	3.71	1.94	27.6	3.97	2.04
	80	11.7	2.25	1.52	13.7	2.50	1.60	14.5	2.60	1.64	17.3	2.90	1.75	20.2	3.17	1.87	22.2	3.34	1.95	23.0	3.41	1.98	25.9	3.62	2.10
800	60	12.9	2.31	1.64	15.2	2.65	1.69	16.3	2.79	1.71	19.6	3.24	1.77	22.9	3.66	1.84	25.3	3.93	1.89	26.3	4.05	1.91	29.6	4.41	1.97
	70	12.4	2.28	1.59	14.5	2.57	1.66	15.5	2.69	1.69	18.6	3.06	1.78	21.7	3.39	1.88	23.9	3.61	1.94	24.8	3.69	1.97	28.0	3.97	2.07
	80	11.8	2.21	1.56	13.8	2.46	1.64	14.7	2.56	1.68	17.5	2.87	1.79	20.4	3.13	1.91	22.4	3.30	1.99	23.2	3.37	2.02	26.1	3.58	2.13

FT4BE-030K with B6VMAX30K-(A,B)

		OUTDOOR TEMPERATURE (Deg. F)																							
CFM	Indoor T. Deg.F	10			17			20			30			40			47			50			60		
		MBH	COP	kW	MBH	COP	kW	MBH	COP	kW	MBH	COP	kW	MBH	COP	kW	MBH	COP	kW	MBH	COP	kW	MBH	COP	kW
785	60	15.8	2.62	1.76	18.5	2.91	1.87	19.7	3.03	1.91	23.7	3.38	2.05	27.6	3.68	2.20	30.3	3.87	2.30	31.5	3.95	2.34	35.5	4.18	2.49
	70	15.1	2.53	1.75	17.7	2.78	1.87	18.9	2.87	1.93	22.6	3.15	2.10	26.3	3.39	2.27	28.9	3.54	2.39	30.0	3.60	2.44	33.7	3.78	2.62
	80	14.6	2.43	1.76	17.0	2.63	1.90	18.1	2.71	1.95	21.5	2.94	2.15	25.0	3.14	2.34	27.5	3.25	2.47	28.5	3.30	2.53	32.0	3.44	2.72
885	60	15.8	2.57	1.80	18.6	2.87	1.90	19.8	2.99	1.94	23.8	3.35	2.09	27.8	3.67	2.23	30.7	3.87	2.32	31.9	3.95	2.37	35.9	4.19	2.51
	70	15.3	2.49	1.80	17.9	2.74	1.92	19.0	2.84	1.97	22.8	3.13	2.13	26.6	3.38	2.30	29.2	3.54	2.42	30.3	3.60	2.47	34.1	3.79	2.64
	80	14.7	2.39	1.80	17.2	2.60	1.93	18.2	2.68	1.99	21.8	2.93	2.18	25.3	3.13	2.37	27.8	3.25	2.51	28.9	3.30	2.56	32.4	3.45	2.75
985	60	15.9	2.53	1.85	18.8	2.83	1.94	20.0	2.96	1.98	24.0	3.33	2.12	28.1	3.65	2.25	30.9	3.86	2.35	32.1	3.94	2.39	36.2	4.20	2.53
	70	15.4	2.46	1.83	18.1	2.72	1.95	19.2	2.82	2.00	23.0	3.12	2.16	26.8	3.38	2.33	29.5	3.54	2.44	30.6	3.60	2.49	34.5	3.80	2.66
	80	14.8	2.36	1.84	17.3	2.58	1.97	18.4	2.66	2.03	21.9	2.90	2.21	25.5	3.11	2.40	28.0	3.24	2.54	29.1	3.29	2.59	32.6	3.44	2.78

FT4BE-036K with B6VMAX36K-B

		OUTDOOR TEMPERATURE (Deg. F)																							
CFM	Indoor T. Deg.F	10			17			20			30			40			47			50			60		
		MBH	COP	kW	MBH	COP	kW	MBH	COP	kW	MBH	COP	kW	MBH	COP	kW	MBH	COP	kW	MBH	COP	kW	MBH	COP	kW
975	60	17.7	2.63	1.97	21.0	3.01	2.05	22.4	3.16	2.08	27.1	3.64	2.18	31.7	4.07	2.28	35.0	4.36	2.36	36.4	4.47	2.39	41.1	4.84	2.49
	70	17.0	2.51	1.99	20.2	2.84	2.08	21.5	2.98	2.12	26.0	3.39	2.24	30.4	3.77	2.37	33.5	4.01	2.45	34.9	4.10	2.49	39.3	4.41	2.62
	80	16.5	2.38	2.03	19.4	2.68	2.13	20.7	2.80	2.17	24.9	3.17	2.31	29.2	3.50	2.45	32.1	3.70	2.54	33.4	3.79	2.59	37.6	4.05	2.72
1125	60	17.8	2.58	2.03	21.2	2.96	2.10	22.6	3.12	2.13	27.4	3.61	2.22	32.1	4.06	2.32	35.5	4.35	2.39	36.9	4.47	2.42	41.6	4.85	2.52
	70	17.2	2.46	2.05	20.4	2.80	2.14	21.8	2.94	2.17	26.3	3.37	2.29	30.8	3.75	2.41	34.0	4.00	2.49	35.4	4.10	2.53	39.9	4.42	2.65
	80	16.6	2.33	2.09	19.7	2.64	2.18	20.9	2.76	2.22	25.3	3.14	2.36	29.6	3.48	2.49	32.6	3.70	2.59	33.9	3.78	2.63	38.2	4.06	2.76
1275	60	18.0	2.53	2.08	21.3	2.92	2.15	22.8	3.07	2.17	27.6	3.57	2.27	32.5	4.03	2.36	35.9	4.33	2.43	37.3	4.46	2.46	42.2	4.85	2.55
	70	17.4	2.43	2.10	20.6	2.77	2.18	22.0	2.91	2.22	26.6	3.35	2.33	31.2	3.74	2.45	34.5	3.99	2.53	35.8	4.10	2.56	40.4	4.43	2.68
	80	16.8	2.30	2.14	19.9	2.61	2.24	21.2	2.73	2.27	25.6	3.12	2.41	29.9	3.46	2.54	33.0	3.68	2.63	34.3	3.77	2.67	38.7	4.05	2.80

HEAT PUMP EXPANDED RATINGS + VSB HEATING (CONTINUED)

FT4BE-042K with B6VMAX48K-(B,C)

		OUTDOOR TEMPERATURE (Deg. F)																							
CFM	Indoor T. Deg.F	10			17			20			30			40			47			50			60		
		MBH	COP	kW	MBH	COP	kW	MBH	COP	kW	MBH	COP	kW	MBH	COP	kW	MBH	COP	kW	MBH	COP	kW	MBH	COP	kW
1175	60	21.0	2.68	2.30	24.8	3.03	2.40	26.4	3.17	2.45	31.8	3.60	2.59	37.2	3.99	2.74	41.0	4.23	2.84	42.6	4.33	2.88	48.0	4.65	3.03
	70	20.3	2.51	2.37	23.9	2.82	2.49	25.5	2.95	2.54	30.7	3.33	2.70	35.9	3.67	2.87	39.5	3.89	2.98	41.1	3.97	3.03	46.3	4.24	3.20
	80	19.8	2.35	2.46	23.2	2.63	2.59	24.7	2.74	2.64	29.7	3.09	2.82	34.7	3.39	3.00	38.1	3.57	3.13	39.6	3.65	3.18	44.6	3.89	3.36
1325	60	21.2	2.65	2.35	25.0	3.00	2.45	26.7	3.14	2.49	32.2	3.59	2.63	37.6	3.99	2.77	41.5	4.24	2.86	43.1	4.35	2.91	48.6	4.68	3.05
	70	20.5	2.48	2.42	24.2	2.80	2.53	25.8	2.93	2.58	31.0	3.32	2.74	36.3	3.68	2.90	40.0	3.90	3.01	41.6	3.99	3.06	46.8	4.28	3.21
	80	19.9	2.32	2.51	23.5	2.61	2.64	25.0	2.72	2.69	30.0	3.08	2.86	35.1	3.39	3.03	38.6	3.59	3.16	40.2	3.67	3.21	45.2	3.92	3.38
1475	60	21.3	2.60	2.40	25.2	2.96	2.49	26.8	3.11	2.53	32.4	3.56	2.67	38.0	3.98	2.80	41.9	4.24	2.90	43.6	4.35	2.94	49.1	4.69	3.07
	70	20.7	2.46	2.47	24.5	2.78	2.58	26.1	2.91	2.62	31.4	3.32	2.78	36.7	3.68	2.93	40.5	3.91	3.04	42.0	4.00	3.08	47.4	4.30	3.23
	80	20.1	2.30	2.56	23.7	2.59	2.68	25.2	2.71	2.73	30.3	3.07	2.90	35.4	3.39	3.07	39.0	3.59	3.18	40.5	3.68	3.23	45.7	3.94	3.40

FT4BE-048K with B6VMAX48K-C

		OUTDOOR TEMPERATURE (Deg. F)																							
CFM	Indoor T. Deg.F	10			17			20			30			40			47			50			60		
		MBH	COP	kW	MBH	COP	kW	MBH	COP	kW	MBH	COP	kW	MBH	COP	kW	MBH	COP	kW	MBH	COP	kW	MBH	COP	kW
1475	60	25.2	2.65	2.79	28.7	2.94	2.86	30.1	3.06	2.89	35.1	3.44	2.99	40.0	3.80	3.09	43.5	4.03	3.16	45.0	4.13	3.19	49.9	4.44	3.29
	70	24.4	2.44	2.93	27.7	2.70	3.01	29.2	2.81	3.04	33.9	3.16	3.15	38.7	3.48	3.26	42.0	3.70	3.33	43.5	3.78	3.37	48.2	4.07	3.48
	80	23.9	2.26	3.09	27.0	2.50	3.17	28.4	2.60	3.21	32.9	2.91	3.32	37.5	3.20	3.44	40.7	3.39	3.52	42.0	3.47	3.55	46.6	3.72	3.67
1625	60	25.4	2.63	2.83	28.9	2.93	2.89	30.4	3.05	2.92	35.4	3.44	3.02	40.5	3.81	3.11	44.0	4.06	3.18	45.5	4.16	3.21	50.5	4.48	3.30
	70	24.6	2.43	2.97	28.0	2.70	3.04	29.5	2.81	3.07	34.3	3.17	3.18	39.1	3.50	3.28	42.5	3.72	3.35	44.0	3.81	3.38	48.8	4.11	3.48
	80	24.0	2.25	3.14	27.3	2.49	3.21	28.6	2.59	3.24	33.3	2.91	3.35	37.9	3.21	3.46	41.1	3.41	3.53	42.5	3.50	3.57	47.2	3.77	3.67
1775	60	25.4	2.60	2.87	29.0	2.90	2.93	30.5	3.03	2.96	35.7	3.43	3.05	40.8	3.81	3.14	44.4	4.06	3.21	45.9	4.16	3.23	51.1	4.50	3.33
	70	24.9	2.42	3.01	28.3	2.69	3.08	29.7	2.81	3.11	34.6	3.17	3.21	39.5	3.51	3.30	43.0	3.74	3.37	44.4	3.83	3.40	49.3	4.13	3.50
	80	24.2	2.24	3.17	27.5	2.48	3.25	28.9	2.59	3.28	33.6	2.91	3.38	38.3	3.22	3.48	41.5	3.43	3.55	42.9	3.51	3.58	47.6	3.79	3.68

FT4BE-060K with B6VMAX60K-C

		OUTDOOR TEMPERATURE (Deg. F)																							
CFM	Indoor T. Deg.F	10			17			20			30			40			47			50			60		
		MBH	COP	kW	MBH	COP	kW	MBH	COP	kW	MBH	COP	kW	MBH	COP	kW	MBH	COP	kW	MBH	COP	kW	MBH	COP	kW
1450	60	32.8	2.65	3.62	36.8	2.87	3.76	38.6	2.96	3.82	44.4	3.24	4.02	50.2	3.49	4.21	54.3	3.66	4.35	56.1	3.73	4.41	61.9	3.94	4.61
	70	31.8	2.39	3.89	35.8	2.60	4.04	37.5	2.68	4.10	43.2	2.95	4.30	48.9	3.19	4.50	52.9	3.34	4.64	54.6	3.41	4.70	60.3	3.61	4.90
	80	31.3	2.19	4.19	35.2	2.38	4.34	36.8	2.45	4.40	42.3	2.69	4.61	47.7	2.90	4.82	51.5	3.05	4.96	53.2	3.10	5.03	58.6	3.29	5.23
1650	60	33.1	2.65	3.65	37.2	2.88	3.78	39.0	2.98	3.84	44.9	3.27	4.02	50.8	3.54	4.21	55.0	3.72	4.34	56.8	3.79	4.40	62.7	4.01	4.58
	70	32.2	2.41	3.92	36.2	2.62	4.05	37.9	2.71	4.11	43.7	2.98	4.30	49.5	3.24	4.48	53.5	3.40	4.61	55.2	3.47	4.67	61.0	3.68	4.86
	80	31.5	2.19	4.22	35.5	2.39	4.36	37.1	2.47	4.41	42.7	2.72	4.61	48.3	2.95	4.80	52.2	3.11	4.93	53.9	3.17	4.99	59.4	3.37	5.18
1850	60	33.1	2.63	3.69	37.3	2.87	3.81	39.1	2.97	3.87	45.2	3.28	4.05	51.3	3.56	4.23	55.6	3.74	4.36	57.4	3.82	4.41	63.5	4.06	4.59
	70	32.5	2.41	3.96	36.6	2.63	4.09	38.4	2.72	4.14	44.2	3.00	4.32	50.0	3.27	4.49	54.1	3.44	4.61	55.8	3.51	4.67	61.7	3.73	4.84
	80	31.9	2.19	4.26	35.8	2.40	4.38	37.5	2.48	4.44	43.1	2.74	4.61	48.8	2.99	4.79	52.7	3.15	4.91	54.4	3.21	4.97	60.1	3.43	5.14



GENERAL TERMS OF LIMITED WARRANTY

NORDYNE will furnish a replacement for any part of this product which fails in normal use and service within the first ten years of installation, in accordance with the terms of the warranty.

For complete details of the Limited Warranty, including applicable terms and conditions, see your local installer or contact the NORDYNE warranty department for a copy.



COMPLETE COMFORT. GENUINE VALUE. 8000 Phoenix Parkway | O'Fallon, MO 63368-3827

Specifications and illustrations subject to change without notice and without incurring obligations. Printed in U.S.A (05/2012)

199D-0512 (Replaces 199D-0112)