



**Submittal:DXH36ESK3IL** **Standard Efficiency Heat Pump**

Job Name:	Location:	Date:
Purchaser:	Engineer:	
Submitted To:	For:	
Unit Designation:	Schedule #:	

- Features:**
- Inverter-driven Compressor and Fan
  - Flared Piping Connections
  - Wireless Remote Controller Included
  - Anti-corrosion coils
  - Intelligent defrost
  - Auto-Restart
  - Easy diagnosis
  - Limited 5-year parts & 7-year compressor warranty



SYSTEM RATINGS	
Rated Cooling Capacity (Btu):	33,600
Minimum Cooling Capacity (Btu):	7,850
Maximum Cooling Capacity (Btu):	37,500
Rated Heating Capacity (Btu):	34,600
Minimum Heating Capacity (Btu):	10,000
Maximum Heating Capacity (Btu):	37,500
SEER:	21.00
EER:	10.6
HSPF:	8.5
COP:	10.4
METERING DEVICE	
Location	ODU
Type	EEV


OUTDOOR UNIT DATA	
<b>Compressor</b>	
Type:	Rotary
RLA:	16.0
<b>Fan Motor</b>	
Ouput Power(W):	90
RLA:	1.7
<b>Sound Pressure (dBA):</b>	62
<b>Physical Characteristics</b>	
Net Weight (lbs):	122.4
<b>Dimensions (in)</b>	
W:	39.3
H:	29.3
D:	16.8

Operation Range (Outdoor Ambient)	
Cooling (Min-Max)°F:	-4~122
Heating (Min-Max)°F:	-13~75
Power Supply	
Voltage (Min-Max):	187/253
Minimum Circuit Ampacity (MCA):	23
Max. Overcurrent Protection (MOCP):	35


Refrigerant Piping Data	
Refrigerant Type:	R-32
Pre-charged Amount (Oz):	56.4
Pre-Charged Length (ft):	24.6
Additional amount (Oz/ft.):	0.4
Max. Piping Length (ft):	131.2
Max. Piping Height (ft):	82.0
ODU Connection Size (Gas):	5/8"
ODU Connection Size (Liquid):	1/4"

Submittal: DXH36ESK3IL

Outdoor Unit Dimensions



Outdoor Unit Minimum Clearances



*Specifications are subject to change without notice.*




**Submittal:DHH36ESK3IL**

**Standard Efficiency Heat Pump**

**Features:**

- Inverter-driven Variable Speed Blower
- Flared Piping Connections
- Wireless Remote Controller Included
- Anti-corrosion coils
- iFeel Operation
- Air Filters Included
- Turbo Cooling
- Intelligent Preheating
- Child Lock Function



**Indoor Unit Data**

**Blower Data**

CFM (Max/Min):	794/441
Output (W):	60
RLA:	0.7
Capacitor Rating (µF):	N/A

**Sound Pressure**

Cooling dB (A) (Min/Max):	36/52
---------------------------	-------

**Physical Characteristics**

Net Weight (lbs): 34.2

**Dimensions (in.)**

W: 42.4

H: 13.1


D: 9.6

**Piping Connection Size**


"Liquid": 1/4"

Gas: 5/8"

**Dimensions**



**Clearances**



Specifications & illustrations are subject to change without notice or incurring obligations.  
O'Fallon, MO ©Nordyne, LLC 2024. All Rights Reserved. 043G (11/24)

**ODU SKU: 1049127**  
**IDU SKU: 1049126**