

TECHNICAL SPECIFICATIONS

JT4BD Series

R-410A High Efficiency Heat Pump 13 SEER Residential System 1.5 – 5 Ton Capacity

The JT4BD Series now offers the choice of a heat pump that uses a more efficient and environmentally friendly refrigerant designated R-410A. The JT4BD Series of heat pumps offers exceptional performance. The unit, when combined with our engineered coils or air handlers, offers a full line of quality, split system cooling and heating equipment. The JT4BD is rated at 13 SEER and 8.0 HSPF when matched with our air handlers. When matched with our variable speed air handler, or our variable speed blower kits, the JT4BD is rated up to 14 SEER and 8.5 HSPF. Units are ideally sized for slab or rooftop mounting in single, multifamily, and light commercial applications.




WARRANTY

- This product offers a 10-year all-parts warranty.
- This product offers a 1 Year Quality Pledge to replace the unit if the compressor fails in the first year of operation, to the original owner. All split system products must be installed with a matched indoor air handler or indoor coil.
- Consumer product registration required for 10 year All Parts Warranty and Quality Pledge within a limited period of time after the installation. See current warranty document or visit our consumer web site for warranty details.

FEATURES and BENEFITS


- **R-410A Refrigerant:** Earth friendly non-ozone depleting refrigerant.
- **Designed using galvanized steel:** With a polyester urethane coat finish. The 950 hour salt spray finish resists corrosion 50% better than comparable units.
- **Copper Tube / Aluminum Fin Coils:** Both indoor and outdoor coils are designed to optimize heat transfer, minimize size and cost, and increase durability and reliability.
- **Permanently Lubricated Motor:** A heavy duty PSC motor for long lasting reliability and quiet operation. Requires no maintenance and is completely protected from rain and snow.
- **Complete Metal Wrapper:** Durable metal guard protects the coil from yard hazards and extreme weather.
- **Removable Top Grille Assembly:** Allows ease of service from the top without disconnecting fan motor leads.
- **High Pressure Switch:** Protects against abnormally high system pressures. Auto-reset feature prevents nuisance service visits.
- **Liquid Line Filter Drier:** Included with unit, field installed.
- **One Piece Top/Orifice:** Designed for maximum airflow and quiet operation.
- **Five Minute Restart Time Delay:** When the unit shuts down, a five minute delay keeps the unit from restarting, eliminating the highest cause for compressor failure.
- **Suction Accumulator:** Protection from liquid flood back and future compressor failures.
- **Hot Gas Muffler:** Reduces compressor noise and vibration.
- **Easy Compressor and Control Access:** Designed to make servicing easier for the contractor, access panels are provided to all controls and the compressor from the side of the unit.
- **Composite Base Pan:** Absorbs sound and is corrosion resistant. Composite is also stronger and lighter than steel.

MODEL IDENTIFICATION CODES



DIMENSIONS OUTDOOR SECTION

JT4BD	018K	024K	030K	036K	042K	048K	060K
H	31 1/2	35 1/2	39 1/2	43 1/2	39 1/2	43 1/2	43 1/2
W	30 3/4	30 3/4	30 3/4	30 3/4	30 3/4	30 3/4	30 3/4
D	30 3/4	30 3/4	30 3/4	30 3/4	30 3/4	30 3/4	30 3/4



PHYSICAL AND ELECTRICAL SPECIFICATIONS / OUTDOOR UNITS

13 SEER — High Efficiency — Single Phase

Model Number JT4BD-		018K	024K	030K	036K	042K	048K	060K	
Electrical Data	Volts-Cycles-Phase (1)	208/230-60-1	208/230-60-1	208/230-60-1	208/230-60-1	208/230-60-1	208/230-60-1	208/230-60-1	
	Total Amps	10.2	14.6	15.3	17.8	19.4	23.2	27.7	
	Delay Fuse Max. (2)	20	30	30	35	40	50	60	
	Min. Circuit Ampacity	12.4	18.0	18.8	22.0	23.9	28.7	34.3	
Condenser Data	Coil	Area	17.7	20.3	22.8	25.3	22.8	25.3	25.3
		Rows-FPI	1-18	1-18	1-20	1-20	2-16	2-16	2-16
		Tube Dia	3/8" O.D.	3/8" O.D.	3/8" O.D.	3/8" O.D.	3/8" O.D.	3/8" O.D.	3/8" O.D.
	Fan Motor	Type	PSC	PSC	PSC	PSC	PSC	PSC	PSC
		Amps	1.2	1.2	1.2	1.2	1.46	1.46	1.46
		HP	0.2	0.2	0.2	0.2	0.25	0.25	0.25
	Fan Blade	Dia - # Blades	24" - 2						
		SCFM	3000	3200	3300	3400	3700	3800	3800
	Compressor Data	RLA	9.0	13.4	14.1	16.6	17.9	21.8	26.2
		LRA	48.0	58.3	73.0	79.0	112.0	117.0	134.0
Refrigerant suction line O.D. Note: Liquid line is 3/8" O.D. for entire length		0-24 ft.	3/4"	3/4"	3/4"	7/8"	7/8"	7/8"	7/8"
		25-39 ft.	3/4"	3/4"	3/4"	7/8"	7/8"	7/8"	1-1/8" (3)
		40-75 ft.	3/4"	3/4"	3/4"	7/8"	7/8"	7/8"	1-1/8" (3)
Approximate Weight (lbs.)		Net	166	171	176	181	247	280	290
		Ship	175	180	185	190	260	295	305
Sound Rating db (5)		73.0	73.0	73.0	73.0	79.0	79.0	79.0	

(1) Operating Voltage Range: 187v min. - 253v max.

(2) HACR Type Circuit Breakers may be used.

(3) Requires 7/8" to 1-1/8" reducer from line to unit.

(4) Additional charge for line sets above 15 feet.

Values based on suction line as follows with 3/8" liquid line.

a) 3/4" = 0.6 oz. per additional foot.

b) 7/8" = 0.7 oz. per additional foot.

c) 1 1/8" = 0.8 oz. per additional foot.

5) Tested in compliance with AHRI 270-2008 but not listed with AHRI.

ACCESSORIES - Condensing Unit

Start Assist Kit - 912933

Provides additional starting torque for the compressor motor when operating with low line voltage or high operating temperatures.

Snow Stand Kit - 920636

Outdoor Thermostat - 913852

Two-stage logic provides ability to lock out electric strips down to balance point and bring on in stages.

Extreme Wind Condition Mounting Kit - 920900

Time Delay Relay Kit (TDR) - 918476

SYSTEM COOLING CAPACITIES

13 SEER — High Efficiency — Single Phase

Outdoor Unit Model Number JT4BD-	Indoor Unit Model Number C6B(A,H)-	Cooling Capacity Btuh	SEER	EER	Heating Capacity BTUH @ 47°F	HSPF	Nominal SCFM
024K	X24(C,U)-A + MB6BM	23,800	13	12.5	23,800	8.0	750
024K	X24(C,U)-B + MB6BM	23,800	13	12.5	23,800	8.0	750
030K	X30(C,U)-A + MB6BM	28,400	13	12.0	29,400	7.8	800
030K	X30(C,U)-B + MB6BM	28,400	13	12.0	29,400	7.8	800
036K	X35(C,U)-A + MB6BM	35,600	13	12.0	36,000	8.0	1100
036K	X36(C,U)-B + MB6BM	35,600	13	12.0	36,000	8.0	1100
036K	X36(C,U)-C + MB6BM	35,600	13	12.0	36,000	8.0	1100
042K	X42(C,U)-B + MB6BM	42,000	13	13.0	42,000	8.0	1325
042K	X42(C,U)-C + MB6BM	42,000	13	13.0	42,000	8.0	1325
048K	X48(C,U)-C + MB6BM	48,000	13	11.7	47,000	8.0	1675
060K	X60(C,U)-C + MB6EM	57,000	13	12.0	55,000	8.0	1850

SYSTEM COOLING CAPACITIES

13 SEER — High Efficiency — Single Phase

Outdoor Unit Model Number JT4BD-	Indoor Unit Model Number GB5BM-0, B5BM-X	Cooling Capacity Btuh	SEER	EER	Heating Capacity BTUH @ 47°F	HSPF	Nominal SCFM
018K	24K-(A,B)	18,000	13.0	11.0	18,000	8.0	650
024K	24K-(A,B)	23,600	13.0	12.6	23,600	8.0	750
030K	30K-(A,B)	29,400	13.0	12.0	30,000	8.0	850
036K	36K-B	35,400	13.0	11.8	36,000	8.0	1200
042K	42K-B	39,600	13.0	11.7	41,000	8.0	1400
048K	48K-C	48,000	13.0	12.0	48,000	8.0	1600
060K	60K-C	59,500	13.5	11.7	58,000	8.0	1750

Outdoor Unit Model Number JT4BD-	Indoor Unit + TDR	BTUH	SEER	EER	Heat Capacity BTUH @ 47 F	Heating Capacity BTUH @ 17 F	HSPF	SCFM
018K	GB5BMM024K-A	17,400	13.00	11.00	20,000	10,800	8.00	650
018K	GB5BMM024K-B	17,500	13.00	11.00	17,700	10,500	7.70	650
024K	GB5BMM024K-A	23,400	13.00	11.00	25,200	15,200	8.00	855
024K	GB5BMM024K-B	23,000	13.00	11.00	26,000	15,000	8.00	820
030K	GB5BMM030K-A	28,400	13.00	11.00	32,800	20,200	8.00	1125
030K	GB5BMM030K-B	28,400	13.00	11.00	32,200	19,200	8.00	1080
036K	GB5BMM036K-B	35,000	13.00	11.00	36,800	22,000	8.00	1170
042K	GB5BMM042K-B	40,000	13.00	11.00	41,600	25,600	7.90	1530
048K	GB5BMM048K-B	46,500	13.00	11.00	49,800	30,200	8.00	1360
048K	GB5BMM048K-C	47,500	13.00	11.00	47,500	30,000	8.00	1620
060K	GB5BMM060K-C	57,000	13.00	11.00	60,500	36,000	8.00	1665

Outdoor Unit Model Number JT4BD	Indoor TXV Coil + TDR	Cooling Capacity BTUH	SEER	EER	Heating Capacity BTUH @ 47F	HSPF	Nominal SCFM
018K	C6B(A,H)-X24(C,U)-(A,B)	18,000	13	11.05	18,200	7.7	625
024K	C6B(A,H)-X24(C,U)-(A,B)	24,000	13	11.6	23,600	8.0	750
030K	C6B(A,H)-X30(C,U)-(A,B,C)	28,000	13	11.6	29,000	8.0	1000
036K	C6B(A,H)-X35(C,U)-B	35,600	13	12	36,000	8.0	1100
036K	C6B(A,H)-X36(C,U)-(B,C)	35,600	13	12	36,000	8.0	1100
042K	C6B(A,H)-X42(C,U)-(B,C)	42,000	13	12.95	42,000	8.0	1325
048K	C6B(A,H)-X47(C,U)-(B,C)	47,500	13	11.75	46,500	8.0	1675
048K	C6B(A,H)-X48(C,U)-(C,D)	47,500	13	11.75	46,500	8.0	1675

14 SEER — High Efficiency — Single Phase

Outdoor Unit Model Number JT4BD-	Indoor Unit Model Number B4VM-	Cooling Capacity Btuh	SEER	EER	Heating Capacity BTUH @ 47°F	HSPF	Nominal SCFM
018K	X24K-B	18,400	14	12.9	18,000	8.0	600
024K	X24K-B	24,000	14	13.4	23,200	8.5	750
030K	X30K-B	29,600	14	12.9	29,600	8.5	900
036K	X36K-B	35,800	14	12.6	37,800	8.5	1180
042K	X48K-C	41,500	14	13.5	41,500	8.5	1400
048K	X48K-C	48,500	14	13.0	47,500	8.5	1600
060K	X60K-C	59,500	13.5	12	57,500	8.5	1700

¹ Orifice supplied with outdoor unit.

All ratings are with time delay relay.

See current AHRI Directory for certified combinations and ratings.

www.ahridirectory.org

13 SEER + LOOSE COIL COOLING EXPANDED RATINGS

JT4BD-018K with C6B(A,H)-X24(C,U)-(A,B) - LOOSE COIL

O.D.T			75°F			85°F			95°F			105°F			115°F		
CFM	E.D.B.	E.W.B.	T.C.	S.C.	K.W.	T.C.	S.C.	K.W.	T.C.	S.C.	K.W.	T.C.	S.C.	K.W.	T.C.	S.C.	K.W.
525	80	62	18.8	16.6	1.33	17.9	16.3	1.47	17.0	16.0	1.62	15.9	15.5	1.78	14.9	14.9	1.96
	80	67	20.5	14.1	1.33	19.5	13.7	1.47	18.5	13.2	1.62	17.4	12.7	1.78	16.1	12.2	1.96
	80	72	22.6	11.3	1.33	21.5	10.9	1.47	20.4	10.5	1.62	19.1	10.0	1.79	17.7	9.6	1.97
	75	63	19.0	13.6	1.34	18.2	13.2	1.47	17.2	12.7	1.62	16.1	12.3	1.78	14.9	11.7	1.96
600	80	62	19.3	17.9	1.36	18.4	17.6	1.50	17.4	17.3	1.64	16.4	16.4	1.80	15.4	15.4	1.99
	80	67	20.9	15.0	1.36	19.9	14.6	1.50	18.9	14.1	1.65	17.7	13.6	1.81	16.3	13.1	1.99
	80	72	23.0	11.9	1.36	21.9	11.5	1.50	20.7	11.1	1.65	19.3	10.6	1.82	17.9	10.1	2.00
	75	63	19.5	14.5	1.36	18.5	14.0	1.50	17.5	13.6	1.64	16.4	13.1	1.81	15.2	12.5	1.99
675	80	62	19.6	19.1	1.39	18.8	18.7	1.52	17.9	17.9	1.67	17.0	17.0	1.84	15.9	15.9	2.01
	80	67	21.3	15.9	1.39	20.2	15.4	1.52	19.1	15.0	1.67	17.9	14.5	1.84	16.5	13.9	2.02
	80	72	23.3	12.5	1.38	22.1	12.1	1.53	20.9	11.7	1.68	19.4	11.2	1.85	18.0	10.7	2.03
	75	63	19.8	15.3	1.39	18.8	14.9	1.53	17.8	14.4	1.68	16.6	13.9	1.84	15.4	13.3	2.02

JT4BD-024K with C6B(A,H)-X24(C,U)-(A,B) (LOOSE COIL)

O.D.T			75°F			85°F			95°F			105°F			115°F		
CFM	E.D.B.	E.W.B.	T.C.	S.C.	K.W.	T.C.	S.C.	K.W.	T.C.	S.C.	K.W.	T.C.	S.C.	K.W.	T.C.	S.C.	K.W.
700	80	62	23.9	21.4	1.60	22.8	21.0	1.77	21.6	20.5	1.96	20.4	19.8	2.17	19.0	19.0	2.41
	80	67	25.9	18.0	1.60	24.7	17.5	1.78	23.4	16.9	1.97	22.0	16.3	2.18	20.4	15.6	2.41
	80	72	28.3	14.4	1.60	27.0	14.0	1.78	25.5	13.5	1.97	23.9	12.9	2.19	22.0	12.2	2.42
	75	63	24.1	17.4	1.60	23.0	16.9	1.78	21.8	16.3	1.97	20.5	15.7	2.18	19.0	15.0	2.41
800	80	62	24.4	22.9	1.63	23.3	22.4	1.81	22.2	22.0	2.00	21.0	21.0	2.21	19.6	19.6	2.44
	80	67	26.3	19.1	1.63	25.1	18.6	1.81	23.8	18.0	2.00	22.3	17.4	2.22	20.6	16.7	2.45
	80	72	28.7	15.2	1.64	27.2	14.7	1.82	25.7	14.2	2.01	24.0	13.5	2.23	22.3	12.9	2.46
	75	63	24.6	18.5	1.64	23.4	17.9	1.81	22.2	17.4	2.00	20.8	16.7	2.21	19.3	16.0	2.45
900	80	62	25.0	24.4	1.67	23.9	23.7	1.85	22.8	22.7	2.04	21.5	21.5	2.25	20.1	20.1	2.48
	80	67	26.8	20.2	1.67	25.5	19.7	1.85	24.1	19.1	2.04	22.5	18.4	2.25	20.8	17.7	2.49
	80	72	28.9	15.9	1.67	27.5	15.4	1.86	26.0	14.8	2.05	24.3	14.2	2.26	22.5	13.5	2.50
	75	63	24.9	19.5	1.67	23.8	19.0	1.85	22.5	18.4	2.04	21.0	17.7	2.25	19.4	17.0	2.48

JT4BD-030K with C6B(A,H)-X30(C,U)-(A,B,C) (LOOSE COIL)

O.D.T			75°F			85°F			95°F			105°F			115°F		
CFM	E.D.B.	E.W.B.	T.C.	S.C.	K.W.	T.C.	S.C.	K.W.	T.C.	S.C.	K.W.	T.C.	S.C.	K.W.	T.C.	S.C.	K.W.
800	80	62	28.7	24.9	1.95	27.5	24.5	2.15	26.2	24.0	2.36	24.7	23.2	2.61	23.0	22.4	2.89
	80	67	31.1	21.1	1.96	29.8	20.5	2.16	28.3	19.8	2.37	26.6	19.1	2.62	24.7	18.3	2.89
	80	72	33.9	17.1	1.97	32.4	16.5	2.17	30.7	15.9	2.38	28.8	15.3	2.63	26.8	14.5	2.90
	75	63	29.0	20.4	1.96	27.8	19.9	2.15	26.4	19.2	2.37	24.8	18.5	2.61	23.1	17.7	2.89
1000	80	62	29.9	27.9	2.03	28.6	27.3	2.22	27.2	26.8	2.44	25.7	25.6	2.68	24.1	24.0	2.96
	80	67	32.1	23.3	2.04	30.7	22.7	2.23	29.1	22.0	2.45	27.3	21.2	2.69	25.3	20.4	2.97
	80	72	34.6	18.5	2.04	33.1	17.9	2.24	31.4	17.3	2.46	29.5	16.6	2.70	27.2	15.8	2.98
	75	63	29.9	22.5	2.03	28.6	21.9	2.23	27.2	21.2	2.44	25.5	20.4	2.69	23.6	19.6	2.97
1200	80	62	30.8	30.3	2.11	29.6	29.4	2.30	28.2	28.2	2.52	26.7	26.7	2.76	24.9	24.9	3.04
	80	67	32.7	25.4	2.11	31.3	24.8	2.31	29.6	24.0	2.53	27.7	23.2	2.77	25.7	22.3	3.04
	80	72	35.1	19.8	2.12	33.6	19.2	2.32	31.8	18.6	2.54	29.8	17.8	2.78	27.6	17.0	3.06
	75	63	30.5	24.4	2.11	29.2	23.8	2.31	27.6	23.1	2.52	25.9	22.2	2.76	24.0	21.3	3.04

JT4BD-036K with C6B(A,H)-X36(C,U)-(B,C) (LOOSE COIL)

O.D.T			75°F			85°F			95°F			105°F			115°F		
CFM	E.D.B.	E.W.B.	T.C.	S.C.	K.W.	T.C.	S.C.	K.W.	T.C.	S.C.	K.W.	T.C.	S.C.	K.W.	T.C.	S.C.	K.W.
1050	80	62	36.0	31.9	2.42	34.5	31.3	2.66	32.7	30.6	2.93	30.8	29.5	3.23	28.6	28.4	3.58
	80	67	39.1	26.9	2.44	37.3	26.1	2.68	35.3	25.3	2.95	33.1	24.3	3.25	30.6	23.3	3.60
	80	72	42.5	21.7	2.46	40.5	21.0	2.70	38.2	20.2	2.97	35.8	19.3	3.27	33.1	18.3	3.61
	75	63	36.4	26.0	2.43	34.8	25.3	2.67	32.9	24.4	2.94	30.9	23.5	3.24	28.6	22.4	3.59
1200	80	62	36.9	34.1	2.48	35.3	33.4	2.72	33.5	32.8	2.99	31.5	31.4	3.29	29.5	29.4	3.64
	80	67	39.7	28.5	2.50	37.9	27.8	2.74	35.9	26.9	3.01	33.6	25.9	3.31	31.0	24.8	3.65
	80	72	43.0	22.8	2.52	41.0	22.1	2.76	38.8	21.2	3.03	36.2	20.3	3.33	33.5	19.3	3.67
	75	63	37.1	27.6	2.49	35.4	26.8	2.73	33.5	25.9	3.00	31.4	25.0	3.30	29.0	23.9	3.64
1350	80	62	37.7	36.2	2.54	36.1	35.3	2.78	34.2	34.2	3.05	32.3	32.3	3.35	30.2	30.2	3.71
	80	67	40.3	30.2	2.56	38.4	29.4	2.80	36.3	28.5	3.07	34.0	27.5	3.37	31.4	26.3	3.71
	80	72	43.5	23.8	2.58	41.5	23.1	2.82	39.1	22.2	3.09	36.6	21.3	3.39	33.7	20.2	3.73
	75	63	37.6	29.1	2.55	35.9	28.3	2.79	33.9	27.4	3.05	31.7	26.4	3.36	29.2	25.2	3.70

13 SEER + LOOSE COIL COOLING EXPANDED RATINGS (CONTINUED)

JT4BD-042K with C6B(A,H)-X42(C,U)-(B,C) (LOOSE COIL)

O.D.T			75°F			85°F			95°F			105°F			115°F		
CFM	E.D.B.	E.W.B.	T.C.	S.C.	K.W.	T.C.	S.C.	K.W.	T.C.	S.C.	K.W.	T.C.	S.C.	K.W.	T.C.	S.C.	K.W.
1225	80	62	43.4	38.0	2.71	41.5	37.2	2.97	39.2	36.4	3.26	36.7	35.1	3.59	34.1	33.8	3.97
	80	67	46.9	32.0	2.71	44.8	31.1	2.98	42.3	30.0	3.27	39.5	28.8	3.59	36.5	27.6	3.97
	80	72	51.1	25.9	2.72	48.7	25.0	2.98	45.9	24.0	3.27	42.7	22.9	3.60	39.3	21.6	3.97
	75	63	43.8	31.1	2.71	41.8	30.2	2.98	39.5	29.1	3.27	36.9	27.9	3.60	34.2	26.6	3.97
1400	80	62	44.5	40.7	2.77	42.3	39.8	3.04	40.1	39.1	3.33	37.6	37.5	3.66	35.0	35.0	4.03
	80	67	47.8	34.0	2.78	45.5	33.0	3.04	43.0	32.0	3.33	40.2	30.8	3.66	37.0	29.4	4.03
	80	72	51.7	27.2	2.79	49.1	26.3	3.05	46.3	25.2	3.34	43.2	24.0	3.66	39.8	22.8	4.04
	75	63	44.7	32.9	2.78	42.5	32.0	3.04	40.2	30.9	3.33	37.5	29.7	3.66	34.6	28.3	4.03
1575	80	62	45.3	43.2	2.84	43.3	42.3	3.10	40.9	40.9	3.39	38.5	38.5	3.72	35.9	35.9	4.09
	80	67	48.5	35.9	2.85	46.2	34.9	3.11	43.6	33.8	3.40	40.5	32.5	3.72	37.3	31.1	4.09
	80	72	52.2	28.4	2.85	49.7	27.4	3.11	46.8	26.4	3.41	43.6	25.2	3.73	40.1	23.9	4.10
	75	63	45.3	34.7	2.85	43.2	33.7	3.11	40.7	32.6	3.40	38.0	31.3	3.73	34.9	29.9	4.10

JT4BD-048K with C6B(AH)-X48(C,U)-(C,D) (LOOSE COIL)

O.D.T			75°F			85°F			95°F			105°F			115°F		
CFM	E.D.B.	E.W.B.	T.C.	S.C.	K.W.	T.C.	S.C.	K.W.	T.C.	S.C.	K.W.	T.C.	S.C.	K.W.	T.C.	S.C.	K.W.
1400	80	62	43.1	32.6	3.11	41.5	31.9	3.44	39.8	31.3	3.83	37.8	30.3	4.27	35.6	29.4	4.80
	80	67	47.4	28.5	3.13	45.6	27.7	3.46	43.7	26.8	3.84	41.5	25.8	4.28	39.0	24.7	4.80
	80	72	52.1	24.2	3.15	50.2	23.4	3.48	48.0	22.5	3.86	45.7	21.6	4.30	43.0	20.5	4.82
	75	63	44.1	27.9	3.12	42.4	27.1	3.45	40.6	26.2	3.83	38.5	25.2	4.28	36.2	24.1	4.80
1600	80	62	45.7	36.3	3.20	44.0	35.6	3.53	42.0	35.2	3.91	39.8	34.1	4.35	37.4	32.9	4.87
	80	67	49.7	31.4	3.22	47.7	30.5	3.54	45.6	29.5	3.92	43.2	28.5	4.37	40.6	27.3	4.88
	80	72	54.8	26.1	3.24	52.7	25.2	3.57	50.3	24.3	3.95	47.7	23.3	4.39	44.7	22.2	4.90
	75	63	46.3	30.6	3.20	44.6	29.7	3.53	42.6	28.8	3.91	40.3	27.7	4.36	37.9	26.5	4.88
1800	80	62	47.6	40.0	3.28	45.7	39.4	3.61	43.6	38.6	3.99	41.3	37.4	4.43	38.7	36.1	4.95
	80	67	51.5	34.0	3.30	49.4	33.0	3.63	47.1	32.0	4.01	44.6	30.8	4.45	41.8	29.6	4.96
	80	72	56.6	27.8	3.32	54.3	26.9	3.65	51.7	25.9	4.03	48.8	24.9	4.47	45.5	23.8	4.97
	75	63	48.1	33.0	3.29	46.2	32.1	3.62	44.0	31.1	4.00	41.6	29.8	4.44	39.0	28.6	4.95

13 SEER + AHU COOLING EXPANDED RATINGS

JT4BD-018K with C6B(A,H)-X24(C,U)-(A,B) + MB6B(*)-(A,B)

JT4BD-018K with B5BM-X24K-(A,B), or GB5BM-024K-(A,B)

O.D.T			75°F			85°F			95°F			105°F			115°F		
CFM	E.D.B.	E.W.B.	T.C.	S.C.	K.W.	T.C.	S.C.	K.W.	T.C.	S.C.	K.W.	T.C.	S.C.	K.W.	T.C.	S.C.	K.W.
525	80	62	19.1	16.9	1.21	18.2	16.6	1.34	17.2	16.2	1.49	16.2	15.7	1.65	15.2	15.2	1.82
	80	67	20.8	14.3	1.20	19.8	13.9	1.34	18.8	13.4	1.49	17.7	12.9	1.66	16.4	12.4	1.84
	80	72	22.9	11.4	1.21	21.8	11.1	1.35	20.6	10.6	1.50	19.4	10.2	1.66	18.0	9.7	1.84
	75	63	19.3	13.8	1.21	18.4	13.4	1.34	17.5	13.0	1.49	16.4	12.5	1.65	15.2	12.0	1.84
600	80	62	19.5	18.1	1.26	18.6	17.8	1.39	17.6	17.5	1.54	16.7	16.7	1.68	15.7	15.7	1.86
	80	67	21.2	15.1	1.25	20.2	14.7	1.39	19.1	14.3	1.54	17.9	13.8	1.71	16.6	13.2	1.89
	80	72	23.2	12.0	1.25	22.1	11.6	1.39	20.9	11.2	1.55	19.5	10.7	1.71	18.1	10.3	1.90
	75	63	19.7	14.6	1.26	18.7	14.2	1.39	17.7	13.8	1.54	16.6	13.3	1.70	15.4	12.7	1.89
675	80	62	19.7	19.2	1.32	19.0	18.9	1.42	18.1	18.1	1.57	17.2	17.2	1.73	16.1	16.1	1.91
	80	67	21.4	16.0	1.32	20.3	15.5	1.45	19.2	15.1	1.61	18.0	14.5	1.77	16.6	14.0	1.95
	80	72	23.4	12.6	1.31	22.3	12.1	1.45	21.0	11.7	1.61	19.5	11.2	1.78	18.1	10.7	1.96
	75	63	19.9	15.4	1.32	18.9	15.0	1.46	17.9	14.5	1.61	16.7	14.0	1.77	15.5	13.4	1.95

JT4BD-024K with C6B(A,H)-X24(C,U)-(A,B) + MB6B(*)-(A,B)

JT4BD-024K with B5BM-X24K-(A,B), or GB5BM-024K-(A,B)

O.D.T			75°F			85°F			95°F			105°F			115°F		
CFM	E.D.B.	E.W.B.	T.C.	S.C.	K.W.	T.C.	S.C.	K.W.	T.C.	S.C.	K.W.	T.C.	S.C.	K.W.	T.C.	S.C.	K.W.
700	80	62	24.2	21.6	1.52	23.1	21.2	1.70	21.9	20.8	1.89	20.6	20.1	2.10	19.4	19.4	2.30
	80	67	26.1	18.2	1.52	25.0	17.6	1.70	23.7	17.1	1.89	22.2	16.5	2.10	20.6	15.8	2.33
	80	72	28.6	14.6	1.52	27.3	14.1	1.70	25.8	13.6	1.90	24.1	13.0	2.11	22.3	12.4	2.34
	75	63	24.4	17.6	1.52	23.3	17.1	1.70	22.1	16.5	1.89	20.8	15.9	2.10	19.3	15.3	2.33
800	80	62	24.5	23.0	1.61	23.4	22.5	1.78	22.3	22.1	1.97	21.2	21.2	2.14	19.9	19.9	2.37
	80	67	26.4	19.2	1.60	25.2	18.7	1.78	23.9	18.1	1.97	22.4	17.5	2.19	20.7	16.8	2.42
	80	72	28.8	15.3	1.61	27.3	14.8	1.79	25.8	14.2	1.98	24.2	13.6	2.19	22.4	12.9	2.43
	75	63	24.7	18.5	1.61	23.5	18.0	1.78	22.3	17.4	1.97	20.9	16.8	2.18	19.4	16.1	2.42
900	80	62	24.8	24.2	1.71	23.9	23.7	1.83	22.8	22.8	2.02	21.6	21.6	2.23	20.2	20.2	2.46
	80	67	26.6	20.1	1.71	25.3	19.6	1.89	23.9	19.0	2.08	22.4	18.3	2.29	20.7	17.6	2.52
	80	72	28.7	15.8	1.71	27.4	15.3	1.89	25.9	14.7	2.09	24.2	14.1	2.30	22.3	13.4	2.53
	75	63	24.8	19.4	1.71	23.6	18.9	1.89	22.3	18.3	2.08	20.9	17.6	2.29	19.3	16.8	2.52

13 SEER + AHU COOLING EXPANDED RATINGS (CONTINUED)

JT4BD-030K with C6B(A,H)-X30(C,U)-(A,B,C) + MB6B(*)-(A,B,C)

JT4BD-030K with B5BM-X30K-(A,B), or GB5BM-030K-(A,B)

O.D.T			75°F			85°F			95°F			105°F			115°F		
CFM	E.D.B.	E.W.B.	T.C.	S.C.	K.W.	T.C.	S.C.	K.W.	T.C.	S.C.	K.W.	T.C.	S.C.	K.W.	T.C.	S.C.	K.W.
875	80	62	29.0	25.9	2.03	27.8	25.4	2.23	26.4	24.9	2.44	24.9	24.0	2.69	23.2	23.1	2.96
	80	67	31.4	21.8	2.04	30.0	21.2	2.24	28.5	20.6	2.45	26.8	19.8	2.69	24.8	19.0	2.97
	80	72	34.0	17.6	2.04	32.5	17.0	2.25	30.8	16.4	2.46	28.9	15.7	2.70	26.8	14.9	2.98
	75	63	29.2	21.1	2.04	28.0	20.5	2.23	26.6	19.9	2.45	25.0	19.1	2.69	23.1	18.3	2.97
1000	80	62	29.3	27.3	2.21	28.0	26.7	2.40	26.6	26.3	2.62	25.3	25.3	2.78	23.7	23.7	3.05
	80	67	31.5	22.8	2.21	30.1	22.2	2.41	28.5	21.6	2.62	26.7	20.8	2.87	24.7	19.9	3.14
	80	72	34.0	18.2	2.22	32.5	17.6	2.42	30.8	17.0	2.63	28.8	16.2	2.88	26.6	15.4	3.15
	75	63	29.3	22.0	2.21	28.0	21.4	2.41	26.6	20.7	2.62	24.9	20.0	2.86	23.0	19.1	3.14
1125	80	62	29.3	28.4	2.43	28.0	27.8	2.62	27.0	27.0	2.72	25.6	25.5	2.97	23.8	23.8	3.24
	80	67	31.4	23.7	2.43	29.9	23.1	2.63	28.3	22.4	2.84	26.5	21.6	3.08	24.4	20.6	3.36
	80	72	33.8	18.7	2.44	32.3	18.1	2.64	30.5	17.4	2.85	28.5	16.7	3.09	26.3	15.8	3.37
	75	63	29.1	22.8	2.43	27.9	22.2	2.63	26.3	21.4	2.84	24.6	20.6	3.08	22.7	19.7	3.36

JT4BD-036K with C6B(A,H)-X36(C,U)-(B,C) + MB6B(*)-(B,C)

JT4BD-036K with B5BM-X36K-B, or GB5BM-036K-B

O.D.T			75°F			85°F			95°F			105°F			115°F		
CFM	E.D.B.	E.W.B.	T.C.	S.C.	K.W.	T.C.	S.C.	K.W.	T.C.	S.C.	K.W.	T.C.	S.C.	K.W.	T.C.	S.C.	K.W.
1050	80	62	36.2	32.0	2.38	34.6	31.4	2.62	32.9	30.7	2.89	30.9	29.7	3.19	28.8	28.5	3.54
	80	67	39.2	27.0	2.40	37.4	26.2	2.64	35.5	25.4	2.90	33.3	24.4	3.21	30.8	23.4	3.55
	80	72	42.6	21.8	2.42	40.7	21.1	2.66	38.3	20.3	2.92	36.0	19.4	3.23	33.3	18.4	3.57
	75	63	36.5	26.1	2.38	34.9	25.4	2.63	33.1	24.5	2.89	31.0	23.6	3.20	28.7	22.6	3.54
1200	80	62	36.7	33.9	2.54	35.1	33.2	2.78	33.3	32.6	3.05	31.5	31.5	3.28	29.5	29.5	3.63
	80	67	39.5	28.4	2.56	37.7	27.6	2.80	35.7	26.8	3.07	33.4	25.8	3.36	30.8	24.7	3.71
	80	72	42.8	22.7	2.58	40.8	22.0	2.82	38.6	21.1	3.09	36.0	20.2	3.38	33.3	19.2	3.73
	75	63	36.9	27.5	2.55	35.2	26.7	2.79	33.3	25.8	3.05	31.2	24.8	3.36	28.8	23.7	3.70
1350	80	62	37.0	35.5	2.75	35.4	34.6	2.99	33.8	33.8	3.15	31.9	31.9	3.46	29.8	29.8	3.81
	80	67	39.6	29.6	2.76	37.8	28.8	3.00	35.6	27.9	3.27	33.3	26.9	3.57	30.7	25.8	3.91
	80	72	42.8	23.5	2.78	40.8	22.7	3.02	38.5	21.8	3.29	35.9	20.9	3.59	33.0	19.8	3.93
	75	63	36.9	28.6	2.75	35.2	27.7	2.99	33.2	26.8	3.26	31.0	25.8	3.56	28.6	24.6	3.90

JT4BD-042K with C6B(A,H)-X42(C,U)-(B,C) + MB6B(*)-(B,C)

JT4BD-042K with B5BM-X42K-B, or GB5BM-042K-B

O.D.T			75°F			85°F			95°F			105°F			115°F		
CFM	E.D.B.	E.W.B.	T.C.	S.C.	K.W.	T.C.	S.C.	K.W.	T.C.	S.C.	K.W.	T.C.	S.C.	K.W.	T.C.	S.C.	K.W.
1225	80	62	43.6	38.2	2.63	41.7	37.5	2.89	39.5	36.7	3.18	37.0	35.3	3.51	34.4	34.0	3.89
	80	67	47.2	32.2	2.63	45.0	31.3	2.90	42.6	30.2	3.19	39.8	29.0	3.51	36.8	27.8	3.89
	80	72	51.4	26.0	2.64	49.0	25.1	2.90	46.2	24.2	3.19	43.0	23.1	3.52	39.6	21.8	3.89
	75	63	44.1	31.3	2.63	42.1	30.4	2.90	39.8	29.3	3.19	37.2	28.1	3.52	34.4	26.8	3.89
1400	80	62	44.4	40.6	2.81	42.2	39.7	3.06	40.0	39.0	3.36	37.5	37.4	3.69	35.1	35.1	4.00
	80	67	47.7	34.0	2.81	45.4	33.0	3.07	42.9	31.9	3.36	40.1	30.7	3.69	36.9	29.3	4.06
	80	72	51.6	27.2	2.81	49.0	26.2	3.07	46.3	25.2	3.36	43.1	24.0	3.69	39.7	22.7	4.06
	75	63	44.6	32.9	2.81	42.4	31.9	3.07	40.1	30.8	3.36	37.5	29.6	3.69	34.5	28.2	4.06
1575	80	62	44.7	42.7	3.02	42.7	41.7	3.28	40.5	40.5	3.50	38.2	38.2	3.83	35.5	35.5	4.20
	80	67	47.9	35.5	3.03	45.6	34.5	3.29	42.9	33.3	3.58	39.9	32.0	3.90	36.7	30.6	4.27
	80	72	51.6	28.1	3.03	49.1	27.1	3.29	46.2	26.0	3.58	43.0	24.8	3.91	39.5	23.5	4.27
	75	63	44.7	34.2	3.03	42.6	33.2	3.29	40.1	32.1	3.58	37.3	30.8	3.91	34.3	29.4	4.28

JT4BD-048K with C6B(A,H)-X48(C,U)-C + MB6B(*)-C

JT4BD-048K with B5BM-X48K-C, or GB5BM-048K-C

O.D.T			75°F			85°F			95°F			105°F			115°F		
CFM	E.D.B.	E.W.B.	T.C.	S.C.	K.W.	T.C.	S.C.	K.W.	T.C.	S.C.	K.W.	T.C.	S.C.	K.W.	T.C.	S.C.	K.W.
1400	80	62	49.7	43.5	3.23	47.6	42.7	3.55	45.3	41.9	3.92	42.7	40.5	4.35	39.8	39.1	4.83
	80	67	53.7	36.7	3.25	51.4	35.7	3.57	48.8	34.5	3.94	45.9	33.3	4.36	42.6	31.9	4.84
	80	72	58.5	29.7	3.27	55.9	28.8	3.59	52.7	27.7	3.95	49.4	26.5	4.38	45.9	25.1	4.85
	75	63	50.1	35.6	3.24	48.0	34.6	3.56	45.6	33.5	3.93	42.9	32.2	4.35	39.9	30.8	4.84
1600	80	62	50.6	46.3	3.41	48.4	45.4	3.73	46.0	44.7	4.10	43.3	42.9	4.52	40.6	40.5	4.96
	80	67	54.3	38.7	3.43	52.0	37.6	3.75	49.2	36.5	4.11	46.2	35.1	4.53	42.8	33.7	5.01
	80	72	58.6	31.0	3.45	56.0	30.0	3.77	53.0	28.8	4.13	49.7	27.6	4.55	46.0	26.2	5.02
	75	63	50.8	37.4	3.41	48.5	36.4	3.73	46.0	35.2	4.10	43.2	33.9	4.53	40.0	32.4	5.01
1800	80	62	51.0	48.7	3.63	48.8	47.7	3.95	46.5	46.5	4.26	44.0	44.0	4.68	41.3	41.2	5.17
	80	67	54.7	40.5	3.65	52.2	39.4	3.97	49.4	38.1	4.33	46.2	36.8	4.75	42.7	35.2	5.23
	80	72	58.8	32.0	3.67	56.2	31.0	3.98	53.1	29.8	4.35	49.7	28.5	4.76	46.0	27.1	5.24
	75	63	51.0	39.1	3.64	48.7	38.0	3.96	46.1	36.7	4.33	43.2	35.3	4.75	39.9	33.8	5.23

13 SEER + AHU COOLING EXPANDED RATINGS (CONTINUED)

JT4BD-060K with B5BM-X60K-C, or GB5BM-060K-C

O.D.T			75°F			85°F			95°F			105°F			115°F		
CFM	E.D.B.	E.W.B.	T.C.	S.C.	K.W.	T.C.	S.C.	K.W.	T.C.	S.C.	K.W.	T.C.	S.C.	K.W.	T.C.	S.C.	K.W.
1750	80	62	54.5	41.2	3.63	52.3	40.4	4.06	49.9	39.5	4.54	47.2	38.1	5.08	43.9	36.5	5.73
	80	67	59.9	36.1	3.66	57.3	34.9	4.09	54.6	33.8	4.57	51.6	32.5	5.11	47.7	30.9	5.77
	80	72	65.6	30.5	3.70	62.9	29.3	4.13	60.2	28.2	4.61	56.8	26.9	5.15	52.4	25.4	5.81
	75	63	55.8	35.3	3.64	53.6	34.2	4.06	51.0	33.0	4.54	48.1	31.7	5.09	44.5	30.2	5.73
2000	80	62	57.7	45.9	3.73	55.2	44.9	4.16	52.5	44.2	4.64	49.6	42.8	5.18	46.1	40.6	5.83
	80	67	62.7	39.7	3.76	59.9	38.5	4.19	57.0	37.2	4.67	53.6	35.8	5.21	49.4	34.1	5.87
	80	72	69.4	32.8	3.81	66.2	31.7	4.24	62.7	30.5	4.71	59.0	29.2	5.25	54.2	27.5	5.91
	75	63	58.6	38.8	3.74	56.0	37.6	4.17	53.3	36.3	4.64	50.2	34.8	5.18	46.3	33.1	5.83
2250	80	62	59.9	50.3	3.87	57.3	49.4	4.30	54.4	48.3	4.77	51.3	46.6	5.31	47.2	44.1	5.97
	80	67	64.7	42.8	3.90	61.8	41.5	4.32	58.7	40.1	4.80	55.2	38.7	5.35	50.8	36.8	6.01
	80	72	71.1	35.0	3.94	67.8	33.8	4.37	64.2	32.5	4.85	60.2	31.2	5.39	55.0	29.5	6.04
	75	63	60.6	41.7	3.87	57.9	40.4	4.30	54.9	39.0	4.77	51.7	37.5	5.32	47.6	35.7	5.97

JT4BD-018K with GB5BMM024K-(A,B)

O.D.T			65°F			75°F			85°F			95°F			105°F			115°F		
CFM	E.D.B.	E.W.B.	T.C.	S.C.	K.W.	T.C.	S.C.	K.W.	T.C.	S.C.	K.W.	T.C.	S.C.	K.W.	T.C.	S.C.	K.W.	T.C.	S.C.	K.W.
500	80	62	17.7	14.0	1.06	16.9	13.9	1.19	16.0	13.9	1.32	15.1	13.6	1.47	14.19	13.95	1.64	13.42	13.19	1.82
	80	67	19.5	11.3	1.08	18.7	11.2	1.20	17.7	11.3	1.34	16.6	11.0	1.48	15.39	10.72	1.64	14.34	10.11	1.83
	80	72	21.6	8.8	1.10	20.7	8.8	1.23	19.7	8.9	1.36	18.7	8.7	1.51	17.45	8.50	1.67	16.05	8.60	1.85
	75	63	17.9	10.9	1.07	17.1	10.8	1.19	16.2	10.8	1.33	15.2	10.5	1.47	14.23	9.58	1.64	13.24	10.33	1.82
650	80	62	18.8	16.4	1.11	18.0	16.6	1.24	17.2	16.1	1.38	16.3	15.4	1.52	15.31	14.79	1.69	14.39	14.27	1.87
	80	67	20.5	12.9	1.13	19.6	13.2	1.26	18.5	12.9	1.39	17.4	12.7	1.53	16.17	12.57	1.69	14.86	12.74	1.88
	80	72	22.6	9.8	1.16	21.6	10.2	1.28	20.6	9.9	1.42	19.4	9.8	1.56	18.13	9.84	1.72	16.61	9.79	1.90
	75	63	18.9	12.4	1.11	18.0	12.7	1.24	17.0	12.3	1.37	15.8	12.0	1.52	14.76	11.92	1.68	13.75	12.14	1.87
800	80	62	20.0	18.2	1.17	19.2	17.9	1.29	18.3	17.1	1.43	17.4	16.5	1.58	16.33	15.77	1.74	15.07	15.01	1.92
	80	67	21.1	14.5	1.18	20.1	14.7	1.30	19.1	14.3	1.44	18.0	14.6	1.58	16.70	14.47	1.74	15.14	14.32	1.92
	80	72	23.2	11.0	1.22	22.1	11.2	1.34	21.0	10.9	1.47	19.8	10.8	1.61	18.47	10.72	1.77	17.02	10.74	1.95
	75	63	19.5	13.9	1.16	18.5	14.0	1.29	17.6	14.0	1.42	16.4	13.9	1.57	15.11	13.62	1.73	14.03	13.59	1.91

JT4BD-024K with GB5BMM024K-(A,B)

O.D.T			65°F			75°F			85°F			95°F			105°F			115°F		
CFM	E.D.B.	E.W.B.	T.C.	S.C.	K.W.	T.C.	S.C.	K.W.	T.C.	S.C.	K.W.	T.C.	S.C.	K.W.	T.C.	S.C.	K.W.	T.C.	S.C.	K.W.
650	80	62	23.6	18.0	1.36	22.8	18.2	1.52	21.7	18.3	1.68	20.4	17.9	1.86	18.96	18.58	2.06	17.80	17.44	2.29
	80	67	26.0	15.0	1.38	24.9	14.9	1.53	23.7	15.0	1.70	22.4	14.6	1.88	21.00	14.26	2.08	19.37	13.10	2.30
	80	72	28.8	11.7	1.42	27.7	11.6	1.57	26.5	11.9	1.74	25.1	11.6	1.91	23.59	11.37	2.11	21.93	11.59	2.33
	75	63	23.9	14.5	1.37	23.0	14.3	1.52	21.8	14.4	1.68	20.5	14.0	1.86	19.00	12.63	2.06	17.76	13.57	2.29
800	80	62	24.8	20.7	1.42	23.8	21.1	1.57	22.6	20.6	1.74	21.5	20.2	1.92	20.36	19.67	2.12	18.95	18.79	2.34
	80	67	27.0	16.5	1.45	25.9	16.9	1.60	24.6	16.5	1.76	23.3	16.2	1.94	21.80	16.12	2.14	20.16	15.96	2.36
	80	72	29.8	12.7	1.49	28.6	13.3	1.64	27.2	12.9	1.80	25.7	12.8	1.98	23.93	12.77	2.17	22.26	12.71	2.38
	75	63	24.9	15.9	1.42	23.9	16.3	1.57	22.7	15.8	1.74	21.4	15.5	1.92	19.84	15.29	2.11	18.18	15.01	2.34
950	80	62	25.7	23.2	1.48	24.8	23.1	1.63	23.8	22.2	1.80	22.7	21.5	1.98	21.39	20.67	2.18	20.00	19.91	2.41
	80	67	27.7	18.2	1.51	26.5	18.4	1.66	25.3	17.9	1.82	23.8	17.7	2.00	22.30	17.51	2.19	20.70	17.90	2.41
	80	72	30.3	14.0	1.55	28.9	14.2	1.70	27.5	13.8	1.86	26.1	13.7	2.03	24.46	13.57	2.23	22.74	13.61	2.44
	75	63	25.6	17.5	1.48	24.5	17.6	1.63	23.3	17.1	1.79	21.9	16.9	1.97	20.43	17.03	2.17	18.53	16.73	2.39

JT4BD-030K with GB5BMM030K-(A,B)

O.D.T			65°F			75°F			85°F			95°F			105°F			115°F		
CFM	E.D.B.	E.W.B.	T.C.	S.C.	K.W.	T.C.	S.C.	K.W.	T.C.	S.C.	K.W.	T.C.	S.C.	K.W.	T.C.	S.C.	K.W.	T.C.	S.C.	K.W.
950	80	62	29.4	24.3	1.81	28.3	24.2	1.98	27.0	24.3	2.17	25.7	23.9	2.38	24.53	24.11	2.64	23.11	22.72	2.92
	80	67	32.2	19.2	1.86	30.9	19.1	2.04	29.5	19.3	2.22	28.0	18.9	2.43	26.42	18.63	2.67	24.64	17.63	2.95
	80	72	35.4	14.8	1.93	34.0	14.7	2.10	32.6	15.0	2.29	31.0	14.7	2.50	29.31	14.52	2.74	27.45	14.86	3.02
	75	63	29.7	18.6	1.82	28.5	18.4	1.98	27.2	18.6	2.17	25.8	18.1	2.39	24.15	16.47	2.63	22.39	17.81	2.91
1100	80	62	30.3	26.5	1.88	29.1	27.0	2.05	28.2	26.2	2.24	27.0	25.5	2.46	25.64	24.77	2.71	24.15	23.94	2.99
	80	67	32.9	20.6	1.94	31.5	21.2	2.10	30.1	20.7	2.29	28.6	20.5	2.49	26.95	20.48	2.73	25.11	20.41	3.01
	80	72	36.1	15.6	2.01	34.7	16.4	2.18	33.2	15.9	2.36	31.6	15.8	2.57	29.80	15.91	2.81	27.90	16.00	3.09
	75	63	30.4	19.9	1.88	29.2	20.4	2.05	27.8	19.9	2.24	26.3	19.6	2.45	24.67	19.48	2.69	22.95	19.95	2.97
1250	80	62	31.4	28.5	1.96	30.4	28.3	2.13	29.2	27.2	2.32	27.9	26.5	2.53	26.51	25.62	2.78	24.97	24.87	3.06
	80	67	33.4	22.3	2.00	32.1	22.5	2.17	30.6	22.0	2.35	29.0	22.0	2.56	27.32	21.81	2.80	25.52	22.67	3.08
	80	72	36.7	16.8	2.08	35.2	17.2	2.25	33.6	16.7	2.43	31.9	16.8	2.64	30.11	16.76	2.88	28.13	16.95	3.15
	75	63	30.9	21.4	1.95	29.6	21.6	2.11	28.3	21.1	2.30	26.7	20.9	2.51	25.11	21.48	2.75	23.29	21.44	3.03

13 SEER + AHU COOLING EXPANDED RATINGS (CONTINUED)

JT4BD-036K with GB5BMM036K-B

O.D.T			65°F			75°F			85°F			95°F			105°F			115°F		
CFM	E.D.B.	E.W.B.	T.C.	S.C.	K.W.	T.C.	S.C.	K.W.	T.C.	S.C.	K.W.	T.C.	S.C.	K.W.	T.C.	S.C.	K.W.	T.C.	S.C.	K.W.
1000	80	62	35.4	27.2	2.23	34.0	26.9	2.46	32.4	27.0	2.71	30.6	26.4	2.99	28.71	27.66	3.30	26.68	25.71	3.66
	80	67	38.9	22.6	2.30	37.4	22.4	2.52	35.7	22.6	2.77	33.9	22.2	3.05	31.87	21.76	3.37	29.74	19.70	3.73
	80	72	42.8	17.6	2.38	41.2	17.5	2.61	39.4	17.8	2.86	37.5	17.5	3.15	35.39	17.17	3.47	33.13	17.56	3.84
	75	63	36.0	21.9	2.24	34.5	21.7	2.47	32.9	21.8	2.72	31.1	21.3	2.99	29.20	19.30	3.31	27.08	20.85	3.67
1150	80	62	36.4	29.2	2.30	34.8	29.7	2.52	33.2	29.0	2.77	31.4	28.5	3.05	29.54	28.10	3.37	27.60	27.37	3.73
	80	67	39.8	24.1	2.37	38.2	24.8	2.59	36.5	24.2	2.84	34.6	23.9	3.12	32.55	23.82	3.45	30.30	23.72	3.80
	80	72	43.8	18.5	2.46	42.1	19.4	2.69	40.2	18.8	2.94	38.2	18.6	3.22	36.02	18.74	3.55	33.65	18.82	3.91
	75	63	36.9	23.3	2.32	35.4	23.9	2.53	33.7	23.2	2.78	31.8	22.9	3.06	29.80	22.70	3.38	27.66	22.49	3.73
1300	80	62	37.1	31.4	2.37	35.6	31.5	2.59	33.9	30.7	2.84	32.2	30.2	3.12	30.35	29.32	3.44	28.59	28.47	3.81
	80	67	40.6	25.9	2.44	38.9	26.2	2.66	37.1	25.6	2.91	35.2	25.5	3.19	33.04	25.25	3.51	30.77	25.28	3.87
	80	72	44.5	19.8	2.53	42.7	20.3	2.76	40.8	19.7	3.01	38.7	19.7	3.29	36.35	19.65	3.61	33.99	19.85	3.98
	75	63	37.6	25.0	2.38	36.0	25.2	2.60	34.2	24.5	2.85	32.4	24.3	3.13	30.29	24.03	3.44	28.09	23.78	3.79

JT4BD-042K with GB5BMM042K-B

O.D.T			65°F			75°F			85°F			95°F			105°F			115°F		
CFM	E.D.B.	E.W.B.	T.C.	S.C.	K.W.	T.C.	S.C.	K.W.	T.C.	S.C.	K.W.	T.C.	S.C.	K.W.	T.C.	S.C.	K.W.	T.C.	S.C.	K.W.
1400	80	62	41.6	34.3	2.63	39.9	34.0	2.84	37.9	34.0	3.10	35.8	33.0	3.39	33.51	32.94	3.73	31.23	30.70	4.11
	80	67	45.7	28.3	2.67	43.9	28.1	2.89	41.8	28.3	3.15	39.5	27.7	3.44	36.99	27.23	3.77	34.20	24.97	4.14
	80	72	50.2	21.6	2.75	48.2	21.5	2.97	46.0	21.9	3.22	43.6	21.5	3.51	40.90	21.12	3.84	38.10	21.50	4.21
	75	63	42.2	27.3	2.63	40.5	27.0	2.85	38.4	27.2	3.10	36.2	26.5	3.40	33.59	23.63	3.73	30.76	25.58	4.10
1550	80	62	42.3	36.1	2.69	40.6	36.6	2.91	38.7	35.5	3.16	36.6	34.5	3.46	34.54	33.37	3.80	32.26	31.99	4.18
	80	67	46.4	29.7	2.75	44.5	30.5	2.97	42.3	29.7	3.21	40.0	29.4	3.50	37.42	29.25	3.84	34.61	28.86	4.21
	80	72	50.7	22.5	2.82	48.7	23.5	3.04	46.4	22.8	3.29	44.0	22.6	3.58	41.32	22.67	3.91	38.49	22.68	4.28
	75	63	42.9	28.6	2.70	41.0	29.3	2.91	39.0	28.5	3.17	36.7	28.0	3.46	34.03	27.53	3.79	31.02	27.01	4.16
1700	80	62	43.0	38.0	2.76	41.3	38.0	2.98	39.3	36.7	3.23	37.5	35.6	3.53	35.38	34.19	3.87	33.10	32.96	4.25
	80	67	46.9	31.5	2.82	44.9	31.9	3.03	42.7	31.1	3.28	40.3	30.9	3.57	37.76	30.38	3.90	34.88	30.27	4.28
	80	72	51.1	23.8	2.89	49.1	24.3	3.11	46.8	23.6	3.36	44.3	23.6	3.65	41.67	23.48	3.98	38.80	23.66	4.35
	75	63	43.4	30.3	2.77	41.5	30.5	2.99	39.4	29.7	3.23	37.0	29.2	3.52	34.43	28.73	3.86	31.40	28.32	4.23

JT4BD-048K with GB5BMM048K-(B,C)

O.D.T			65°F			75°F			85°F			95°F			105°F			115°F		
CFM	E.D.B.	E.W.B.	T.C.	S.C.	K.W.	T.C.	S.C.	K.W.	T.C.	S.C.	K.W.	T.C.	S.C.	K.W.	T.C.	S.C.	K.W.	T.C.	S.C.	K.W.
1200	80	62	47.7	34.8	2.95	45.8	34.4	3.23	43.7	34.5	3.54	41.2	33.5	3.89	38.32	34.94	4.29	35.92	32.75	4.76
	80	67	52.4	29.2	3.02	50.4	28.9	3.30	48.2	29.2	3.61	45.7	28.5	3.97	43.03	27.88	4.37	39.90	25.20	4.82
	80	72	58.0	23.1	3.14	55.8	23.0	3.42	53.5	23.4	3.73	50.9	22.9	4.08	48.04	22.46	4.48	44.92	22.95	4.93
	75	63	48.4	28.3	2.96	46.5	28.0	3.24	44.3	28.1	3.55	41.9	27.3	3.90	38.85	24.77	4.29	36.36	26.63	4.76
1350	80	62	48.9	36.9	3.02	47.0	37.6	3.30	44.7	36.4	3.62	42.2	35.8	3.97	39.30	35.33	4.36	36.57	34.88	4.82
	80	67	53.6	30.7	3.10	51.6	31.6	3.38	49.3	30.7	3.70	46.8	30.3	4.05	43.94	30.14	4.44	40.89	29.91	4.90
	80	72	59.2	24.0	3.22	57.0	25.2	3.50	54.5	24.4	3.82	51.8	24.2	4.17	48.84	24.29	4.57	45.59	24.36	5.02
	75	63	49.6	29.7	3.03	47.7	30.5	3.32	45.4	29.6	3.63	42.9	29.0	3.98	40.04	28.69	4.37	36.95	28.26	4.83
1500	80	62	49.9	39.2	3.10	47.9	39.4	3.38	45.6	38.4	3.69	43.1	37.9	4.04	40.26	37.24	4.44	37.17	36.56	4.89
	80	67	54.7	32.6	3.18	52.6	33.1	3.46	50.2	32.2	3.77	47.6	32.0	4.12	44.72	31.59	4.52	41.59	31.54	4.97
	80	72	60.2	25.6	3.30	57.8	26.2	3.58	55.3	25.4	3.90	52.5	25.4	4.25	49.34	25.24	4.64	45.91	25.47	5.09
	75	63	50.6	31.6	3.11	48.6	31.9	3.39	46.3	30.9	3.70	43.7	30.6	4.05	40.89	30.10	4.45	37.45	29.69	4.89

JT4BD-060K with GB5BMM060K-C

O.D.T			65°F			75°F			85°F			95°F			105°F			115°F		
CFM	E.D.B.	E.W.B.	T.C.	S.C.	K.W.	T.C.	S.C.	K.W.	T.C.	S.C.	K.W.	T.C.	S.C.	K.W.	T.C.	S.C.	K.W.	T.C.	S.C.	K.W.
1450	80	62	58.3	40.8	3.54	55.9	40.3	3.90	53.2	40.3	4.29	50.0	39.2	4.74	47.19	41.30	5.28	44.22	38.70	5.88
	80	67	64.2	34.5	3.67	61.7	34.1	4.02	58.9	34.4	4.43	55.9	33.5	4.89	52.57	32.80	5.40	48.85	29.84	5.97
	80	72	70.9	27.6	3.84	68.4	27.5	4.20	65.5	28.0	4.61	61.9	27.1	5.06	58.36	26.56	5.58	54.54	27.13	6.15
	75	63	59.3	33.6	3.56	56.9	33.1	3.92	54.2	33.2	4.31	51.0	32.2	4.77	47.89	29.38	5.29	44.84	31.59	5.89
1600	80	62	59.8	42.7	3.61	57.3	43.6	3.96	54.5	42.3	4.36	51.3	41.6	4.81	48.09	41.21	5.33	45.00	40.65	5.93
	80	67	65.7	35.9	3.74	63.1	37.0	4.10	60.3	35.8	4.50	57.2	35.3	4.96	53.74	35.15	5.48	49.96	34.88	6.04
	80	72	72.5	28.5	3.92	69.8	29.9	4.28	66.4	28.8	4.68	62.9	28.4	5.13	59.39	28.52	5.66	55.50	28.57	6.23
	75	63	60.7	34.9	3.63	58.2	35.8	3.98	55.4	34.6	4.38	52.4	33.9	4.84	48.70	33.45	5.34	45.58	33.24	5.94
1750	80	62	61.0	45.2	3.67	58.4	45.4	4.02	55.6	44.2	4.42	52.4	43.7	4.88	48.78	42.63	5.38	45.61	42.50	5.98
	80	67	67.0	37.9	3.81	64.3	38.3	4.17	61.4	37.2	4.57	58.2	37.0	5.03	54.74	36.54	5.54	51.00	36.53	6.11
	80	72	73.8	30.1	4.00	70.5	30.7	4.35	67.3	29.6	4.75	63.9	29.6	5.20	60.24	29.43	5.73	56.29	29.75	6.30
	75	63	61.9	36.8	3.69	59.4	37.1	4.04	56.5	35.9	4.44	53.3	35.5	4.90	49.78	34.80	5.40	46.26	34.65	5.98

13 SEER + VSB COOLING EXPANDED RATINGS

JT4BD-018K with C6B(A,H)-X24(C,U)-(A,B) + VSB

JT4BD-018K with B4VM-X24K-(A,B)

O.D.T			75°F			85°F			95°F			105°F			115°F		
CFM	E.D.B.	E.W.B.	T.C.	S.C.	K.W.	T.C.	S.C.	K.W.	T.C.	S.C.	K.W.	T.C.	S.C.	K.W.	T.C.	S.C.	K.W.
525	80	62	18.3	16.5	1.08	17.5	16.2	1.22	16.6	15.9	1.36	15.6	15.4	1.53	14.7	14.7	1.71
	80	67	19.9	13.9	1.08	19.0	13.5	1.22	18.0	13.1	1.37	16.9	12.6	1.53	15.7	12.2	1.72
	80	72	21.8	11.1	1.07	20.8	10.7	1.22	19.7	10.3	1.37	18.5	9.9	1.54	17.2	9.5	1.73
	75	63	18.5	13.5	1.08	17.7	13.1	1.22	16.8	12.7	1.37	15.7	12.2	1.53	14.6	11.7	1.72
600	80	62	18.7	17.8	1.10	17.9	17.4	1.24	17.1	17.1	1.37	16.2	16.2	1.54	15.2	15.2	1.73
	80	67	20.3	14.8	1.09	19.4	14.4	1.24	18.3	14.0	1.39	17.2	13.5	1.55	15.9	13.0	1.74
	80	72	22.2	11.7	1.10	21.2	11.3	1.24	20.0	10.9	1.39	18.7	10.5	1.56	17.3	10.0	1.75
	75	63	18.9	14.3	1.10	18.0	13.9	1.24	17.1	13.5	1.39	16.0	13.0	1.55	14.8	12.5	1.74
675	80	62	19.2	19.0	1.11	18.5	18.4	1.25	17.6	17.6	1.40	16.7	16.7	1.56	15.7	15.7	1.75
	80	67	20.6	15.7	1.12	19.6	15.3	1.26	18.6	14.9	1.42	17.4	14.4	1.58	16.1	13.9	1.77
	80	72	22.5	12.3	1.12	21.3	11.9	1.27	20.1	11.5	1.42	18.8	11.0	1.59	17.5	10.5	1.78
	75	63	19.2	15.1	1.12	18.3	14.7	1.26	17.3	14.3	1.41	16.2	13.8	1.58	15.0	13.3	1.77

JT4BD-024K with C6B(A,H)-X24(C,U)-(A,B) + VSB

JT4BD-024K with B4VM-X24K-(A,B)

O.D.T			75°F			85°F			95°F			105°F			115°F		
CFM	E.D.B.	E.W.B.	T.C.	S.C.	K.W.	T.C.	S.C.	K.W.	T.C.	S.C.	K.W.	T.C.	S.C.	K.W.	T.C.	S.C.	K.W.
700	80	62	23.2	21.2	1.36	22.2	20.8	1.54	21.0	20.4	1.73	19.8	19.7	1.94	18.7	18.7	2.16
	80	67	25.0	17.7	1.36	23.9	17.2	1.54	22.7	16.7	1.73	21.3	16.1	1.94	19.8	15.5	2.18
	80	72	27.3	14.1	1.35	26.0	13.7	1.54	24.6	13.2	1.74	23.1	12.7	1.95	21.3	12.1	2.19
	75	63	23.4	17.1	1.36	22.3	16.7	1.54	21.2	16.1	1.73	19.9	15.6	1.94	18.5	14.9	2.18
800	80	62	23.6	22.6	1.40	22.6	22.1	1.58	21.7	21.6	1.76	20.5	20.5	1.97	19.2	19.2	2.20
	80	67	25.4	18.8	1.40	24.2	18.3	1.58	22.9	17.8	1.78	21.5	17.2	1.99	20.0	16.5	2.23
	80	72	27.5	14.9	1.41	26.2	14.4	1.59	24.7	13.9	1.79	23.1	13.3	2.00	21.4	12.7	2.24
	75	63	23.7	18.2	1.40	22.6	17.7	1.58	21.4	17.1	1.77	20.1	16.5	1.99	18.7	15.9	2.23
900	80	62	24.2	23.9	1.44	23.3	23.1	1.61	22.2	22.2	1.80	20.9	20.9	2.01	19.6	19.6	2.25
	80	67	25.7	19.8	1.45	24.5	19.3	1.64	23.1	18.7	1.83	21.7	18.1	2.05	20.0	17.4	2.28
	80	72	27.6	15.5	1.45	26.2	15.0	1.65	24.8	14.5	1.84	23.3	13.9	2.06	21.6	13.2	2.30
	75	63	23.9	19.1	1.46	22.8	18.6	1.64	21.6	18.0	1.83	20.2	17.4	2.05	18.7	16.7	2.28

JT4BD-030K with C6B(A,H)-X30(C,U)-(A,B,C) + VSB

JT4BD-030K with B4VM-X30K-(A,B)

O.D.T			75°F			85°F			95°F			105°F			115°F		
CFM	E.D.B.	E.W.B.	T.C.	S.C.	K.W.	T.C.	S.C.	K.W.	T.C.	S.C.	K.W.	T.C.	S.C.	K.W.	T.C.	S.C.	K.W.
800	80	62	29.4	25.8	1.73	28.0	25.3	1.93	26.6	24.8	2.15	25.0	24.0	2.39	23.3	23.2	2.67
	80	67	31.7	21.7	1.74	30.3	21.1	1.94	28.7	20.4	2.15	26.9	19.7	2.40	24.9	18.9	2.68
	80	72	34.4	17.4	1.74	32.8	16.8	1.94	31.1	16.2	2.16	29.1	15.5	2.41	26.9	14.7	2.69
	75	63	29.6	21.1	1.73	28.3	20.5	1.93	26.8	19.8	2.15	25.2	19.1	2.39	23.3	18.3	2.67
1000	80	62	30.4	28.9	1.82	29.1	28.3	2.02	27.8	27.7	2.21	26.2	26.2	2.45	24.5	24.5	2.73
	80	67	32.5	24.0	1.82	31.1	23.4	2.02	29.4	22.8	2.24	27.5	22.0	2.49	25.4	21.2	2.77
	80	72	35.2	18.9	1.84	33.5	18.3	2.04	31.7	17.7	2.26	29.6	16.9	2.50	27.2	16.1	2.78
	75	63	30.5	23.3	1.82	29.1	22.7	2.02	27.5	22.0	2.24	25.8	21.2	2.48	23.8	20.4	2.76
1200	80	62	31.5	31.0	1.90	30.2	30.0	2.10	28.8	28.7	2.32	27.1	27.1	2.57	25.2	25.2	2.84
	80	67	33.0	26.2	1.95	31.4	25.5	2.15	29.7	24.8	2.37	27.7	24.0	2.61	25.5	23.1	2.89
	80	72	35.5	20.2	1.96	33.8	19.6	2.16	31.9	18.9	2.38	29.7	18.1	2.62	27.3	17.3	2.90
	75	63	30.9	25.3	1.95	29.4	24.6	2.14	27.8	23.9	2.36	26.0	23.0	2.61	23.9	22.1	2.89

JT4BD-036K with C6B(A,H)-X36(C,U)-(B,C) + VSB

JT4BD-036K with B4VM-X36K-B

O.D.T			75°F			85°F			95°F			105°F			115°F		
CFM	E.D.B.	E.W.B.	T.C.	S.C.	K.W.	T.C.	S.C.	K.W.	T.C.	S.C.	K.W.	T.C.	S.C.	K.W.	T.C.	S.C.	K.W.
1050	80	62	34.9	31.5	2.28	33.5	31.0	2.51	31.9	30.4	2.78	30.0	29.3	3.07	28.1	28.1	3.39
	80	67	37.9	26.5	2.30	36.2	25.8	2.53	34.3	25.0	2.79	32.3	24.1	3.09	29.9	23.2	3.43
	80	72	41.0	21.2	2.32	39.2	20.6	2.55	37.0	19.8	2.81	34.9	19.0	3.11	32.3	18.1	3.45
	75	63	35.3	25.6	2.28	33.7	24.9	2.52	32.0	24.2	2.78	30.1	23.3	3.08	27.9	22.3	3.41
1200	80	62	35.5	33.5	2.39	34.1	32.8	2.63	32.4	32.2	2.89	30.9	30.9	3.08	28.9	28.9	3.47
	80	67	38.2	28.0	2.41	36.5	27.3	2.64	34.6	26.5	2.90	32.4	25.6	3.20	30.0	24.6	3.53
	80	72	41.2	22.2	2.44	39.5	21.5	2.66	37.4	20.8	2.93	35.0	19.9	3.22	32.4	18.9	3.55
	75	63	35.7	27.1	2.40	34.1	26.4	2.63	32.3	25.5	2.89	30.3	24.6	3.19	28.0	23.6	3.52
1350	80	62	36.1	35.1	2.53	34.5	34.3	2.77	33.2	33.2	2.95	31.4	31.3	3.25	29.3	29.3	3.59
	80	67	38.4	29.4	2.55	36.7	28.6	2.78	34.7	27.8	3.04	32.5	26.9	3.34	30.0	25.8	3.68
	80	72	41.5	23.1	2.57	39.6	22.4	2.81	37.4	21.6	3.06	35.0	20.7	3.36	32.3	19.7	3.69
	75	63	35.8	28.3	2.54	34.2	27.6	2.77	32.4	26.8	3.03	30.3	25.8	3.33	28.0	24.7	3.67

13 SEER + VSB COOLING EXPANDED RATINGS (CONTINUED)

JT4BD-042K with C6B(A,H)-X42(C,U)-(B,C) + VSB

JT4BD-042K with B4VM-X48K-(B,C)

O.D.T			75°F			85°F			95°F			105°F			115°F		
CFM	E.D.B.	E.W.B.	T.C.	S.C.	K.W.	T.C.	S.C.	K.W.	T.C.	S.C.	K.W.	T.C.	S.C.	K.W.	T.C.	S.C.	K.W.
1225	80	62	42.1	37.6	2.52	40.3	37.0	2.77	38.3	36.2	3.06	35.9	34.9	3.38	33.6	33.5	3.72
	80	67	45.5	31.6	2.53	43.5	30.7	2.78	41.2	29.8	3.07	38.6	28.7	3.39	35.7	27.5	3.75
	80	72	49.4	25.3	2.53	47.2	24.5	2.79	44.5	23.6	3.07	41.7	22.6	3.39	38.5	21.4	3.76
	75	63	42.6	30.7	2.52	40.7	29.8	2.78	38.5	28.8	3.06	36.1	27.8	3.39	33.4	26.6	3.75
1400	80	62	43.0	40.1	2.64	41.0	39.2	2.89	38.9	38.5	3.18	36.8	36.8	3.46	34.4	34.4	3.83
	80	67	46.1	33.5	2.65	44.0	32.6	2.90	41.6	31.6	3.18	38.9	30.5	3.50	35.9	29.2	3.87
	80	72	49.8	26.6	2.66	47.5	25.7	2.91	44.9	24.8	3.19	41.9	23.7	3.51	38.6	22.5	3.87
	75	63	43.1	32.4	2.64	41.2	31.5	2.90	38.9	30.5	3.18	36.4	29.4	3.50	33.6	28.1	3.87
1575	80	62	43.6	42.2	2.79	41.6	41.3	3.04	39.7	39.7	3.28	37.5	37.5	3.60	34.9	34.9	3.96
	80	67	46.4	35.2	2.79	44.3	34.2	3.05	41.8	33.2	3.33	39.0	32.0	3.65	35.9	30.7	4.02
	80	72	50.0	27.6	2.80	47.7	26.7	3.06	45.0	25.8	3.34	42.0	24.6	3.66	38.6	23.4	4.02
	75	63	43.4	33.9	2.79	41.4	33.0	3.05	39.1	32.0	3.33	36.5	30.8	3.65	33.6	29.5	4.02

JT4BD-048K with C6B(A,H)-X48(C,U)-(C,D) + VSB

JT4BD-048K with B4VM-X48K-C

O.D.T			75°F			85°F			95°F			105°F			115°F		
CFM	E.D.B.	E.W.B.	T.C.	S.C.	K.W.	T.C.	S.C.	K.W.	T.C.	S.C.	K.W.	T.C.	S.C.	K.W.	T.C.	S.C.	K.W.
1400	80	62	43.7	33.1	2.82	42.2	32.5	3.14	40.4	31.9	3.52	38.5	30.9	3.95	36.4	30.0	4.47
	80	67	48.0	28.9	2.83	46.3	28.1	3.15	44.4	27.3	3.53	42.2	26.3	3.96	39.8	25.2	4.47
	80	72	52.7	24.5	2.85	50.8	23.7	3.17	48.7	22.8	3.54	46.4	21.9	3.97	43.8	20.9	4.47
	75	63	44.7	28.3	2.82	43.1	27.5	3.14	41.3	26.6	3.52	39.3	25.7	3.96	36.9	24.6	4.47
1600	80	62	46.4	37.0	2.87	44.7	36.3	3.20	42.8	36.0	3.57	40.6	34.9	4.01	38.3	33.7	4.52
	80	67	50.4	31.9	2.89	48.5	31.1	3.21	46.4	30.1	3.58	44.1	29.1	4.01	41.5	27.9	4.52
	80	72	55.5	26.4	2.91	53.4	25.6	3.23	51.1	24.7	3.60	48.5	23.7	4.02	45.6	22.7	4.52
	75	63	47.0	31.1	2.88	45.2	30.3	3.20	43.3	29.3	3.57	41.1	28.3	4.01	38.7	27.1	4.52
1800	80	62	48.3	40.7	2.95	46.4	40.2	3.27	44.4	39.4	3.65	42.1	38.3	4.08	39.6	37.0	4.59
	80	67	52.2	34.5	2.97	50.2	33.6	3.29	47.9	32.5	3.66	45.5	31.4	4.09	42.7	30.2	4.59
	80	72	57.3	28.1	2.99	55.0	27.3	3.30	52.5	26.4	3.67	49.7	25.4	4.10	46.5	24.2	4.59
	75	63	48.8	33.6	2.96	46.9	32.7	3.28	44.8	31.6	3.65	42.4	30.5	4.08	39.9	29.3	4.59

JT4BD-060K with C6B(A,H)-X60(C,U)-(C,D) + VSB

JT4BD-060K with B4VM-X60K-C

O.D.T			75°F			85°F			95°F			105°F			115°F		
CFM	E.D.B.	E.W.B.	T.C.	S.C.	K.W.	T.C.	S.C.	K.W.	T.C.	S.C.	K.W.	T.C.	S.C.	K.W.	T.C.	S.C.	K.W.
1750	80	62	54.5	41.2	3.63	52.3	40.4	4.06	49.9	39.5	4.54	47.2	38.1	5.08	43.9	36.5	5.73
	80	67	59.9	36.1	3.66	57.3	34.9	4.09	54.6	33.8	4.57	51.6	32.5	5.11	47.7	30.9	5.77
	80	72	65.6	30.5	3.70	62.9	29.3	4.13	60.2	28.2	4.61	56.8	26.9	5.15	52.4	25.4	5.81
	75	63	55.8	35.3	3.64	53.6	34.2	4.06	51.0	33.0	4.54	48.1	31.7	5.09	44.5	30.2	5.73
2000	80	62	57.7	45.9	3.73	55.2	44.9	4.16	52.5	44.2	4.64	49.6	42.8	5.18	46.1	40.6	5.83
	80	67	62.7	39.7	3.76	59.9	38.5	4.19	57.0	37.2	4.67	53.6	35.8	5.21	49.4	34.1	5.87
	80	72	69.4	32.8	3.81	66.2	31.7	4.24	62.7	30.5	4.71	59.0	29.2	5.25	54.2	27.5	5.91
	75	63	58.6	38.8	3.74	56.0	37.6	4.17	53.3	36.3	4.64	50.2	34.8	5.18	46.3	33.1	5.83
2250	80	62	59.9	50.3	3.87	57.3	49.4	4.30	54.4	48.3	4.77	51.3	46.6	5.31	47.2	44.1	5.97
	80	67	64.7	42.8	3.90	61.8	41.5	4.32	58.7	40.1	4.80	55.2	38.7	5.35	50.8	36.8	6.01
	80	72	71.1	35.0	3.94	67.8	33.8	4.37	64.2	32.5	4.85	60.2	31.2	5.39	55.0	29.5	6.04
	75	63	60.6	41.7	3.87	57.9	40.4	4.30	54.9	39.0	4.77	51.7	37.5	5.32	47.6	35.7	5.97

13 SEER + LOOSE COIL HEATING EXPANDED RATINGS

JT4BD-018K with C6B(A,H)-X24(C,U)-(A,B) - LOOSE COIL

		OUTDOOR TEMPERATURE (Deg. F)																							
CFM	Indoor T. Deg.F	10			17			20			30			40			47			50			60		
		MBH	COP	kW	MBH	COP	kW	MBH	COP	kW	MBH	COP	kW	MBH	COP	kW	MBH	COP	kW	MBH	COP	kW	MBH	COP	kW
500	60	10.0	2.18	1.34	11.8	2.54	1.36	12.5	2.69	1.37	15.0	3.18	1.39	17.6	3.66	1.41	19.4	3.98	1.43	20.1	4.12	1.43	22.7	4.56	1.46
	70	9.5	2.20	1.26	11.1	2.50	1.30	11.7	2.63	1.31	14.0	3.03	1.36	16.3	3.40	1.41	17.9	3.65	1.44	18.6	3.75	1.45	20.9	4.07	1.50
	80	8.9	2.16	1.20	10.3	2.43	1.24	10.9	2.53	1.26	12.9	2.88	1.32	15.0	3.19	1.38	16.4	3.39	1.42	17.0	3.48	1.44	19.1	3.74	1.49
600	60	10.0	2.12	1.39	11.8	2.48	1.40	12.6	2.63	1.41	15.2	3.12	1.43	17.8	3.60	1.45	19.6	3.93	1.46	20.4	4.07	1.47	23.0	4.52	1.49
	70	9.6	2.13	1.31	11.2	2.44	1.35	11.9	2.57	1.36	14.2	2.97	1.41	16.6	3.35	1.45	18.2	3.60	1.48	18.9	3.70	1.50	21.2	4.04	1.54
	80	9.0	2.12	1.24	10.5	2.38	1.29	11.1	2.49	1.31	13.2	2.83	1.37	15.3	3.14	1.43	16.8	3.34	1.47	17.4	3.42	1.49	19.5	3.68	1.55
700	60	10.2	2.09	1.43	12.0	2.44	1.45	12.8	2.59	1.45	15.4	3.09	1.47	18.0	3.57	1.48	19.9	3.90	1.49	20.6	4.04	1.50	23.3	4.50	1.51
	70	9.7	2.10	1.35	11.3	2.40	1.38	12.1	2.53	1.40	14.4	2.94	1.44	16.8	3.32	1.49	18.5	3.57	1.52	19.2	3.68	1.53	21.6	4.02	1.58
	80	9.1	2.08	1.29	10.6	2.34	1.33	11.2	2.44	1.35	13.3	2.77	1.41	15.5	3.07	1.48	16.9	3.27	1.52	17.6	3.35	1.54	19.7	3.60	1.60

13 SEER + LOOSE COIL HEATING EXPANDED RATINGS (CONTINUED)

JT4BD-024K with C6B(A,H)-X24(C,U)-(A,B) (LOOSE COIL)

		OUTDOOR TEMPERATURE (Deg. F)																							
100 CFM	Indoor T. Deg.F	10			17			20			30			40			47			50			60		
		MBH	COP	kW	MBH	COP	kW	MBH	COP	kW	MBH	COP	kW	MBH	COP	kW	MBH	COP	kW	MBH	COP	kW	MBH	COP	kW
650	60	11.7	2.05	1.67	14.2	2.44	1.70	15.2	2.60	1.72	18.8	3.12	1.76	22.3	3.62	1.81	24.8	3.95	1.84	25.8	4.09	1.85	29.3	4.54	1.89
	70	11.2	1.99	1.64	13.5	2.33	1.69	14.4	2.48	1.71	17.7	2.93	1.78	21.0	3.35	1.84	23.3	3.62	1.89	24.3	3.73	1.91	27.6	4.10	1.97
	80	10.6	1.89	1.64	12.7	2.21	1.69	13.6	2.33	1.71	16.7	2.73	1.79	19.7	3.10	1.86	21.8	3.34	1.91	22.7	3.44	1.94	25.8	3.76	2.01
750	60	11.8	2.01	1.71	14.3	2.40	1.74	15.4	2.57	1.75	18.9	3.09	1.80	22.5	3.59	1.84	25.0	3.93	1.87	26.1	4.07	1.88	29.7	4.53	1.92
	70	11.3	1.95	1.69	13.6	2.30	1.73	14.6	2.44	1.75	17.9	2.90	1.82	21.3	3.32	1.88	23.6	3.60	1.92	24.6	3.72	1.94	27.9	4.09	2.00
	80	10.7	1.87	1.67	12.9	2.18	1.73	13.8	2.31	1.75	16.9	2.71	1.83	20.0	3.08	1.90	22.2	3.32	1.96	23.1	3.42	1.98	26.2	3.74	2.06
850	60	11.9	1.99	1.76	14.4	2.38	1.78	15.5	2.54	1.79	19.1	3.06	1.83	22.8	3.57	1.87	25.3	3.91	1.90	26.4	4.06	1.91	30.0	4.52	1.94
	70	11.4	1.93	1.73	13.7	2.28	1.77	14.8	2.42	1.79	18.1	2.88	1.85	21.5	3.31	1.91	23.9	3.59	1.95	24.9	3.71	1.97	28.3	4.08	2.03
	80	10.8	1.85	1.71	13.0	2.16	1.77	13.9	2.28	1.79	17.1	2.68	1.87	20.2	3.05	1.94	22.4	3.28	2.00	23.3	3.38	2.02	26.4	3.70	2.10

JT4BD-030K with C6B(A,H)-X30(C,U)-(A,B,C) (LOOSE COIL)

		OUTDOOR TEMPERATURE (Deg. F)																							
100 CFM	Indoor T.	10			17			20			30			40			47			50			60		
	Deg.F	MBH	COP	kW	MBH	COP	kW	MBH	COP	kW	MBH	COP	kW	MBH	COP	kW	MBH	COP	kW	MBH	COP	kW	MBH	COP	kW
900	60	15.0	2.23	1.98	17.9	2.57	2.04	19.2	2.72	2.07	23.3	3.16	2.16	27.5	3.56	2.26	30.3	3.83	2.32	31.6	3.94	2.35	35.7	4.28	2.45
	70	14.4	2.12	2.00	17.1	2.42	2.08	18.3	2.55	2.11	22.2	2.93	2.23	26.2	3.28	2.34	28.9	3.50	2.42	30.1	3.59	2.46	34.0	3.88	2.57
	80	13.8	1.99	2.03	16.4	2.27	2.12	17.5	2.38	2.16	21.2	2.71	2.29	24.9	3.02	2.42	27.5	3.21	2.51	28.6	3.29	2.54	32.2	3.54	2.67
1000	60	15.1	2.20	2.01	18.0	2.55	2.08	19.3	2.69	2.10	23.5	3.14	2.20	27.7	3.55	2.29	30.7	3.83	2.35	31.9	3.94	2.38	36.1	4.29	2.47
	70	14.5	2.09	2.04	17.3	2.40	2.11	18.5	2.53	2.15	22.5	2.92	2.26	26.4	3.27	2.37	29.2	3.50	2.45	30.4	3.59	2.48	34.4	3.89	2.59
	80	13.9	1.97	2.07	16.6	2.25	2.16	17.7	2.36	2.20	21.4	2.71	2.32	25.2	3.02	2.45	27.8	3.21	2.54	28.9	3.29	2.57	32.7	3.55	2.70
1100	60	15.2	2.17	2.05	18.2	2.52	2.11	19.4	2.66	2.14	23.7	3.12	2.23	27.9	3.54	2.31	30.9	3.82	2.37	32.2	3.93	2.40	36.4	4.29	2.49
	70	14.6	2.07	2.07	17.5	2.39	2.15	18.7	2.51	2.18	22.7	2.91	2.29	26.7	3.27	2.40	29.5	3.50	2.47	30.7	3.60	2.50	34.7	3.90	2.61
	80	14.1	1.96	2.10	16.7	2.23	2.19	17.8	2.35	2.23	21.6	2.69	2.35	25.4	3.00	2.48	28.0	3.20	2.57	29.1	3.28	2.60	32.9	3.54	2.73

JT4BD-036K with C6B(A,H)-X36(C,U)-(B,C) (LOOSE COIL)

		OUTDOOR TEMPERATURE (Deg. F)																							
150 CFM	Indoor T.	10			17			20			30			40			47			50			60		
	Deg.F	MBH	COP	kW	MBH	COP	kW	MBH	COP	kW	MBH	COP	kW	MBH	COP	kW	MBH	COP	kW	MBH	COP	kW	MBH	COP	kW
950	60	19.0	2.52	2.21	22.4	2.83	2.32	23.9	2.96	2.36	28.7	3.35	2.51	33.6	3.70	2.66	37.0	3.92	2.77	38.4	4.01	2.81	43.3	4.28	2.96
	70	18.3	2.36	2.27	21.5	2.64	2.39	22.9	2.76	2.44	27.6	3.10	2.61	32.3	3.40	2.79	35.5	3.59	2.91	36.9	3.66	2.96	41.6	3.90	3.13
	80	17.7	2.22	2.35	20.8	2.46	2.48	22.2	2.56	2.54	26.6	2.86	2.72	31.0	3.12	2.91	34.1	3.29	3.04	35.5	3.35	3.10	39.9	3.56	3.29
1100	60	19.1	2.48	2.26	22.6	2.80	2.36	24.1	2.93	2.41	29.0	3.34	2.55	34.0	3.70	2.70	37.5	3.93	2.80	39.0	4.02	2.84	43.9	4.32	2.98
	70	18.5	2.33	2.33	21.8	2.62	2.44	23.2	2.74	2.49	28.0	3.09	2.65	32.7	3.40	2.82	36.0	3.60	2.93	37.4	3.68	2.98	42.2	3.93	3.15
	80	17.9	2.18	2.40	21.1	2.44	2.53	22.4	2.54	2.58	26.9	2.86	2.76	31.5	3.13	2.95	34.6	3.30	3.07	36.0	3.37	3.13	40.5	3.59	3.31
1250	60	19.2	2.44	2.31	22.8	2.77	2.41	24.3	2.90	2.45	29.3	3.32	2.59	34.3	3.69	2.73	37.9	3.93	2.83	39.4	4.03	2.87	44.4	4.33	3.01
	70	18.7	2.31	2.37	22.1	2.60	2.48	23.5	2.72	2.53	28.3	3.08	2.69	33.1	3.40	2.85	36.5	3.61	2.96	37.9	3.69	3.01	42.7	3.95	3.17
	80	18.1	2.16	2.45	21.3	2.42	2.57	22.7	2.53	2.63	27.2	2.85	2.80	31.8	3.13	2.98	35.0	3.31	3.10	36.4	3.38	3.15	40.9	3.60	3.33

JT4BD-042K with C6B(A,H)-X42(C,U)-(B,C) (LOOSE COIL)

		OUTDOOR TEMPERATURE (Deg. F)																							
150 CFM	Indoor T.	10			17			20			30			40			47			50			60		
	Deg.F	MBH	COP	kW	MBH	COP	kW	MBH	COP	kW	MBH	COP	kW	MBH	COP	kW	MBH	COP	kW	MBH	COP	kW	MBH	COP	kW
1175	60	22.1	2.53	2.56	26.0	2.87	2.66	27.7	3.01	2.70	33.4	3.44	2.85	39.0	3.83	2.99	43.0	4.08	3.09	44.7	4.18	3.13	50.3	4.50	3.28
	70	21.3	2.34	2.67	25.1	2.65	2.78	26.8	2.78	2.83	32.2	3.16	2.99	37.7	3.51	3.15	41.5	3.74	3.26	43.2	3.83	3.31	48.6	4.12	3.46
	80	20.8	2.18	2.80	24.4	2.45	2.92	26.0	2.57	2.97	31.2	2.92	3.14	36.5	3.23	3.31	40.2	3.43	3.43	41.7	3.51	3.49	47.0	3.77	3.66
1325	60	22.2	2.50	2.60	26.2	2.85	2.70	28.0	2.99	2.74	33.7	3.44	2.88	39.5	3.84	3.02	43.5	4.10	3.11	45.2	4.20	3.15	50.9	4.54	3.29
	70	21.5	2.32	2.72	25.4	2.64	2.82	27.1	2.77	2.87	32.6	3.17	3.02	38.1	3.53	3.17	42.0	3.76	3.28	43.7	3.86	3.32	49.2	4.15	3.47
	80	20.9	2.15	2.85	24.7	2.44	2.96	26.2	2.56	3.01	31.6	2.92	3.17	36.9	3.24	3.34	40.6	3.45	3.45	42.2	3.54	3.50	47.6	3.81	3.66
1475	60	22.3	2.47	2.65	26.4	2.82	2.74	28.1	2.97	2.78	34.0	3.42	2.91	39.8	3.83	3.05	43.9	4.10	3.14	45.7	4.21	3.18	51.5	4.56	3.31
	70	21.8	2.31	2.76	25.7	2.63	2.86	27.3	2.76	2.91	32.9	3.17	3.05	38.5	3.53	3.20	42.5	3.77	3.30	44.1	3.87	3.34	49.7	4.18	3.49
	80	21.1	2.14	2.89	24.9	2.43	3.00	26.5	2.55	3.05	31.9	2.92	3.20	37.3	3.25	3.36	41.0	3.47	3.47	42.6	3.55	3.52	48.0	3.83	3.68

JT4BD-048K with C6B(A,H)-X48(C,U)-(C,D) (LOOSE COIL)

		OUTDOOR TEMPERATURE (Deg. F)																							
200 CFM	Indoor T.	10			17			20			30			40			47			50			60		
	Deg.F	MBH	COP	kW	MBH	COP	kW	MBH	COP	kW	MBH	COP	kW	MBH	COP	kW	MBH	COP	kW	MBH	COP	kW	MBH	COP	kW
1475	60	25.4	2.45	3.04	29.6	2.73	3.17	31.3	2.85	3.23	37.3	3.20	3.42	43.2	3.51	3.61	47.3	3.71	3.74	49.1	3.79	3.79	55.0	4.05	3.98
	70	24.6	2.24	3.23	28.6	2.49	3.37	30.3	2.60	3.42	36.1	2.92	3.62	41.8	3.21	3.82	45.9	3.39	3.96	47.6	3.47	4.02	53.3	3.70	4.22
	80	24.1	2.06	3.43	27.9	2.29	3.58	29.6	2.38	3.64	35.1	2.67	3.86	40.6	2.93	4.07	44.5	3.10	4.22	46.2	3.16	4.28	51.7	3.37	4.49
1675	60	25.7	2.44	3.09	29.9	2.73	3.21	31.7	2.85	3.26	37.7	3.22	3.44	43.8	3.55	3.62	48.0	3.76	3.74	49.8	3.85	3.80	55.8	4.12	3.97
	70	24.9	2.23	3.27	29.0	2.50	3.40	30.8	2.61	3.46	36.6	2.94	3.65	42.4	3.25	3.83	46.5	3.44	3.96	48.3	3.52	4.02	54.1	3.77	4.21
	80	24.3	2.05	3.48	28.3	2.29	3.62	29.9	2.39	3.68	35.6	2.69	3.88	41.2	2.97	4.07	45.2	3.15	4.21	46.9	3.22	4.27	52.5	3.45	4.47
1875	60	25.8	2.41	3.13	30.1	2.71	3.25	31.9	2.83	3.30	38.1	3.21	3.48	44.3	3.56	3.65	48.6	3.78	3.77	50.4	3.87	3.82	56.6	4.16	3.99
	70	25.2	2.23	3.32	29.4	2.50	3.45	31.2	2.61	3.50	37.1	2.96	3.68	43.0	3.27	3.85	47.1	3.47	3.98	48.9	3.55	4.03	54.8	3.82	4.21
	80	24.6	2.04	3.53	28.6	2.29	3.66	30.3	2.39	3.72	36.0	2.71	3.90	41.7	2.99	4.09	45.7	3.18	4.22	47.4	3.25	4.27	53.1	3.49	4.46

13 SEER + AHU HEATING EXPANDED RATINGS

JT4BD-018K with C6B(A,H)-X24(C,U)-(A,B) + MB6B(*)-(A,B)

JT4BD-018K with B5BM-X24K-(A,B), or GB5BM-024K-(A,B)

		OUTDOOR TEMPERATURE (Deg. F)																							
100 CFM	Indoor T. Deg.F	10			17			20			30			40			47			50			60		
		MBH	COP	kW	MBH	COP	kW	MBH	COP	kW	MBH	COP	kW	MBH	COP	kW	MBH	COP	kW	MBH	COP	kW	MBH	COP	kW
500	60	8.7	2.03	1.26	10.6	2.47	1.26	11.5	2.66	1.27	14.2	3.28	1.27	16.9	3.89	1.28	18.9	4.32	1.28	19.7	4.50	1.28	22.4	5.10	1.29
	70	8.2	2.07	1.17	10.0	2.46	1.19	10.7	2.62	1.20	13.2	3.15	1.23	15.7	3.65	1.26	17.4	3.99	1.28	18.2	4.13	1.29	20.6	4.58	1.32
	80	7.6	2.04	1.09	9.2	2.40	1.12	9.9	2.55	1.13	12.1	3.02	1.17	14.3	3.46	1.21	15.9	3.76	1.24	16.6	3.88	1.25	18.8	4.27	1.29
600	60	8.8	1.97	1.30	10.7	2.41	1.31	11.6	2.59	1.31	14.4	3.21	1.31	17.2	3.82	1.32	19.1	4.25	1.32	20.0	4.43	1.32	22.8	5.03	1.33
	70	8.3	2.00	1.22	10.1	2.39	1.24	10.9	2.55	1.25	13.4	3.08	1.28	15.9	3.58	1.31	17.7	3.91	1.33	18.5	4.06	1.33	21.0	4.52	1.36
	80	7.7	2.00	1.13	9.4	2.35	1.17	10.0	2.50	1.18	12.3	2.96	1.22	14.6	3.38	1.27	16.3	3.67	1.30	17.0	3.78	1.31	19.3	4.16	1.36
700	60	9.0	1.94	1.35	10.9	2.37	1.35	11.8	2.55	1.35	14.6	3.16	1.35	17.4	3.78	1.35	19.4	4.20	1.35	20.2	4.39	1.35	23.0	5.00	1.35
	70	8.4	1.96	1.26	10.2	2.35	1.28	11.0	2.51	1.29	13.6	3.03	1.32	16.2	3.53	1.34	18.0	3.87	1.36	18.8	4.01	1.37	21.4	4.47	1.40
	80	7.9	1.96	1.18	9.5	2.30	1.21	10.2	2.44	1.23	12.5	2.88	1.27	14.8	3.30	1.32	16.4	3.57	1.35	17.1	3.68	1.37	19.5	4.04	1.41

JT4BD-024K with C6B(A,H)-X24(C,U)-(A,B) + MB6B(*)-(A,B)

JT4BD-024K with B5BM-X24K-(A,B), or GB5BM-024K-(A,B)

		OUTDOOR TEMPERATURE (Deg. F)																							
100 CFM	Indoor T. Deg.F	10			17			20			30			40			47			50			60		
		MBH	COP	kW	MBH	COP	kW	MBH	COP	kW	MBH	COP	kW	MBH	COP	kW	MBH	COP	kW	MBH	COP	kW	MBH	COP	kW
650	60	11.9	2.13	1.64	14.4	2.52	1.67	15.4	2.68	1.69	19.0	3.20	1.74	22.5	3.69	1.79	25.0	4.02	1.82	26.0	4.15	1.84	29.5	4.59	1.89
	70	11.4	2.07	1.61	13.7	2.42	1.66	14.6	2.56	1.68	17.9	3.00	1.75	21.2	3.41	1.82	23.5	3.68	1.87	24.5	3.79	1.89	27.8	4.14	1.97
	80	10.8	1.98	1.59	12.9	2.29	1.65	13.8	2.42	1.67	16.9	2.81	1.76	19.9	3.17	1.84	22.0	3.41	1.90	22.9	3.50	1.92	26.0	3.80	2.00
750	60	12.0	2.09	1.68	14.5	2.48	1.71	15.6	2.64	1.73	19.1	3.16	1.77	22.7	3.66	1.82	25.2	3.99	1.85	26.3	4.13	1.87	29.9	4.58	1.92
	70	11.5	2.04	1.65	13.8	2.38	1.70	14.8	2.52	1.72	18.1	2.97	1.79	21.5	3.39	1.86	23.8	3.66	1.91	24.8	3.77	1.93	28.1	4.13	2.00
	80	10.9	1.96	1.63	13.1	2.27	1.69	14.0	2.39	1.71	17.1	2.79	1.80	20.2	3.15	1.88	22.4	3.38	1.94	23.3	3.48	1.97	26.4	3.78	2.05
850	60	12.1	2.06	1.72	14.6	2.45	1.75	15.7	2.61	1.77	19.3	3.14	1.81	23.0	3.64	1.85	25.5	3.97	1.88	26.6	4.11	1.89	30.2	4.57	1.94
	70	11.6	2.01	1.69	13.9	2.36	1.74	15.0	2.50	1.76	18.3	2.95	1.82	21.7	3.37	1.89	24.1	3.65	1.94	25.1	3.76	1.96	28.5	4.13	2.03
	80	11.0	1.93	1.67	13.2	2.24	1.73	14.1	2.36	1.75	17.3	2.75	1.84	20.4	3.11	1.92	22.6	3.34	1.98	23.5	3.44	2.01	26.6	3.74	2.09

JT4BD-030K with C6B(A,H)-X30(C,U)-(A,B,C) + MB6B(*)-(A,B,C)

JT4BD-030K with B5BM-X30K-(A,B), or GB5BM-030K-(A,B)

		OUTDOOR TEMPERATURE (Deg. F)																							
100 CFM	Indoor T. Deg.F	10			17			20			30			40			47			50			60		
		MBH	COP	kW	MBH	COP	kW	MBH	COP	kW	MBH	COP	kW	MBH	COP	kW	MBH	COP	kW	MBH	COP	kW	MBH	COP	kW
700	60	15.2	2.25	1.98	18.1	2.60	2.05	19.4	2.74	2.08	23.5	3.18	2.17	27.7	3.59	2.26	30.5	3.85	2.33	31.8	3.96	2.35	35.9	4.30	2.45
	70	14.6	2.14	2.00	17.3	2.44	2.08	18.5	2.57	2.12	22.4	2.95	2.23	26.4	3.30	2.34	29.1	3.52	2.42	30.3	3.61	2.46	34.2	3.90	2.57
	80	14.0	2.01	2.04	16.6	2.28	2.13	17.7	2.39	2.17	21.4	2.73	2.29	25.1	3.04	2.42	27.7	3.23	2.51	28.8	3.31	2.55	32.4	3.56	2.67
800	60	15.3	2.22	2.02	18.2	2.57	2.08	19.5	2.71	2.11	23.7	3.16	2.20	27.9	3.57	2.29	30.9	3.85	2.35	32.1	3.96	2.38	36.3	4.31	2.47
	70	14.7	2.11	2.04	17.5	2.42	2.12	18.7	2.55	2.15	22.7	2.94	2.26	26.6	3.29	2.37	29.4	3.52	2.45	30.6	3.61	2.48	34.6	3.91	2.59
	80	14.1	1.99	2.08	16.8	2.27	2.17	17.9	2.38	2.20	21.6	2.72	2.33	25.4	3.03	2.45	28.0	3.23	2.54	29.1	3.31	2.58	32.9	3.57	2.70
900	60	15.4	2.19	2.06	18.4	2.54	2.12	19.6	2.68	2.14	23.9	3.14	2.23	28.1	3.56	2.32	31.1	3.84	2.38	32.4	3.95	2.40	36.6	4.32	2.49
	70	14.8	2.10	2.08	17.7	2.41	2.15	18.9	2.53	2.18	22.9	2.93	2.29	26.9	3.29	2.40	29.7	3.52	2.47	30.9	3.62	2.51	34.9	3.92	2.61
	80	14.3	1.98	2.11	16.9	2.25	2.20	18.0	2.36	2.24	21.8	2.71	2.36	25.6	3.02	2.48	28.2	3.22	2.57	29.3	3.30	2.61	33.1	3.56	2.73

JT4BD-036K with C6B(A,H)-X36(C,U)-(B,C) + MB6B(*)-(B,C)

JT4BD-036K with B5BM-X36K-B, or GB5BM-036K-B

		OUTDOOR TEMPERATURE (Deg. F)																							
150 CFM	Indoor T. Deg.F	10			17			20			30			40			47			50			60		
		MBH	COP	kW	MBH	COP	kW	MBH	COP	kW	MBH	COP	kW	MBH	COP	kW	MBH	COP	kW	MBH	COP	kW	MBH	COP	kW
950	60	19.2	2.52	2.24	22.6	2.83	2.34	24.0	2.96	2.38	28.8	3.35	2.52	33.6	3.70	2.67	37.0	3.92	2.77	38.4	4.01	2.81	43.2	4.29	2.96
	70	18.5	2.36	2.30	21.7	2.64	2.41	23.1	2.75	2.46	27.7	3.09	2.63	32.3	3.40	2.79	35.5	3.59	2.91	36.9	3.66	2.96	41.5	3.90	3.12
	80	18.0	2.22	2.38	21.0	2.46	2.50	22.3	2.56	2.56	26.7	2.86	2.74	31.1	3.12	2.92	34.1	3.29	3.04	35.4	3.35	3.10	39.8	3.56	3.28
1100	60	19.4	2.48	2.29	22.8	2.80	2.38	24.3	2.93	2.42	29.2	3.34	2.56	34.0	3.70	2.70	37.5	3.93	2.80	38.9	4.02	2.84	43.8	4.32	2.97
	70	18.7	2.33	2.35	22.0	2.62	2.46	23.4	2.73	2.51	28.1	3.09	2.67	32.7	3.40	2.82	36.0	3.60	2.93	37.4	3.68	2.98	42.1	3.93	3.14
	80	18.1	2.19	2.43	21.3	2.44	2.55	22.6	2.54	2.61	27.0	2.85	2.78	31.5	3.13	2.95	34.6	3.30	3.07	36.0	3.38	3.12	40.4	3.59	3.30
1250	60	19.5	2.44	2.34	23.0	2.77	2.43	24.4	2.90	2.47	29.4	3.32	2.60	34.4	3.69	2.73	37.9	3.93	2.83	39.4	4.03	2.87	44.3	4.33	3.00
	70	18.9	2.31	2.40	22.3	2.60	2.51	23.7	2.72	2.55	28.4	3.08	2.70	33.1	3.40	2.86	36.5	3.61	2.96	37.9	3.69	3.01	42.6	3.96	3.16
	80	18.3	2.17	2.48	21.5	2.42	2.60	22.8	2.53	2.65	27.3	2.85	2.82	31.8	3.13	2.98	35.0	3.31	3.10	36.3	3.38	3.15	40.8	3.61	3.32

13 SEER + AHU HEATING EXPANDED RATINGS (CONTINUED)

JT4BD-042K with C6B(A,H)-X42(C,U)-(B,C) + MB6B(*)-(B,C)

JT4BD-042K with B5BM-X42K-B, or GB5BM-042K-B

		OUTDOOR TEMPERATURE (Deg. F)																							
150 CFM	Indoor T. Deg.F	10			17			20			30			40			47			50			60		
		MBH	COP	kW	MBH	COP	kW	MBH	COP	kW	MBH	COP	kW	MBH	COP	kW	MBH	COP	kW	MBH	COP	kW	MBH	COP	kW
1175	60	22.3	2.53	2.58	26.2	2.87	2.68	27.9	3.01	2.72	33.5	3.44	2.86	39.1	3.83	3.00	43.0	4.08	3.09	44.7	4.18	3.13	50.2	4.51	3.27
	70	21.5	2.34	2.70	25.3	2.65	2.80	27.0	2.77	2.85	32.4	3.16	3.00	37.8	3.51	3.15	41.5	3.74	3.26	43.2	3.83	3.30	48.6	4.12	3.46
	80	21.0	2.18	2.83	24.6	2.45	2.95	26.2	2.57	2.99	31.4	2.91	3.16	36.5	3.23	3.32	40.2	3.43	3.43	41.7	3.51	3.48	46.9	3.77	3.65
1325	60	22.5	2.51	2.63	26.5	2.85	2.72	28.2	2.99	2.76	33.8	3.43	2.89	39.5	3.84	3.02	43.5	4.10	3.11	45.2	4.21	3.15	50.9	4.55	3.28
	70	21.8	2.33	2.74	25.6	2.64	2.84	27.2	2.77	2.89	32.7	3.16	3.03	38.2	3.53	3.17	42.0	3.76	3.28	43.6	3.86	3.32	49.1	4.16	3.46
	80	21.2	2.16	2.88	24.9	2.44	2.99	26.4	2.56	3.03	31.7	2.92	3.19	37.0	3.24	3.34	40.6	3.45	3.45	42.2	3.54	3.50	47.5	3.81	3.65
1475	60	22.5	2.47	2.67	26.6	2.82	2.76	28.3	2.97	2.80	34.1	3.42	2.92	39.9	3.83	3.05	43.9	4.10	3.14	45.6	4.21	3.18	51.4	4.56	3.30
	70	22.0	2.32	2.79	25.9	2.63	2.88	27.5	2.76	2.93	33.1	3.16	3.06	38.6	3.53	3.20	42.5	3.77	3.30	44.1	3.87	3.34	49.6	4.18	3.48
	80	21.4	2.15	2.92	25.1	2.43	3.03	26.7	2.55	3.07	32.0	2.91	3.22	37.3	3.25	3.37	41.0	3.47	3.47	42.6	3.55	3.52	47.9	3.83	3.67

JT4BD-048K with C6B(A,H)-X48(C,U)-C + MB6B(*)-C

JT4BD-048K with B5BM-X48K-C, or GB5BM-048K-C

		OUTDOOR TEMPERATURE (Deg. F)																							
200 CFM	Indoor T. Deg.F	10			17			20			30			40			47			50			60		
		MBH	COP	kW	MBH	COP	kW	MBH	COP	kW	MBH	COP	kW	MBH	COP	kW	MBH	COP	kW	MBH	COP	kW	MBH	COP	kW
1475	60	25.6	2.45	3.06	29.8	2.73	3.19	31.6	2.85	3.25	37.6	3.20	3.45	43.6	3.51	3.64	47.8	3.71	3.78	49.6	3.79	3.84	55.6	4.05	4.03
	70	24.7	2.23	3.24	28.8	2.49	3.39	30.6	2.60	3.45	36.4	2.92	3.66	42.3	3.21	3.86	46.4	3.39	4.01	48.1	3.47	4.07	54.0	3.70	4.28
	80	24.2	2.06	3.45	28.1	2.29	3.61	29.8	2.38	3.67	35.5	2.67	3.89	41.1	2.93	4.11	45.0	3.09	4.27	46.7	3.16	4.33	52.3	3.37	4.55
1675	60	25.8	2.44	3.10	30.1	2.73	3.23	31.9	2.85	3.29	38.1	3.22	3.47	44.2	3.55	3.65	48.5	3.76	3.78	50.3	3.85	3.84	56.4	4.12	4.02
	70	25.0	2.23	3.29	29.2	2.50	3.43	31.0	2.61	3.48	36.9	2.94	3.68	42.8	3.25	3.87	47.0	3.44	4.01	48.8	3.52	4.06	54.7	3.77	4.26
	80	24.4	2.04	3.50	28.5	2.29	3.65	30.2	2.39	3.71	35.9	2.69	3.91	41.6	2.97	4.12	45.7	3.15	4.26	47.4	3.22	4.32	53.1	3.44	4.52
1875	60	25.9	2.41	3.15	30.3	2.71	3.27	32.2	2.84	3.33	38.4	3.22	3.50	44.7	3.56	3.68	49.1	3.78	3.81	50.9	3.87	3.86	57.2	4.15	4.04
	70	25.4	2.23	3.34	29.6	2.50	3.47	31.4	2.61	3.52	37.4	2.96	3.71	43.4	3.27	3.89	47.6	3.47	4.02	49.4	3.55	4.08	55.4	3.81	4.26
	80	24.7	2.04	3.55	28.8	2.29	3.69	30.5	2.39	3.74	36.3	2.71	3.94	42.1	2.99	4.13	46.2	3.18	4.26	47.9	3.25	4.32	53.7	3.49	4.51

JT4BD-060K with B5BM-X60K-C, or GB5BM-060K-C

		OUTDOOR TEMPERATURE (Deg. F)																							
200 CFM	Indoor T. Deg.F	10			17			20			30			40			47			50			60		
		MBH	COP	kW	MBH	COP	kW	MBH	COP	kW	MBH	COP	kW	MBH	COP	kW	MBH	COP	kW	MBH	COP	kW	MBH	COP	kW
1650	60	33.7	2.68	3.69	37.8	2.88	3.86	39.6	2.96	3.93	45.6	3.21	4.17	51.6	3.43	4.42	55.8	3.57	4.59	57.6	3.63	4.66	63.6	3.80	4.90
	70	32.7	2.41	3.97	36.8	2.60	4.15	38.5	2.68	4.22	44.4	2.91	4.47	50.3	3.12	4.72	54.4	3.26	4.89	56.1	3.31	4.96	62.0	3.49	5.21
	80	32.2	2.21	4.28	36.2	2.38	4.46	37.8	2.44	4.54	43.5	2.66	4.80	49.1	2.84	5.06	53.0	2.97	5.24	54.7	3.02	5.32	60.4	3.17	5.58
1850	60	34.0	2.68	3.72	38.2	2.89	3.88	40.0	2.98	3.95	46.1	3.24	4.18	52.2	3.48	4.41	56.5	3.63	4.57	58.3	3.69	4.63	64.4	3.88	4.86
	70	33.0	2.42	4.00	37.2	2.62	4.16	39.0	2.70	4.23	44.9	2.95	4.46	50.8	3.17	4.70	55.0	3.32	4.86	56.8	3.38	4.93	62.7	3.56	5.16
	80	32.4	2.20	4.31	36.5	2.39	4.48	38.2	2.46	4.55	43.9	2.69	4.79	49.7	2.89	5.03	53.7	3.03	5.20	55.4	3.08	5.27	61.2	3.25	5.51
2050	60	33.9	2.65	3.75	38.3	2.88	3.91	40.2	2.97	3.97	46.5	3.25	4.20	52.7	3.50	4.42	57.1	3.66	4.58	59.0	3.72	4.64	65.2	3.93	4.87
	70	33.4	2.43	4.04	37.6	2.63	4.19	39.4	2.71	4.26	45.4	2.97	4.48	51.4	3.21	4.70	55.6	3.36	4.85	57.4	3.42	4.92	63.4	3.62	5.14
	80	32.7	2.21	4.35	36.8	2.40	4.51	38.6	2.47	4.57	44.4	2.71	4.80	50.2	2.93	5.02	54.2	3.07	5.18	56.0	3.13	5.24	61.8	3.32	5.47

JT4BD-018K with GB5BMM024K-(A,B)

		OUTDOOR TEMPERATURE (Deg. F)																							
100 CFM	Indoor T. Deg.F	10			17			20			30			40			47			50			60		
		MBH	COP	kW	MBH	COP	kW	MBH	COP	kW	MBH	COP	kW	MBH	COP	kW	MBH	COP	kW	MBH	COP	kW	MBH	COP	kW
545	60	9.2	2.02	1.33	11.4	2.40	1.40	12.4	2.55	1.42	15.6	3.01	1.52	18.8	3.42	1.61	21.0	3.68	1.68	22.0	3.78	1.71	25.2	4.11	1.80
	70	8.7	2.03	1.25	10.7	2.35	1.34	11.6	2.47	1.38	14.6	2.84	1.50	17.5	3.16	1.63	19.6	3.35	1.71	20.5	3.43	1.75	23.4	3.66	1.88
	80	8.0	1.98	1.19	9.9	2.26	1.29	10.8	2.36	1.34	13.5	2.67	1.48	16.2	2.93	1.62	18.1	3.08	1.72	18.9	3.14	1.76	21.6	3.32	1.91
645	60	9.2	1.96	1.37	11.5	2.34	1.44	12.5	2.50	1.47	15.7	2.97	1.56	19.0	3.38	1.65	21.3	3.65	1.71	22.3	3.76	1.74	25.6	4.10	1.83
	70	8.8	1.97	1.30	10.9	2.29	1.39	11.8	2.42	1.43	14.8	2.80	1.55	17.8	3.13	1.67	19.9	3.33	1.75	20.8	3.41	1.79	23.8	3.65	1.91
	80	8.2	1.94	1.23	10.1	2.22	1.34	10.9	2.33	1.38	13.7	2.64	1.52	16.5	2.90	1.67	18.4	3.06	1.77	19.3	3.12	1.81	22.1	3.30	1.96
745	60	9.4	1.94	1.42	11.7	2.31	1.48	12.7	2.47	1.51	16.0	2.94	1.59	19.2	3.36	1.68	21.5	3.63	1.74	22.5	3.74	1.77	25.8	4.09	1.85
	70	8.9	1.93	1.34	11.0	2.26	1.43	11.9	2.39	1.46	15.0	2.78	1.58	18.0	3.11	1.70	20.2	3.31	1.79	21.1	3.40	1.82	24.2	3.65	1.94
	80	8.3	1.91	1.28	10.3	2.18	1.38	11.1	2.29	1.42	13.9	2.60	1.57	16.7	2.86	1.71	18.6	3.01	1.81	19.5	3.08	1.86	22.3	3.26	2.00

13 SEER + AHU HEATING EXPANDED RATINGS (CONTINUED)

JT4BD-024K with GB5BMM024K-(A,B)

		OUTDOOR TEMPERATURE (Deg. F)																							
100 CFM	Indoor T.	10			17			20			30			40			47			50			60		
	Deg.F	MBH	COP	kW	MBH	COP	kW	MBH	COP	kW	MBH	COP	kW	MBH	COP	kW	MBH	COP	kW	MBH	COP	kW	MBH	COP	kW
720	60	13.2	2.38	1.63	15.8	2.72	1.70	16.9	2.86	1.73	20.6	3.28	1.84	24.2	3.65	1.95	26.8	3.89	2.02	27.9	3.98	2.06	31.6	4.28	2.16
	70	12.6	2.32	1.59	15.0	2.61	1.69	16.1	2.73	1.73	19.5	3.07	1.86	23.0	3.37	2.00	25.4	3.56	2.09	26.4	3.63	2.13	29.8	3.86	2.27
	80	12.0	2.23	1.58	14.3	2.48	1.69	15.2	2.58	1.73	18.5	2.87	1.88	21.7	3.12	2.04	23.9	3.27	2.14	24.9	3.33	2.19	28.1	3.52	2.34
820	60	13.3	2.33	1.67	15.9	2.68	1.74	17.0	2.81	1.77	20.7	3.24	1.88	24.5	3.63	1.98	27.1	3.87	2.05	28.2	3.97	2.08	32.0	4.28	2.19
	70	12.7	2.28	1.64	15.2	2.57	1.73	16.2	2.69	1.77	19.7	3.04	1.90	23.2	3.35	2.03	25.7	3.54	2.12	26.7	3.62	2.16	30.2	3.86	2.29
	80	12.1	2.20	1.62	14.4	2.45	1.72	15.4	2.55	1.77	18.7	2.85	1.92	22.0	3.11	2.07	24.3	3.26	2.18	25.2	3.32	2.23	28.5	3.52	2.38
920	60	13.4	2.29	1.71	16.0	2.64	1.78	17.2	2.78	1.81	20.9	3.21	1.91	24.7	3.61	2.01	27.4	3.86	2.08	28.5	3.96	2.11	32.3	4.28	2.21
	70	12.8	2.25	1.68	15.3	2.54	1.77	16.4	2.66	1.81	19.9	3.02	1.93	23.5	3.34	2.06	26.0	3.54	2.15	27.0	3.62	2.19	30.6	3.87	2.32
	80	12.3	2.17	1.66	14.6	2.42	1.76	15.6	2.52	1.81	18.9	2.82	1.96	22.1	3.08	2.11	24.5	3.24	2.22	25.4	3.30	2.26	28.7	3.49	2.41

JT4BD-030K with GB5BMM030K-(A,B)

		OUTDOOR TEMPERATURE (Deg. F)																							
150 CFM	Indoor T.	10			17			20			30			40			47			50			60		
	Deg.F	MBH	COP	kW	MBH	COP	kW	MBH	COP	kW	MBH	COP	kW	MBH	COP	kW	MBH	COP	kW	MBH	COP	kW	MBH	COP	kW
930	60	16.6	2.46	1.98	19.8	2.74	2.12	21.1	2.84	2.18	25.7	3.16	2.38	30.2	3.43	2.59	33.4	3.59	2.73	34.8	3.66	2.79	39.3	3.85	2.99
	70	15.9	2.34	2.00	19.0	2.57	2.16	20.3	2.66	2.23	24.6	2.92	2.47	28.9	3.14	2.70	31.9	3.27	2.86	33.2	3.33	2.93	37.6	3.48	3.16
	80	15.4	2.21	2.04	18.2	2.41	2.22	19.5	2.48	2.30	23.6	2.70	2.56	27.6	2.88	2.81	30.5	2.99	2.99	31.7	3.03	3.07	35.8	3.16	3.33
1080	60	16.7	2.41	2.03	20.0	2.70	2.17	21.4	2.81	2.23	26.0	3.15	2.42	30.6	3.43	2.62	33.9	3.60	2.76	35.2	3.67	2.81	39.9	3.89	3.01
	70	16.1	2.29	2.06	19.2	2.54	2.22	20.5	2.63	2.29	24.9	2.91	2.51	29.3	3.15	2.73	32.4	3.29	2.89	33.7	3.35	2.96	38.1	3.52	3.18
	80	15.5	2.17	2.10	18.5	2.38	2.28	19.7	2.46	2.35	23.9	2.70	2.60	28.1	2.89	2.85	31.0	3.01	3.02	32.3	3.05	3.10	36.5	3.19	3.35
1230	60	16.9	2.37	2.08	20.1	2.67	2.22	21.6	2.78	2.27	26.3	3.13	2.46	31.0	3.42	2.65	34.3	3.61	2.79	35.7	3.68	2.84	40.4	3.90	3.03
	70	16.3	2.27	2.11	19.4	2.52	2.26	20.8	2.62	2.33	25.3	2.91	2.55	29.7	3.15	2.77	32.8	3.30	2.92	34.2	3.36	2.98	38.7	3.54	3.20
	80	15.7	2.14	2.16	18.7	2.36	2.33	20.0	2.44	2.40	24.2	2.68	2.64	28.4	2.89	2.88	31.4	3.01	3.05	32.6	3.06	3.13	36.9	3.21	3.37

JT4BD-036K with GB5BMM036K-B

		OUTDOOR TEMPERATURE (Deg. F)																							
150 CFM	Indoor T.	10			17			20			30			40			47			50			60		
	Deg.F	MBH	COP	kW	MBH	COP	kW	MBH	COP	kW	MBH	COP	kW	MBH	COP	kW	MBH	COP	kW	MBH	COP	kW	MBH	COP	kW
1035	60	19.2	2.51	2.24	22.9	2.83	2.37	24.5	2.97	2.42	29.8	3.36	2.60	35.1	3.70	2.78	38.8	3.92	2.90	40.4	4.01	2.96	45.7	4.28	3.14
	70	18.5	2.35	2.31	22.1	2.64	2.45	23.6	2.76	2.51	28.7	3.10	2.71	33.8	3.40	2.91	37.4	3.59	3.05	38.9	3.66	3.11	44.0	3.89	3.32
	80	17.9	2.20	2.39	21.3	2.46	2.55	22.8	2.56	2.61	27.7	2.87	2.83	32.6	3.13	3.05	36.0	3.29	3.21	37.4	3.35	3.27	42.3	3.55	3.50
1185	60	19.3	2.47	2.30	23.1	2.81	2.42	24.7	2.94	2.47	30.1	3.35	2.64	35.5	3.71	2.81	39.3	3.94	2.93	40.9	4.03	2.98	46.3	4.31	3.15
	70	18.7	2.32	2.36	22.3	2.62	2.50	23.9	2.74	2.56	29.0	3.10	2.75	34.2	3.41	2.94	37.8	3.61	3.08	39.4	3.69	3.13	44.6	3.93	3.33
	80	18.1	2.17	2.45	21.6	2.44	2.59	23.1	2.54	2.66	28.0	2.86	2.87	33.0	3.14	3.08	36.5	3.31	3.23	38.0	3.38	3.30	42.9	3.59	3.51
1335	60	19.4	2.43	2.34	23.3	2.77	2.46	24.9	2.91	2.51	30.4	3.33	2.68	35.9	3.70	2.84	39.7	3.94	2.96	41.4	4.03	3.01	46.9	4.33	3.18
	70	18.9	2.30	2.41	22.6	2.60	2.54	24.1	2.72	2.60	29.4	3.09	2.79	34.6	3.42	2.97	38.3	3.62	3.10	39.9	3.70	3.16	45.1	3.95	3.35
	80	18.3	2.15	2.49	21.8	2.42	2.64	23.3	2.53	2.70	28.3	2.86	2.91	33.3	3.14	3.11	36.8	3.32	3.26	38.3	3.39	3.32	43.4	3.61	3.53

JT4BD-042K with GB5BMM042K-B

		OUTDOOR TEMPERATURE (Deg. F)																							
150 CFM	Indoor T.	10			17			20			30			40			47			50			60		
	Deg.F	MBH	COP	kW	MBH	COP	kW	MBH	COP	kW	MBH	COP	kW	MBH	COP	kW	MBH	COP	kW	MBH	COP	kW	MBH	COP	kW
1385	60	22.4	2.41	2.72	26.3	2.65	2.91	27.9	2.74	2.98	33.4	3.02	3.24	38.9	3.26	3.50	42.7	3.40	3.68	44.3	3.46	3.76	49.8	3.63	4.02
	70	21.7	2.22	2.87	25.4	2.43	3.06	27.0	2.51	3.15	32.2	2.76	3.43	37.5	2.97	3.71	41.2	3.10	3.90	42.8	3.15	3.99	48.1	3.31	4.27
	80	21.1	2.05	3.02	24.7	2.24	3.24	26.2	2.31	3.33	31.3	2.52	3.63	36.3	2.71	3.94	39.9	2.82	4.15	41.4	2.86	4.24	46.4	3.00	4.55
1535	60	22.6	2.39	2.77	26.5	2.64	2.94	28.2	2.74	3.02	33.7	3.03	3.27	39.3	3.28	3.51	43.2	3.43	3.69	44.9	3.49	3.76	50.4	3.68	4.01
	70	21.9	2.21	2.91	25.6	2.43	3.10	27.2	2.51	3.18	32.6	2.77	3.45	38.0	3.00	3.72	41.7	3.13	3.91	43.3	3.19	3.99	48.7	3.35	4.26
	80	21.3	2.03	3.07	24.9	2.23	3.27	26.4	2.31	3.36	31.6	2.54	3.65	36.7	2.73	3.94	40.4	2.85	4.15	41.9	2.90	4.23	47.1	3.05	4.52
1685	60	22.6	2.37	2.81	26.6	2.62	2.98	28.3	2.72	3.05	34.0	3.02	3.30	39.6	3.28	3.54	43.6	3.45	3.71	45.3	3.51	3.78	51.0	3.71	4.03
	70	22.1	2.20	2.95	25.9	2.42	3.13	27.5	2.51	3.21	33.0	2.78	3.47	38.4	3.01	3.73	42.2	3.16	3.92	43.8	3.21	4.00	49.2	3.39	4.26
	80	21.5	2.03	3.11	25.1	2.23	3.31	26.7	2.31	3.39	31.9	2.55	3.67	37.1	2.75	3.95	40.7	2.88	4.15	42.3	2.93	4.23	47.5	3.09	4.51

JT4BD-048K with GB5BMM048K-(B,C)

		OUTDOOR TEMPERATURE (Deg. F)																							
200 CFM	Indoor T.	10			17			20			30			40			47			50			60		
	Deg.F	MBH	COP	kW	MBH	COP	kW	MBH	COP	kW	MBH	COP	kW	MBH	COP	kW	MBH	COP	kW	MBH	COP	kW	MBH	COP	kW
1160	60	26.2	2.59	2.97	30.9	2.83	3.20	32.8	2.92	3.30	39.4	3.19	3.63	46.1	3.42	3.95	50.7	3.56	4.18	52.7	3.61	4.28	59.3	3.77	4.60
	70	25.4	2.36	3.15	29.9	2.58	3.40	31.8	2.66	3.50	38.3	2.91	3.85	44.7	3.12	4.20	49.2	3.25	4.45	51.2	3.30	4.55	57.6	3.45	4.90
	80	24.9	2.18	3.35	29.2	2.37	3.62	31.1	2.44	3.73	37.3	2.66	4.11	43.5	2.84	4.49	47.9	2.95	4.75	49.8	3.00	4.87	56.0	3.13	5.24
1360	60	26.5	2.57	3.02	31.2	2.82	3.24	33.2	2.92	3.33	39.9	3.21	3.64	46.6	3.46	3.95	51.3	3.61	4.17	53.4	3.67	4.26	60.1	3.85	4.58
	70	25.7	2.35	3.20	30.3	2.59	3.44	32.2	2.67	3.53	38.8	2.94	3.87	45.3	3.16	4.20	49.9	3.30	4.43	51.8	3.35	4.53	58.3	3.52	4.86
	80	25.1	2.16	3.41	29.5	2.37	3.66	31.4	2.45	3.76	37.8	2.69	4.12	44.1	2.89	4.48	48.5	3.01	4.73	50.4	3.06	4.83	56.8	3.21	5.19
1560	60	26.6	2.54	3.07	31.4	2.80	3.28	33.4	2.91	3.37	40.3	3.21	3.67	47.1	3.48	3.98	51.9	3.64	4.19	54.0	3.70	4.28	60.8	3.89	4.58
	70	26.1	2.35	3.26	30.7	2.59	3.48	32.7	2.68	3.58	39.2	2.96	3.89	45.8	3.19	4.21	50.5	3.34	4.44	52.4	3.39	4.53	59.0	3.57	4.85
	80	25.4	2.15	3.46	29.9	2.37	3.70	31.8	2.45	3.80	38.2	2.71	4.14	44.6	2.92	4.48	49.1	3.05	4.72	51.0	3.10	4.82	57.4	3.26	5.16

13 SEER + AHU HEATING EXPANDED RATINGS (CONTINUED)

JT4BD-060K with GB5BMM060K-C

		OUTDOOR TEMPERATURE (Deg. F)																							
200 CFM	Indoor T. Deg.F	10			17			20			30			40			47			50			60		
		MBH	COP	kW	MBH	COP	kW	MBH	COP	kW	MBH	COP	kW	MBH	COP	kW	MBH	COP	kW	MBH	COP	kW	MBH	COP	kW
1400	60	30.3	2.29	3.88	36.4	2.56	4.17	39.0	2.67	4.29	47.7	2.97	4.70	56.4	3.23	5.12	62.5	3.39	5.41	65.1	3.45	5.53	73.8	3.64	5.94
	70	29.4	2.05	4.20	35.4	2.30	4.50	37.9	2.40	4.63	46.5	2.69	5.06	55.0	2.94	5.49	61.0	3.09	5.79	63.6	3.15	5.92	72.1	3.33	6.34
	80	28.9	1.87	4.54	34.7	2.10	4.86	37.2	2.18	5.00	45.6	2.45	5.46	53.9	2.67	5.92	59.7	2.81	6.24	62.3	2.86	6.38	70.6	3.03	6.84
1600	60	30.6	2.30	3.91	36.8	2.58	4.18	39.4	2.69	4.30	48.2	3.01	4.69	57.0	3.29	5.09	63.2	3.46	5.36	65.8	3.52	5.48	74.6	3.73	5.87
	70	29.7	2.07	4.22	35.8	2.33	4.50	38.4	2.43	4.63	47.0	2.74	5.03	55.6	3.00	5.44	61.7	3.16	5.73	64.3	3.22	5.85	72.9	3.42	6.26
	80	29.1	1.87	4.57	35.0	2.11	4.87	37.6	2.20	5.00	46.0	2.49	5.43	54.5	2.73	5.86	60.4	2.88	6.16	62.9	2.94	6.28	71.4	3.12	6.71
1800	60	30.6	2.28	3.93	36.9	2.57	4.20	39.6	2.69	4.32	48.6	3.03	4.70	57.5	3.31	5.09	63.8	3.49	5.36	66.5	3.56	5.48	75.5	3.77	5.86
	70	30.1	2.07	4.26	36.2	2.34	4.53	38.8	2.45	4.65	47.5	2.76	5.04	56.2	3.04	5.43	62.3	3.20	5.70	64.9	3.27	5.82	73.6	3.48	6.21
	80	29.4	1.87	4.60	35.4	2.12	4.89	37.9	2.22	5.01	46.5	2.52	5.41	55.0	2.77	5.82	61.0	2.93	6.10	63.5	2.99	6.23	72.0	3.19	6.63

13 SEER + VSB HEATING EXPANDED RATINGS

JT4BD-018K with C6B(A,H)-X24(C,U)-(A,B) + VSB

JT4BD-018K with B4VM-X24K-(A,B)

		OUTDOOR TEMPERATURE (Deg. F)																							
100 CFM	Indoor T. Deg.F	10			17			20			30			40			47			50			60		
		MBH	COP	kW	MBH	COP	kW	MBH	COP	kW	MBH	COP	kW	MBH	COP	kW	MBH	COP	kW	MBH	COP	kW	MBH	COP	kW
500	60	9.0	1.99	1.33	10.9	2.40	1.34	11.8	2.57	1.34	14.5	3.14	1.35	17.2	3.70	1.37	19.2	4.09	1.37	20.0	4.25	1.38	22.7	4.80	1.39
	70	8.5	2.00	1.25	10.3	2.36	1.27	11.0	2.51	1.29	13.5	2.99	1.32	16.0	3.45	1.36	17.7	3.76	1.38	18.5	3.88	1.39	20.9	4.30	1.43
	80	7.9	1.95	1.19	9.5	2.28	1.22	10.2	2.42	1.23	12.4	2.84	1.28	14.6	3.24	1.32	16.2	3.51	1.35	16.9	3.62	1.37	19.1	3.97	1.41
600	60	9.1	1.93	1.37	11.0	2.34	1.38	11.9	2.51	1.39	14.7	3.08	1.40	17.5	3.65	1.41	19.4	4.03	1.41	20.3	4.20	1.42	23.1	4.75	1.43
	70	8.6	1.94	1.30	10.4	2.30	1.33	11.2	2.45	1.34	13.7	2.93	1.37	16.2	3.39	1.40	18.0	3.70	1.43	18.8	3.83	1.44	21.3	4.25	1.47
	80	8.0	1.92	1.23	9.7	2.24	1.26	10.3	2.37	1.28	12.6	2.80	1.33	14.9	3.19	1.38	16.6	3.44	1.41	17.3	3.55	1.43	19.6	3.89	1.48
700	60	9.3	1.91	1.42	11.2	2.31	1.43	12.1	2.48	1.43	14.9	3.05	1.43	17.7	3.61	1.44	19.7	4.00	1.44	20.5	4.17	1.44	23.3	4.72	1.45
	70	8.7	1.91	1.34	10.5	2.27	1.36	11.3	2.42	1.37	13.9	2.90	1.41	16.5	3.36	1.44	18.3	3.67	1.46	19.1	3.80	1.47	21.7	4.22	1.51
	80	8.2	1.89	1.27	9.8	2.20	1.31	10.5	2.33	1.32	12.8	2.73	1.37	15.1	3.11	1.42	16.7	3.36	1.46	17.4	3.47	1.48	19.8	3.80	1.53

JT4BD-024K with C6B(A,H)-X24(C,U)-(A,B) + VSB

JT4BD-024K with B4VM-X24K-(A,B)

		OUTDOOR TEMPERATURE (Deg. F)																							
100 CFM	Indoor T. Deg.F	10			17			20			30			40			47			50			60		
		MBH	COP	kW	MBH	COP	kW	MBH	COP	kW	MBH	COP	kW	MBH	COP	kW	MBH	COP	kW	MBH	COP	kW	MBH	COP	kW
650	60	11.6	2.16	1.57	14.0	2.57	1.59	15.0	2.74	1.61	18.5	3.29	1.65	21.9	3.82	1.69	24.4	4.17	1.71	25.4	4.32	1.73	28.9	4.79	1.77
	70	11.0	2.12	1.52	13.3	2.48	1.56	14.2	2.63	1.58	17.4	3.11	1.65	20.7	3.54	1.71	22.9	3.83	1.75	23.9	3.95	1.77	27.1	4.33	1.84
	80	10.4	2.04	1.50	12.5	2.37	1.55	13.4	2.50	1.57	16.4	2.92	1.64	19.3	3.31	1.71	21.4	3.56	1.77	22.3	3.66	1.79	25.3	3.99	1.86
750	60	11.6	2.12	1.61	14.1	2.53	1.63	15.1	2.70	1.64	18.7	3.25	1.68	22.2	3.78	1.72	24.6	4.14	1.75	25.7	4.29	1.76	29.2	4.77	1.80
	70	11.1	2.08	1.57	13.4	2.44	1.61	14.4	2.59	1.63	17.6	3.06	1.69	20.9	3.51	1.75	23.2	3.80	1.79	24.2	3.92	1.81	27.4	4.31	1.87
	80	10.5	2.01	1.53	12.7	2.34	1.59	13.6	2.47	1.61	16.6	2.89	1.68	19.7	3.27	1.76	21.8	3.52	1.81	22.7	3.63	1.84	25.7	3.95	1.91
850	60	11.8	2.09	1.65	14.2	2.49	1.68	15.3	2.66	1.69	18.9	3.22	1.72	22.4	3.75	1.75	24.9	4.11	1.77	25.9	4.26	1.78	29.5	4.76	1.82
	70	11.2	2.05	1.61	13.5	2.41	1.65	14.5	2.56	1.66	17.9	3.04	1.72	21.2	3.49	1.78	23.5	3.78	1.82	24.5	3.90	1.84	27.8	4.29	1.90
	80	10.7	1.99	1.57	12.8	2.31	1.63	13.7	2.44	1.65	16.8	2.85	1.73	19.8	3.23	1.80	22.0	3.47	1.85	22.9	3.58	1.88	25.9	3.90	1.95

JT4BD-030K with C6B(A,H)-X30(C,U)-(A,B,C) + VSB

JT4BD-030K with B4VM-X30K-(A,B)

		OUTDOOR TEMPERATURE (Deg. F)																							
100 CFM	Indoor T. Deg.F	10			17			20			30			40			47			50			60		
		MBH	COP	kW	MBH	COP	kW	MBH	COP	kW	MBH	COP	kW	MBH	COP	kW	MBH	COP	kW	MBH	COP	kW	MBH	COP	kW
750	60	14.7	2.42	1.78	17.6	2.77	1.87	18.9	2.91	1.90	23.1	3.33	2.03	27.2	3.70	2.16	30.1	3.94	2.25	31.4	4.03	2.28	35.6	4.33	2.41
	70	14.1	2.33	1.77	16.8	2.63	1.88	18.0	2.75	1.92	22.0	3.11	2.08	25.9	3.41	2.23	28.7	3.60	2.33	29.9	3.68	2.38	33.8	3.92	2.53
	80	13.5	2.23	1.78	16.1	2.49	1.90	17.2	2.59	1.95	20.9	2.90	2.12	24.7	3.16	2.29	27.3	3.32	2.41	28.4	3.38	2.46	32.1	3.57	2.63
850	60	14.8	2.38	1.82	17.7	2.73	1.90	19.0	2.87	1.94	23.2	3.30	2.06	27.5	3.69	2.19	30.5	3.93	2.27	31.7	4.03	2.31	36.0	4.34	2.43
	70	14.2	2.30	1.81	17.0	2.60	1.92	18.2	2.72	1.96	22.2	3.09	2.11	26.2	3.40	2.26	29.0	3.60	2.36	30.2	3.68	2.41	34.2	3.93	2.56
	80	13.6	2.20	1.82	16.3	2.46	1.93	17.4	2.57	1.99	21.2	2.88	2.16	25.0	3.15	2.33	27.6	3.31	2.44	28.7	3.38	2.49	32.5	3.58	2.66
950	60	14.9	2.34	1.86	17.9	2.70	1.94	19.1	2.84	1.98	23.4	3.28	2.10	27.7	3.67	2.21	30.7	3.92	2.30	32.0	4.02	2.33	36.3	4.34	2.45
	70	14.3	2.27	1.85	17.2	2.58	1.95	18.4	2.70	1.99	22.4	3.07	2.14	26.5	3.39	2.29	29.3	3.60	2.39	30.5	3.68	2.43	34.6	3.93	2.58
	80	13.7	2.17	1.85	16.4	2.44	1.97	17.5	2.54	2.02	21.3	2.86	2.19	25.1	3.13	2.36	27.8	3.30	2.47	28.9	3.36	2.52	32.7	3.57	2.69

13 SEER + VSB HEATING EXPANDED RATINGS (CONTINUED)

JT4BD-036K with C6B(A,H)-X36(C,U)-(B,C) + VSB

JT4BD-036K with B4VM-X36K-B

		OUTDOOR TEMPERATURE (Deg. F)																							
150 CFM	Indoor T. Deg.F	10			17			20			30			40			47			50			60		
		MBH	COP	kW	MBH	COP	kW	MBH	COP	kW	MBH	COP	kW	MBH	COP	kW	MBH	COP	kW	MBH	COP	kW	MBH	COP	kW
950	60	17.3	2.48	2.05	21.0	2.83	2.18	22.5	2.96	2.23	27.7	3.36	2.42	32.9	3.71	2.61	36.6	3.92	2.74	38.2	4.00	2.79	43.4	4.26	2.98
	70	16.7	2.35	2.08	20.2	2.65	2.23	21.7	2.77	2.29	26.6	3.12	2.51	31.6	3.41	2.72	35.1	3.59	2.87	36.6	3.66	2.94	41.6	3.87	3.15
	80	16.1	2.21	2.13	19.4	2.48	2.30	20.9	2.58	2.37	25.6	2.88	2.61	30.4	3.14	2.84	33.7	3.29	3.01	35.2	3.35	3.08	39.9	3.53	3.31
1100	60	17.5	2.44	2.10	21.2	2.79	2.23	22.8	2.93	2.28	28.1	3.34	2.46	33.4	3.71	2.64	37.1	3.93	2.77	38.7	4.02	2.82	43.9	4.30	3.00
	70	16.9	2.31	2.14	20.4	2.62	2.28	21.9	2.74	2.35	27.0	3.10	2.55	32.1	3.41	2.76	35.6	3.60	2.90	37.1	3.68	2.96	42.2	3.91	3.17
	80	16.2	2.18	2.19	19.7	2.45	2.35	21.1	2.56	2.42	26.0	2.88	2.65	30.8	3.14	2.88	34.2	3.30	3.04	35.7	3.37	3.11	40.5	3.57	3.33
1250	60	17.6	2.40	2.15	21.3	2.75	2.27	23.0	2.89	2.33	28.3	3.32	2.50	33.7	3.69	2.68	37.5	3.93	2.80	39.1	4.02	2.85	44.5	4.31	3.03
	70	17.1	2.28	2.19	20.6	2.60	2.33	22.2	2.72	2.39	27.3	3.09	2.59	32.5	3.41	2.79	36.1	3.61	2.93	37.6	3.69	2.99	42.7	3.93	3.19
	80	16.5	2.15	2.24	19.9	2.43	2.40	21.4	2.54	2.47	26.3	2.86	2.69	31.2	3.14	2.91	34.6	3.31	3.07	36.1	3.37	3.13	41.0	3.58	3.36

JT4BD-042K with C6B(A,H)-X42(C,U)-(B,C) + VSB

JT4BD-042K with B4VM-X48K-(B,C)

		OUTDOOR TEMPERATURE (Deg. F)																							
150 CFM	Indoor T. Deg.F	10			17			20			30			40			47			50			60		
		MBH	COP	kW	MBH	COP	kW	MBH	COP	kW	MBH	COP	kW	MBH	COP	kW	MBH	COP	kW	MBH	COP	kW	MBH	COP	kW
1175	60	22.3	2.53	2.58	26.2	2.87	2.68	27.9	3.01	2.72	33.5	3.44	2.86	39.1	3.83	3.00	43.0	4.08	3.09	44.7	4.18	3.13	50.2	4.51	3.27
	70	21.5	2.34	2.70	25.3	2.65	2.80	27.0	2.77	2.85	32.4	3.16	3.00	37.8	3.51	3.15	41.5	3.74	3.26	43.2	3.83	3.30	48.6	4.12	3.46
	80	21.0	2.18	2.83	24.6	2.45	2.95	26.2	2.57	2.99	31.4	2.91	3.16	36.5	3.23	3.32	40.2	3.43	3.43	41.7	3.51	3.48	46.9	3.77	3.65
1325	60	22.5	2.51	2.63	26.5	2.85	2.72	28.2	2.99	2.76	33.8	3.43	2.89	39.5	3.84	3.02	43.5	4.10	3.11	45.2	4.21	3.15	50.9	4.55	3.28
	70	21.8	2.33	2.74	25.6	2.64	2.84	27.2	2.77	2.89	32.7	3.16	3.03	38.2	3.53	3.17	42.0	3.76	3.28	43.6	3.86	3.32	49.1	4.16	3.46
	80	21.2	2.16	2.88	24.9	2.44	2.99	26.4	2.56	3.03	31.7	2.92	3.19	37.0	3.24	3.34	40.6	3.45	3.45	42.2	3.54	3.50	47.5	3.81	3.65
1475	60	22.5	2.47	2.67	26.6	2.82	2.76	28.3	2.97	2.80	34.1	3.42	2.92	39.9	3.83	3.05	43.9	4.10	3.14	45.6	4.21	3.18	51.4	4.56	3.30
	70	22.0	2.32	2.79	25.9	2.63	2.88	27.5	2.76	2.93	33.1	3.16	3.06	38.6	3.53	3.20	42.5	3.77	3.30	44.1	3.87	3.34	49.6	4.18	3.48
	80	21.4	2.15	2.92	25.1	2.43	3.03	26.7	2.55	3.07	32.0	2.91	3.22	37.3	3.25	3.37	41.0	3.47	3.47	42.6	3.55	3.52	47.9	3.83	3.67

JT4BD-048K with C6B(A,H)-X48(C,U)-(C,D) + VSB

JT4BD-048K with B4VM-X48K-C

		OUTDOOR TEMPERATURE (Deg. F)																							
200 CFM	Indoor T. Deg.F	10			17			20			30			40			47			50			60		
		MBH	COP	kW	MBH	COP	kW	MBH	COP	kW	MBH	COP	kW	MBH	COP	kW	MBH	COP	kW	MBH	COP	kW	MBH	COP	kW
1475	60	25.6	2.45	3.06	29.8	2.73	3.19	31.6	2.85	3.25	37.6	3.20	3.45	43.6	3.51	3.64	47.8	3.71	3.78	49.6	3.79	3.84	55.6	4.05	4.03
	70	24.7	2.23	3.24	28.8	2.49	3.39	30.6	2.60	3.45	36.4	2.92	3.66	42.3	3.21	3.86	46.4	3.39	4.01	48.1	3.47	4.07	54.0	3.70	4.28
	80	24.2	2.06	3.45	28.1	2.29	3.61	29.8	2.38	3.67	35.5	2.67	3.89	41.1	2.93	4.11	45.0	3.09	4.27	46.7	3.16	4.33	52.3	3.37	4.55
1675	60	25.8	2.44	3.10	30.1	2.73	3.23	31.9	2.85	3.29	38.1	3.22	3.47	44.2	3.55	3.65	48.5	3.76	3.78	50.3	3.85	3.84	56.4	4.12	4.02
	70	25.0	2.23	3.29	29.2	2.50	3.43	31.0	2.61	3.48	36.9	2.94	3.68	42.8	3.25	3.87	47.0	3.44	4.01	48.8	3.52	4.06	54.7	3.77	4.26
	80	24.4	2.04	3.50	28.5	2.29	3.65	30.2	2.39	3.71	35.9	2.69	3.91	41.6	2.97	4.12	45.7	3.15	4.26	47.4	3.22	4.32	53.1	3.44	4.52
1875	60	25.9	2.41	3.15	30.3	2.71	3.27	32.2	2.84	3.33	38.4	3.22	3.50	44.7	3.56	3.68	49.1	3.78	3.81	50.9	3.87	3.86	57.2	4.15	4.04
	70	25.4	2.23	3.34	29.6	2.50	3.47	31.4	2.61	3.52	37.4	2.96	3.71	43.4	3.27	3.89	47.6	3.47	4.02	49.4	3.55	4.08	55.4	3.81	4.26
	80	24.7	2.04	3.55	28.8	2.29	3.69	30.5	2.39	3.74	36.3	2.71	3.94	42.1	2.99	4.13	46.2	3.18	4.26	47.9	3.25	4.32	53.7	3.49	4.51

JT4BD-060K with C6B(A,H)-X60(C,U)-(C,D) + VSB

JT4BD-060K with B4VM-X60K-C

		OUTDOOR TEMPERATURE (Deg. F)																							
200 CFM	Indoor T. Deg.F	10			17			20			30			40			47			50			60		
		MBH	COP	kW	MBH	COP	kW	MBH	COP	kW	MBH	COP	kW	MBH	COP	kW	MBH	COP	kW	MBH	COP	kW	MBH	COP	kW
1650	60	33.7	2.68	3.69	37.8	2.88	3.86	39.6	2.96	3.93	45.6	3.21	4.17	51.6	3.43	4.42	55.8	3.57	4.59	57.6	3.63	4.66	63.6	3.80	4.90
	70	32.7	2.41	3.97	36.8	2.60	4.15	38.5	2.68	4.22	44.4	2.91	4.47	50.3	3.12	4.72	54.4	3.26	4.89	56.1	3.31	4.96	62.0	3.49	5.21
	80	32.2	2.21	4.28	36.2	2.38	4.46	37.8	2.44	4.54	43.5	2.66	4.80	49.1	2.84	5.06	53.0	2.97	5.24	54.7	3.02	5.32	60.4	3.17	5.58
1850	60	34.0	2.68	3.72	38.2	2.89	3.88	40.0	2.98	3.95	46.1	3.24	4.18	52.2	3.48	4.41	56.5	3.63	4.57	58.3	3.69	4.63	64.4	3.88	4.86
	70	33.0	2.42	4.00	37.2	2.62	4.16	39.0	2.70	4.23	44.9	2.95	4.46	50.8	3.17	4.70	55.0	3.32	4.86	56.8	3.38	4.93	62.7	3.56	5.16
	80	32.4	2.20	4.31	36.5	2.39	4.48	38.2	2.46	4.55	43.9	2.69	4.79	49.7	2.89	5.03	53.7	3.03	5.20	55.4	3.08	5.27	61.2	3.25	5.51
2050	60	33.9	2.65	3.75	38.3	2.88	3.91	40.2	2.97	3.97	46.5	3.25	4.20	52.7	3.50	4.42	57.1	3.66	4.58	59.0	3.72	4.64	65.2	3.93	4.87
	70	33.4	2.43	4.04	37.6	2.63	4.19	39.4	2.71	4.26	45.4	2.97	4.48	51.4	3.21	4.70	55.6	3.36	4.85	57.4	3.42	4.92	63.4	3.62	5.14
	80	32.7	2.21	4.35	36.8	2.40	4.51	38.6	2.47	4.57	44.4	2.71	4.80	50.2	2.93	5.02	54.2	3.07	5.18	56.0	3.13	5.24	61.8	3.32	5.47



GENERAL TERMS OF LIMITED WARRANTY

NORDYNE will furnish a replacement for any part of this product which fails in normal use and service within the first ten years of installation, in accordance with the terms of the warranty.

For complete details of the Limited Warranty, including applicable terms and conditions, see your local installer or contact the NORDYNE warranty department for a copy.

NORDYNE
COMPLETE COMFORT. GENUINE VALUE.

8000 Phoenix Parkway | O'Fallon, MO 63368-3827

Specifications and illustrations subject to change without notice and without incurring obligations. Printed in U.S.A (07/2011)

256D-0711 (Replaces 256D-0410)