



Submittal: DXH12PSK3IH	High Efficiency Heat Pump
-------------------------------	----------------------------------

Job Name:	Location:	Date:
-----------	-----------	-------

Purchaser:	Engineer:
------------	-----------

Submitted To:	For:
---------------	------

Unit Designation:	Schedule #:
-------------------	-------------

- Features:**
- Inverter-driven Compressor and Fan
 - Flared Piping Connections
 - Wireless Remote Controller Included
 - Anti-corrosion coils
 - Intelligent defrost
 - Auto-Restart
 - Easy diagnosis
 - Limited 5-year parts & 7-year compressor warranty



SYSTEM RATINGS	
Rated Cooling Capacity (Btu):	12,000
Minimum Cooling Capacity (Btu):	2,730
Maximum Cooling Capacity (Btu):	15,013
Rated Heating Capacity (Btu):	12,000
Minimum Heating Capacity (Btu):	3,071
Maximum Heating Capacity (Btu):	15,695
SEER:	24.5
EER:	13.0
HSPF:	9.5
COP:	13.0
METERING DEVICE	
Location	ODU
Type	EEV

OUTDOOR UNIT DATA	
Compressor	
Type:	Rotary
RLA:	7.00
Fan Motor	
Output Power(W):	30
RLA:	0.7
Sound Pressure (dBA):	52
Physical Characteristics	
Net Weight (lbs):	67.3
Dimensions (in)	
W:	31.5
H:	21.8
D:	13.7


Operation Range (Outdoor Ambient)	
Cooling (Min-Max)°F:	-20~122
Heating (Min-Max)°F:	-22~86

Power Supply	
Voltage (Min-Max):	187/253
Minimum Circuit Ampacity (MCA):	10
Max. Overcurrent Protection (MOCP):	15


Refrigerant Piping Data	
Refrigerant Type:	R-32
Pre-charged Amount (Oz):	28.2
Pre-Charged Length (ft):	24.6
Additional amount (Oz/ft.):	0.2
Max. Piping Length (ft):	65.6
Max. Piping Height (ft):	40.0
ODU Connection Size (Gas):	1/2"
ODU Connection Size (Liquid):	1/4"

Submittal: DXH12PSK3IH

Outdoor Unit Dimensions



Outdoor Unit Minimum Clearances



Specifications are subject to change without notice.



Submittal: DHH12PUK3IH High Efficiency Heat Pump

- Features:**
- Inverter-driven Variable Speed Blower
 - Flared Piping Connections
 - Wireless Remote Controller Included
 - Anti-corrosion coils
 - iFeel Operation
 - Air Filters Included
 - Turbo Cooling
 - Intelligent Preheating
 - Child Lock Function




Indoor Unit Data


Blower Data	
CFM (Max/Min):	400/212
Output (W):	55
RLA:	0.4
Capacitor Rating (µF):	N/A
Sound Pressure	
Cooling dB (A) (Min/Max):	20/43

Physical Characteristics	
Net Weight (lbs):	20.9
Dimensions (in.)	
W:	32.4
H:	11.5
D:	7.7
Piping Connection Size	
"Liquid":	1/4"
Gas:	1/2"

Dimensions



Clearances



Specifications & illustrations are subject to change without notice or incurring obligations.
 O'Fallon, MO ©Nordyne, LLC 2024. All Rights Reserved. 045G (11/24)

ODU SKU: 1049131
IDU SKU: 1049130