NuTone[®] Product Line



R

Drive

SEER

iQ

Drive

SEEE

N.C.

SFFR

Ľ

Furnaces FG7MQ 97+ AFUE Extra High Efficiency, Fully Modulating, Condensing, Upflow/Horizontal Gas Furnace, iSEER® technology, iQ Drive® Ready, 60,000 -120,000 BTUH Input, Variable-Speed Blower

95.1% Gas Furnaces

FG7T(C, L)-VS 95.1 AFUE Extra High Efficiency, Direct Vent or Non-Direct Vent, Condensing, 2-Stage (Upflow/ Horizontal, Downflow) Gas Furnace, iSEER technology, iQ Drive Ready, 60.000 - 120.000 BTUH Input, Variable-Speed Blower

FG7T(C, L) 95.1 AFUE Extra High Efficiency, Direct Vent or Non-Direct Vent, Condensing, 2-Stage (Upflow/ Horizontal, Downflow) Gas

Non-Direct Vent, Condensing, 2-Stage (Upflow/ Horizontal, Downflow) Gas Furnace, iSEER technology, 60,000 - 120,000 BTUH Input



B.T.S.

N.C.

N.T.

iR

Drive

SFF

92.1% Gas Furnaces

FG7S(C, L) 92.1 AFUE Extra High Efficiency, Direct Vent or Non-Direct Vent, Condensing, 1-Stage, (Upflow/ Horizontal, Downflow) Gas Furnace, 38,000 - 120.000 BTUH

Input

80% Gas Furnaces

FG7T(A, K)-VS 80 AFUE High Efficiency, 2-Stage (Upflow/Horizontal, Downflow) Gas Furnace, iSEER technology, iQ Drive Ready, 60,000 - 140,000 BTUH Input, Variable-Speed Blower

80% Gas Furnaces FG7T(A, K) 80 AFUE High

Efficiency, 2-Stage (Upflow/Horizontal, Downflow) Gas Furnace, iSEER technology, 60,000 - 140,000 BTUH Input

FG7S(A, K) 80 AFUE High Efficiency, 1-Stage, (Upflow/Horizontal, Downflow) Gas Furnace, 45,000 - 126,000 BTUH Input

Packaged Systems

All packaged systems feature Anteater® or Anteater MC® Micro-Channel evaporator coils



Gas/Electric, 2-Stage Heat & Cool, Variable-Speed Blower, Square Duct Connections, Convertible Airflow, 15 SEER, 80% AFUE, 12 EER, 2 - 5 Ton, 72,000 - 120,000 BTUH Input

Packaged Systems

SEER

Sec. Property

R6GI Single Packaged Gas/Electric, iQ Drive Technology, functions with 5-Stage output from 2-Stage thermostat, Variable-Speed ECM Blower, Square Duct Connections, Convertible Airflow, 20 SEER, 81% AFUE, Up to 13 EER, 2 - 5 Ton, 52,000 -120,000 BTUH Input

DF6SF-A

Single Packaged iHybrid[™] Dual Fuel, Up to 2-Stage Heat/ 2-Stage Cool, Variable-Speed Blower, Square Duct Connections, Convertible Airflow, 15 SEER, 8.0 HSPF, 80% AFUE, 12 EER, 2 - 5 Ton, 72,000 -120,000 BTUH Input



Single Packaged Gas/ Electric, 2-Stage Heat, Variable-Speed ECM Blower, Square Duct Connections, Convertible Airflow, 14 SEER, 95% AFUE, up to 12 EER, 2 - 5 Ton, 39,000 -100,000 BTUH Input

R8GD

Single Packaged Gas/ Electric, Square Duct Connections, Convertible Airflow, 13 SEER, 80% AFUE, 2 - 5 Ton, 45,000 - 120,000 BTUH Input

Packaged Systems



R

Drive

Hvbrid

Ľ

Single Packaged Air Conditioner, 2-Stage, ECM Blower, Round Duct Connections, 15 SEER, 12 EER, 2 - 5 Ton



P6SD Single Packaged Air Conditioner, Square Duct Connections, Convertible Airflow, 13 SEER, 3, 4 and 5 Ton



P7RD-A Single Packaged Air Conditioner, Round Duct Connections, 13 SEER, 2 - 5 Ton

Q7RD-A Single Packaged Heat Pump, Round Duct Connections, 13 SEER, 7.7 HSPF, 2 - 5 Ton



ENERGY STAR[®] certification is awarded to products designed to reduce energy consumption and utility costs.

To qualify, gas/electric, iHybrid, air conditioner and heat pump packaged systems must have a Seasonal Energy Efficiency Ratio (SEER) rating of 14.0 or higher and an Energy Efficiency Ratio (EER) of 11.0 or higher. Packaged heat pumps must also have a Heating Seasonal Performance Factor (HSPF) of 8.0 or higher.

Split system air conditioners and heat pumps must have a 14.5 SEER rating or higher and an EER of 12.0 or higher. Split system heat pumps must also have an HSPF of 8.2 or higher.





NuTone units offer a 10 year limited warranty on all parts when registered. Plus the NuTone Quality Pledge on select models, which states if within the first 10 years the compressor or furnace heat exchanger fails NuTone will replace the entire unit, registration required. Air handlers and coils carry a 5-year all parts limited warranty and when installed with a matched outdoor unit, will carry the outdoor system warranty. J model air conditioners carry a 5-year all parts limited warranty and a 5-year compressor warranty. See warranty for details.



Split System Air Conditioners

FS4BI

Ultra High Efficiency, Up to 25.5 SEER, Air Conditioner, iQ Drive® Technology, 2, 3 and 4 Ton Capacity

Ľ

Ľ

Drive

FS4BF

Extra High Efficiency, Up to 16 SEER, 2-Stage, Air Conditioner, 2, 3, 4 and 5 Ton Capacity, Anteater MC[®] Micro-Channel

ES6BF

Extra High Efficiency, Up to 16 SEER, 1-Stage, Air Conditioner, 2, 2-1/2, 3, 3-1/2 and 4 Ton Capacity, Anteater MC Micro-Channel

FS4BE/ES4BE

High Efficiency, Up to 15 SEER, Air Conditioner, 1-1/2 -5 Ton Capacity, Anteater MC Micro-Channel

FS4BD/ES4BD

High Efficiency, Up to 14 SEER, Air Conditioner, 1-1/2 -5 Ton Capacity, Anteater MC Micro-Channel

JS6BD

High Efficiency, Up to 14 SEER, Builder's Series, Air Conditioner, 1-1/2 - 3 Ton Capacity, Anteater MC Micro-Channel

NuTone

Split System Heat Pumps FT4BI Ultra High Efficiency, Up to 22 SEER,

Up to 22 SEER, 10.0 HSPF, Heat Pump, iQ Drive Technology, 2, 3 and 4 Ton Capacity

Ľ

Drive

Drive



FT4BF/ET4BF Extra High Efficiency, Up to 16 SEER, 9.0 HSPF, 2-Stage, Heat Pump, 2, 3, 4 and 5 Ton Capacity

FT4BE/ET4BE High Efficiency, Up to 15 SEER, 8.5 HSPF, Heat Pump, 1-1/2 - 5 Ton Capacity, Anteater MC Micro-Channel

FT4BD/ET4BD High Efficiency, Up to 14 SEER, 8.5 HSPF, Heat Pump, 1-1/2 - 5 Ton Capacity, Anteater MC Micro-Channel

* FT4BF models only are rated ecoLogic

Specifications and illustrations subject to change without incurring obligation. www.nutonehvac.com

iQ Drive, iSEER, ecoLogic, Anteater and Anteater MC are registered trademarks of NORDYNE. iHybrid and iQ Zone are trademarks of NORDYNE. © 2014 NORDYNE. All Rights Reserved. Printed in U.S.A. 696C-0614

Air Handlers

B6VMAI iQ Drive Only, Multi-Poised, Vertical/Horizontal, Upflow/ Downflow, Variable-Speed, Air Handler, Anteater®, Electronic TXV

B6VMAX

Multi-Poised, Vertical/ Horizontal, Variable-Speed, Air Handler, TXV, Anteater

B6BMMX

Multi-Poised, Vertical/ Horizontal, Multi-Speed, Air Handler, TXV, Anteater MC Micro-Channel

B6BMM0 Multi-Speed, Multi-Poised, Air Handler, Anteater MC Micro-Channel

B6EMMX ECM Fixed-Speed Motor, Multi-Poised, Air Handler, TXV, Anteater MC Micro-Channel

B6VMMX ECM Variable-Speed Motor, Multi-Poised, Air Handler, TXV, Anteater MC Micro-Channel

B6BW Vertical Wall Mount, Air Handler, Anteater MC Micro-Channel

B6EW Vertical Wall Mount, Multi-Speed, ECM Motor, Air Handler, TXV, Anteater MC Micro-Channel

MB7BM Multi-Poised, Multi-Speed Modular Blower (matched with a cased coil easily creates a 2 piece Air Handler)

MB7EM Energy Efficient Model

MB7VM Variable-Speed Model

Indoor Coils

iQ

Drive

.

C7B(A, H)MO Anteater MC Micro-Channel A, B, C and D sizes available in various capacities Cased & Uncased, Vertical/Horizontal Multi-poised versions available

C7BHMX

Factory-installed TXV, Anteater MC Micro-Channel A, B, C and D sizes available in various capacities Cased Horizontal

C6BA-F/C6BH-(I, X) A, B, C and D

sizes available in various capacities, Anteater Cased, Uncased & Horizontal

& Horizontal versions available

System Accessories

Air Cleaners Electronic Air Cleaner Lifetime filtering systems, removes household allergens and pollutants down to .01 microns

Media Air Cleaner MERV 14, long life media filter, removes airborne particles down to 0.3 microns

1" Electronic Air Cleaner Easy to maintain, 24V, 95% efficient down to .01 microns

HEPA Air Cleaner High efficiency air filtration, captures 99.97% of harmful airborne pollutants

System Accessories



UV object purifiers and Photo Catalytic Oxidation (PCO) units remove mold, bacteria, and viruses that are found in the air stream and also remove odors from the home

Thermostats

Universal, Programmable 7-day, 24V, digital, up to 3 heat/2 cool, backlit display + keypad, auto or manual changeover

Humidifiers Eliminates parched,

dry air which can cause dry nose & throat, itchy & dry skin by delivering humidity and reducing static electricity



Ventilator Brings fresh air from outside to the inside of your home to dilute pollutants and replace stale air



Zoning Total comfort for every room by creating custom comfort zones

44.50-00

and Distances

