

QUICK REFERENCE DATA

*T4BD Series - Residential Split System Heat Pump

MODEL NUMBER: *T4BD			018K	024K	030K	036K	042K	048K	060K
Electrical Data	Volts-Cycles-Phase (1)		208 / 230 - 60 - 1						
	Total Amps		10.2	14.6	15.3	17.8	19.4	23.2	27.7
	Delay Fuse Max. (2)		20	30	30	35	40	50	60
	Min. Circuit Ampacity		12.4	18.0	18.8	22.0	23.9	28.7	34.3
Condenser Data	Coil	Area	17.7	20.3	22.8	25.3	22.8	25.3	25.3
		Rows-FPI	1-18	1-18	1-20	1-20	2-16	2-16	2-16
		Tube Dia	3/8" O.D.						
	Fan Motor	Type	PSC						
		Amps	1.2	1.2	1.2	1.2	1.46	1.46	1.46
		HP	0.2	0.2	0.2	0.2	0.25	0.25	0.25
	Compressor Data	RLA	9	13.4	14.1	16.6	17.9	21.8	26.2
		LRA	48	58.3	73	79	112	117	134
Refrigerant suction line O.D NOTE: Liquid line is 3/8" O.D. for entire length.		0-24 ft.	3/4"	3/4"	3/4"	7/8"	7/8"	7/8"	7/8"
		25-39 ft.	3/4"	3/4"	3/4"	7/8"	7/8"	7/8"	1-1/8" (3)
		40-75 ft.	3/4"	3/4"	3/4"	7/8"	7/8"	7/8"	1-1/8" (3)
Refrigerant charge R-410A in ounces for outdoor unit & 15' lineset. (4)			98	120	140	154	237	232	248
Approximate Weight (lbs.)		Net	166	171	176	181	247	280	290
		Ship	175	180	185	190	260	295	305

(1) Operating Voltage Range: 187v min. — 253v max.

(2) HACR Type Circuit Breakers may be used.

(3) Requires 7/8" to 1-1/8" adapter from unit to line.

(4) Additional charge for line sets above 15 feet. Values based on suction line as follows with 3/8" liquid line.

(a) 3/4" = 0.6 oz. per additional foot.

(b) 7/8" = 0.7 oz. per additional foot.

(c) 1 1/8" = 0.8 oz. per additional foot.

Table 1. Electrical Specifications & Physical Data

Thermostat Wire Gauge	Recommended T-Stat Wire Unit to T-Stat (Length in FT)	
	2-Wire (Heating)	5-Wire (Heating/Cooling)
24	55	25
22	90	45
20	140	70
18	225	110

Table 2. Thermostat Wire Gauge




Figure 1. Clearance Requirements

Model DT4BD Shown			
MODEL NUMBER	HEIGHT (H)	WIDTH (W)	DEPTH (D)
*T4BD-018K	31 1/2"	30 3/4"	30 3/4"
*T4BD-024K	35 1/2"	30 3/4"	30 3/4"
*T4BD-030K	39 1/2"	30 3/4"	30 3/4"
*T4BD-036K	43 1/2"	30 3/4"	30 3/4"
*T4BD-042K	39 1/2"	30 3/4"	30 3/4"
*T4BD-048K	43 1/2"	30 3/4"	30 3/4"
*T4BD-060K	43 1/2"	30 3/4"	30 3/4"

Table 3. Unit Dimensions

Instructions:

1. Find the column for the model of outdoor unit that is being installed.
2. Find the row for the model of the indoor unit that is being installed.
3. Find the cell in the table in which this row and column meet. In this cell the appropriate orifice / TXV and charge addition for this match are listed. If the text in this cell is BOLD, then a change of orifice is necessary.
4. If a change in restrictor is necessary, then the appropriate restrictor will already be supplied with the outdoor unit.

Examples:

- For the *T4BD-018K / GB5BMM024K-B match, the restrictor will need to be changed to the .053" and 14 ounces of additional charge will need to be added. (CHANGE IN CHARGE AND ORIFICE)
- For the *T4BD-048K / B6EMMX48K-C match, the appropriate TXV is the 669852, the appropriate outdoor restrictor is the 0.058", and 8 ounces of additional charge will need to be added. (CHANGE IN CHARGE AND OUTDOOR ORIFICE)

ID Restrictor Installed With ID Unit	Model Number: *T4BD		018K	024K	030K	036K	042K	048K	060K	
	ID Restrictor Supplied With OD Unit:		0.050, 0.053	0.056, 0.055	0.061	0.067	0.073	0.079, 0.081	0.087, 0.094	
	OD Restrictor Supplied With OD Unit:		0.035	0.041	0.048	0.055	0.055	0.060	0.068	
	Outdoor Unit BOM Charge (Oz.)		98	120	140	154	237	232	248	
	MODELS		SUPPLIED WITH ID	REQUIRED RESTRICTOR OR TXV / CHARGE ADDITION (OZ)						
	B4VM									
	B4VM-X24K-A	669564	669564 / 14	669564 / 18	--	--	--	--	--	
	B4VM-X24K-B	669564	669564 / 14	669564 / 18	--	--	--	--	--	
	B4VM-X30K-A	669565	--	--	669565 / 5	--	--	--	--	
	B4VM-X30K-B	669565	--	--	669565 / 5	--	--	--	--	
	B4VM-X36K-B	669566	--	--	--	669566 / 12	--	--	--	
	B4VM-X48K-B	669568	--	--	--	--	669568 / 6	--	--	
	B4VM-X48K-C	669568	--	--	--	--	669568 / 6	669568 / 16	--	
	B4VM-X60K-C	669578	--	--	--	--	--	--	669578 / 0	
	GB5BM-0									
	GB5BM-024K-A	0.055	0.053 / 14	0.055 / 18	--	--	--	--	--	
	GB5BM-024K-B	0.055	0.053 / 14	0.055 / 18	--	--	--	--	--	
	GB5BM-030K-A	0.065	--	--	0.065 / 5	--	--	--	--	
	GB5BM-030K-B	0.065	--	0.055 / 18	0.065 / 5	--	--	--	--	
	GB5BM-036A-B	0.073	--	--	--	0.073 / 12	--	--	--	
	GB5BM-036K-B	0.073	--	--	--	0.073 / 12	--	--	--	
	GB5BM-042K-B	0.077	--	--	--	--	0.077 / 6	--	--	
	GB5BM-048K-C	0.080	--	--	--	--	--	0.080 / 16	--	
	GB5BM-060K-C	0.089	--	--	--	--	--	--	0.089 / 0	
	GB5BMM									
	GB5BMM024K-A	0.055	0.053 / 14	0.055 / 10	--	--	--	--	--	
	GB5BMM024K-B	0.055	0.053 / 14	0.055 / 10	--	--	--	--	--	
	GB5BMM030K-A	0.062	--	--	0.062 / 0	--	--	--	--	
	GB5BMM030K-B	0.062	--	--	0.062 / 0	--	--	--	--	
	GB5BMM036K-B	0.067	--	--	--	0.067 / 4	--	--	--	
	GB5BMM042K-B	0.074	--	--	--	--	0.074 / 11	--	--	
	GB5BMM048K-B	0.079	--	--	--	--	--	0.079 / 16	--	
	GB5BMM048K-C	0.079	--	--	--	--	--	0.079 / 16	--	
	GB5BMM060K-C	0.087	--	--	--	--	--	--	0.087 / 0	
	B5BM-X									
	B5B(M,V)-X24K-A	669564	669564 / 14	669564 / 18	--	--	--	--	--	
	B5B(M,V)-X24K-B	669564	669564 / 14	669564 / 18	--	--	--	--	--	
	B5B(M,V)-X30K-A	669565	--	--	669565 / 5	--	--	--	--	
	B5B(M,V)-X30K-B	669565	--	669565 / 18	669565 / 5	--	--	--	--	
	B5B(M,V)-X36K-B	669566	--	--	--	669566 / 12	--	--	--	
	B5B(M,V)-X42K-B	669567	--	--	--	--	669567 / 6	--	--	
	B5B(M,V)-X48K-B	669568	--	--	--	--	--	669568 / 16	--	
	B5B(M,V)-X48K-C	669568	--	--	--	--	--	669568 / 16	--	
	B5B(M,V)-X60K-C	669578	--	--	--	--	--	--	669578 / 0	

NOTES:

- The charges listed are only valid for the standard 15' lineset.
- Numbers listed as 0.*** are restrictor diameters, while numbers listed as 669*** are TXV part numbers.
- Gray cells require the outdoor restrictor to be changed as well. See Table 5.

Table 4. Restrictor or TXV / Charge Addition (Oz)

Instructions:

1. Find the column for the model of outdoor unit that is being installed.
2. Find the row for the model of the indoor unit that is being installed.
3. Find the cell in the table in which this row and column meet. In this cell the appropriate orifice / TXV and charge addition for this match are listed. If the text in this cell is BOLD, then a change of orifice is necessary.
4. If a change in restrictor is necessary, then the appropriate restrictor will already be supplied with the outdoor unit.

Examples:

- For the *T4BD-018K / GB5BMM024K-B match, the restrictor will need to be changed to the .053" and 14 ounces of additional charge will need to be added. (CHANGE IN CHARGE AND ORIFICE)
- For the *T4BD-048K / B6EMMX48K-C match, the appropriate TXV is the 669852, the appropriate outdoor restrictor is the 0.058", and 8 ounces of additional charge will need to be added. (CHANGE IN CHARGE AND OUTDOOR ORIFICE)

ID Restrictor Installed With ID Unit	Model Number: *T4BD		018K	024K	030K	036K	042K	048K	060K	
	ID Restrictor Supplied With OD Unit:		0.050, 0.053	0.056, 0.055	0.061	0.067	0.073	0.079, 0.081	0.087, 0.094	
	OD Restrictor Supplied With OD Unit:		0.035	0.041	0.048	0.055	0.055	0.060	0.068	
	Outdoor Unit BOM Charge (Oz.)		98	120	140	154	237	232	248	
	MODELS		SUPPLIED WITH ID	REQUIRED RESTRICTOR OR TXV / CHARGE ADDITION (OZ)						
	GB5BW									
	GB5BW-024K(*)	0.057 †	0.050 / 14	0.057 / 18	--	--	--	--	--	
	GB5BW-030K(*)	0.063 #	0.050 / 14	0.057 / 18	0.065 / 5	--	--	--	--	
	B6BM									
	B6BMM024K-A	0.055	0.053 / 14	0.055 / 10	--	--	--	--	--	
	B6BMM024K-B	0.055	0.053 / 14	0.055 / 10	--	--	--	--	--	
	B6BMM030K-A	0.062	--	--	0.062 / 0	--	--	--	--	
	B6BMM030K-B	0.062	--	--	0.062 / 0	--	--	--	--	
	B6BMM036K-B	0.067	--	--	--	0.067 / 4	--	--	--	
	B6BMM042K-B	0.074	--	--	--	--	0.074 / 11	--	--	
	B6BMM048K-B	0.079	--	--	--	--	--	0.079 / 16	--	
	B6BMM048K-C	0.079	--	--	--	--	--	0.079 / 16	--	
	B6BMM060K-C	0.087	--	--	--	--	--	--	0.087 / 0	
	B6BW									
	B6BW-018K(*)	0.056	0.050 / 25	--	--	--	--	--	--	
	B6BW-024K(*)	0.057	--	0.055 / 18	--	--	--	--	--	
	B6BW-030K(*)	0.060	--	--	0.060 / 3	--	--	--	--	
	B6BW-036K(*)	0.069	--	--	--	0.067 / 0	--	--	--	
	B6EM									
	B6EMMX24K-A	669564	669564 / 0	669564 / 10	--	--	--	--	--	
	B6EMMX24K-B	669564	669564 / 0	669564 / 10	--	--	--	--	--	
	B6EMMX30K-A	669565	--	--	669565 / 9	--	--	--	--	
	B6EMMX30K-B	669565	--	--	669565 / 9	--	--	--	--	
	B6EMMX36K-B	669566	--	--	--	669566 / 7	--	--	--	
	B6EMMX42K-B	669567	--	--	--	--	669567 / 0	--	--	
	B6EMMX48K-C	669852	--	--	--	--	669852 / -26‡	669852 / 8	--	
	B6EMMX60K-C	669578	--	--	--	--	--	--	669578 / 5	
	B6VM									
	B6VMAX24K-A	669564	669564 / 14	669564 / 18	--	--	--	--	--	
	B6VMAX24K-B	669564	669564 / 14	669564 / 18	--	--	--	--	--	
	B6VMAX30K-A	669565	--	--	669565 / 5	--	--	--	--	
	B6VMAX30K-B	669565	--	669565 / 18	669565 / 5	--	--	--	--	
	B6VMAX36K-B	669566	--	--	--	669566 / 12	--	--	--	
	B6VMAX42K-B	669567	--	--	--	--	669567 / 6	--	--	
	B6VMAX48K-C	669568	--	--	--	--	669568 / 6	669568 / 16	--	
B6VMAX60K-C	669578	--	--	--	--	--	--	669578 / 0		

NOTES:

- The charges listed are only valid for the standard 15' lineset.
- Numbers listed as 0.*** are restrictor diameters, while numbers listed as 669*** are TXV part numbers.
- Gray cells require the outdoor restrictor to be changed as well. See Table 5.
- ‡ This is a charge reduction. Remove 26 ounces from the initial charge that came with the unit.
- † The GB5BW-024K unit is supplied with an extra 0.050 restrictor for use with the *T4BD-018K.
- # The GB5BW-030K unit is supplied with extra 0.050, 0.057, and 0.065 restrictors.

Table 4. Restrictor or TXV / Charge Addition (Oz) - Continued

ID Restrictor Installed With ID Unit	Model Number: *T4BD		018K	024K	030K	036K	042K	048K	060K
	ID Restrictor Supplied With OD Unit:	0.050, 0.053	0.056, 0.055	0.061	0.067	0.073	0.079, 0.081	0.087, 0.094	
	OD Restrictor Supplied With OD Unit:		0.035	0.041	0.048	0.055	0.055	0.060	0.068
	Outdoor Unit BOM Charge (Oz.)		98	120	140	154	237	232	248
	MODELS	SUPPLIED WITH ID	REQUIRED RESTRICTOR OR TXV / CHARGE ADDITION (OZ)						
	C6								
	C6B(A,H)-X24(C,U)-A	669564	669564 / 14	669564 / 18	--	--	--	--	--
	C6B(A,H)-X24(C,U)-B	669681	669681 / 14	669681 / 18	--	--	--	--	--
	C6B(A,H)-X30(C,U)-A	669565	--	--	669565 / 5	--	--	--	--
	C6B(A,H)-X30(C,U)-B	669682	--	--	669682 / 5	--	--	--	--
	C6B(A,H)-X30(C,U)-C	669682	--	--	669682 / 5	--	--	--	--
	C6B(A,H)-X35(C,U)-B	669683	--	--	--	669683 / 12	--	--	--
	C6B(A,H)-X36(C,U)-B	669683	--	--	--	669683 / 12	--	--	--
	C6B(A,H)-X36(C,U)-C	669683	--	--	--	669683 / 12	--	--	--
	C6B(A,H)-X42(C,U)-B	669684	--	--	--	--	669684 / 6	--	--
	C6B(A,H)-X42(C,U)-C	669684	--	--	--	--	669684 / 6	--	--
	C6B(A,H)-X42(C,U)-D	669684	--	--	--	--	669684 / 6	--	--
	C6B(A,H)-X47(C,U)-C	669852	--	--	--	--	--	669852 / 16	--
	C6B(A,H)-X48(C,U)-C	669852	--	--	--	--	--	669852 / 16	--
	C6B(A,H)-X48(C,U)-D	669852	--	--	--	--	--	669852 / 16	--
	C7-0								
	C7B(A,H)M01824(C,U)-A	0.048	0.053 / 12	0.056 / 0	--	--	--	--	--
	C7B(A,H)M01824(C,U)-B	0.055	0.053 / 12	0.056 / 0	--	--	--	--	--
	C7B(A,H)M030(C,U)-C	0.061	--	--	0.061 / 7	--	--	--	--
	C7B(A,H)M03036(C,U)-A	0.061	--	--	0.061 / 7	--	--	--	--
C7B(A,H)M03036(C,U)-B	0.067	--	--	0.061 / 7	0.067 / 4	--	--	--	
C7B(A,H)M03642(C,U)-B	0.071	--	--	--	0.067 / 4	0.073 / 0	--	--	
C7B(A,H)M03648(C,U)-C	0.067	--	--	--	0.067 / 4	0.073 / 0	0.081 / 0	--	
C7B(A,H)M042(C,U)-D	0.071	--	--	--	--	0.073 / 0	--	--	
C7B(A,H)M048(C,U)-C	0.077	--	--	--	--	--	0.079 / 0	--	
C7B(A,H)M048(C,U)-D	0.087	--	--	--	--	--	0.079 / 0	--	

NOTES:

- The charges listed are only valid for the standard 15' lineset.
- Numbers listed as 0.*** are restrictor diameters, while numbers listed as 669*** are TXV part numbers.
- Gray cells require the outdoor restrictor to be changed as well. See Table 5.

Table 4. Restrictor or TXV / Charge Addition (Oz) - Continued

OD Unit	ID Unit	Factory Installed Restrictor	Correct Outdoor Restrictor
T4BD-018K	B6BW-018K()	0.035	0.044
*T4BD-018K	C7B(A,H)M01824(C,U)-(A,B)	0.035	0.039
T4BD-024K	B6BW-024K()	0.041	0.047
T4BD-030K	B6BW-030K()	0.048	0.050
T4BD-036K	B6BW-036K()	0.053	0.057
*T4BD-048K	B6EMMX48K-C	0.060	0.058
*T4BD-048K	C7B(A,H)M03648(C,U)-C	0.060	0.064
*T4BD-048K	C7B(A,H)M048(C,U)-(C,D)	0.060	0.064

Table 5. *T4BD Outdoor Restrictor Changes

